

VOLTANA 0

5136

Optic	5136
Protector	Flat glass
Source	8 LG Innotek 3535 Gen4
Matrix	395222



Characteristics

416	156	91	2.6	IP 66	IK 08	I EU	0.012
Length (mm)	Width (mm)	Height (mm)	Weight (kg)	Tightness level*	Impact resistance*	Electrical class*	CxS (m²)

* According to IEC-EN60598 and IEC-EN62262

Features

Entry Level cost-effective luminaire family

- Cost-effective and efficient lighting solution for a fast return on investment
- LensoFlex@2 photometric engine with photometry adapted to various applications
- 5 sizes for flexibility
- Designed to incorporate Owllet control and sensor solutions
- ThermiX@: withstands high temperatures (Ta 50°C)
- Mounting : side entry (42-60 mm) with inclination steps -10° to +5°
- Surge protection 10kV (optional)

Information for 1000 lm matrix

Efficacy (%)	84.0	G Class (EN 13201-2)	G3	Aperture 90-270°	8 - X
DLOR (%)	84.0	G* (EN 13201 2015)	G*3	I 70-80-90-95 (cd)	688 - 74 - X - X
ULOR (%)	0.0	Imax (cd)	694		
UWLR (%)	0.0	Aperture 0-180°	43 - 43		

Photometrical characteristics

LED count	Colour code	Colour name	CCT	CRI	Current (mA)	Luminaire power (W)	Source flux (lm)	Luminaire output flux (lm)	Luminaire efficacy (lm/W)	Peak (cd)	BUG Rating	Voltage (V)
						Ambient temp = 25°						
8	WW	Warm White	3000	80	350	10	1168	981	98	811	B1 U0 G0	230
8	WW	Warm White	3000	80	500	14	1577	1325	95	1095	B1 U0 G0	230
8	WW	Warm White	3000	80	700	20	2056	1727	86	1427	B1 U0 G1	230
8	WW	Warm White	3000	80	1000	30	2651	2228	74	1841	B1 U0 G1	230
8	NW	Neutral White	4000	70	350	10	1280	1075	108	889	B1 U0 G0	230
8	NW	Neutral White	4000	70	500	14	1728	1452	104	1200	B1 U0 G0	230
8	NW	Neutral White	4000	70	700	20	2253	1893	95	1564	B1 U0 G1	230
8	NW	Neutral White	4000	70	1000	30	2906	2441	81	2018	B1 U0 G1	230

Tolerance on flux +- 7% - Tolerance on power +- 5%

Summary

CONCEPT

Family of 6 road LED luminaires

Recommended installation height: between 4.00 and 12.00m

For optimal heat dissipation, the driver and LED engine are in separate compartments and juxtaposed in a horizontal section

HOUSING & FINISH

- Housing in high-pressure, die-cast aluminium, polyester powder coated
- Colour: RAL 7038

INSTALLATION

- Luminaire can be fixed by side-entry with a clamp, suitable for 42-60mm diameter
- Built-in inclination steps: -10°, -5°, 0°, 5°
- Post-top adapter diameter 48-60mm or 76mm, tightened with 2 stainless steel screws
- Direct access to the driver compartment with screws for easy maintenance on-site

OPTICAL UNIT

- Protected against lens degradation by 5mm thick extra-clear hardened glass
- Flatbed PCB with acrylic lens overlay principle
- Various photometric distributions: from narrow road to motorway, medium and large area
- CRI > 70
- ULOR: 0%

LED lumen depreciation

- Lifetime residual flux @ Tq=25°C @ 100.000 hrs: 350mA & 500mA: 90%; 700mA: 80%; 1A: 70%

ELECTRICAL

- Class I or Class II
- Input voltage: 120-277V - 50-60Hz
- Power factor > 90% at full load
- Surge protection: 4kV minimum (10kV + 10kA optional)
- Thermal protection on LED PCBA (see Thermix concept)

STANDARDS & CERTIFICATIONS


- CE
- ENEC
- LM79-80
- ROHS
- Certified for 3G vibration
- All measurements in ISO17025 accredited laboratory


OPTIONS

- Other RAL or AKZO colours
- Back Light control system
- OWLET remote management
- Custom dimming profile


VOLTANA 0 - 5136 - 8 LG Innotech 3535 Gen4 - Flat glass - 395222

- Photocell







Isolux




K-Curve






I - Medium

Luminaire classification system (LCS)



Intensity diagram in max Cone and in CPlane



Copyright © 2019 Schröder SA. All rights reserved. Specifications are of an indicative nature and subject to change without notice.

<http://www.schreder.com>