



TECHNICAL DATA SHEET

CLASSIC CX 3000 SAE 30

PRODUCT DESCRIPTION AND USE

NP CLASSIC CX 3000 SAE 30, is a mono grade engine oil produced by adding special additive packages to mineral based base oils. It is used in crankcases of diesel engines operating under light and medium conditions.

FEATURES AND BENEFITS

- ✓ With the help of the detergent-dispersant additives it contains, it prevents the formation and accumulation of sediment in the environment and keeps the engine clean.
- ✓ Protects the engine under heavy load against oxidation and wear thanks to its high film resistance.
- ✓ Thanks to the additives it contains, it prevents rusting and corrosion on metal surfaces.
- ✓ Reduces the chemical effect of acidic residues in the combustion chamber with the film layer it forms on metal surfaces.
- ✓ Prevents performance loss by keeping the engine clean.

MEETS THE SPECIFICATION AND APPROVALS

API CD/SF

TYPICAL PROPERTIES

TEST	UNIT	METOD	TYPICAL VALUES
Density ,@ 15 °C	g/cm ³	ASTM 4052	0,88
K. Viscosity,@ 100 °C	cSt	ASTM D 445	9,3-12,5
Viscosity Index		ASTM D 2270	95
Flash Point	°C	ASTM D 92	225
Pour Point	°C	ASTM D 97	-15

*The above values may vary slightly according to production.

HEALTH, SAFETY AND ENVIRONMENTAL RECOMMENDATIONS

Should not make contact with the skin, should not be swallowed and vapors should not be inhaled. In case of contact with the skin or eyes, wash with plenty of water and seek medical attention if necessary. When swallowed, victim should not be vomiting and immediate medical attention should be sought. When the vapors are inhaled, breathe heavily in fresh air and, if necessary, seek medical attention. Used oils should not be disposed to garbage, sewage and should be collected by licensed waste oil collectors. It should not be mixed with any petroleum products or chemicals. It should not be burned in furnaces and boilers. Should be kept away from children. Empty containers should not be thrown to the garbage or left in the environment and should be delivered to licensed recycling companies.

For more information, please refer to the 'Material Safety Data Sheet'

STORAGE CONDITIONS

Packaging should not be exposed to extended periods of direct sunlight. Packaging should not be in contact with water. Oils should not come into contact with dust and should be kept away from dusty environments. Ambient temperature should not exceed 40 ° C. The user is solely responsible for using the product according to its purpose and for complying with the laws and regulations in effect. Nil Petrol San. Ve Tic A.Ş. may not be held responsible for damages and loss due to the use of the product outside its normal or intended uses or due to inherent dangers of the product and its consequences.

TYPES OF PACKING

16L, 200 L, 1000L