



NetApp Solution Technical Report

Manually Designed Solution

Report Generated:

19-Mar-2025

Project ID:

157dd848

TABLE OF CONTENTS

- 1 Business Requirements..... 3**
- 2 Solution Summary 4**
 - 2.1 Proposed Solution Summary4
- 3 Solution Details..... 5**
 - 3.1 System Details5
 - 3.2 Environmental Details6
 - 3.3 Storage Availability Zone: netapp1/netapp2.....7
 - 3.4 Storage Availability Zone9
 - 3.5 Workload Descriptions10
- 4 Environmental Certifications 11**
 - 4.1 Statements & Certifications11
- 5 Copyright 12**


1 Business Requirements

[Use this section to document the customer's high-level business requirements]

2 Solution Summary

2.1 Proposed Solution Summary

This is a summary of what the proposed solution will deliver.

THROUGHPUT	RAW CAPACITY	STORAGE EFFICIENCY***
500,000 IOPS / 7,812.50 MB/s	734.4 TB	2 : 1
AVERAGE UTILIZATION	USABLE CAPACITY	EFFECTIVE CAPACITY***
56%	567.6 TiB (623TB)	1,135.1934 TiB
MAXIMUM THROUGHPUT*	RAW CAPACITY HEADROOM**	USABLE VS EFFECTIVE
774,944 IOPS / 12,108.50 MB/s	0GB	 567.6 TiB 1,135.1934 TiB
*assumes best practice configuration of aggregates and workload to aggregate mapping	**assumes future expansion using drives of same capacity	***assumes use of storage efficiency technologies like compression and deduplication ***Lowest efficiencies have been applied to unused capacity within the cluster.

Note:Usable and effective capacity is calculated and reported in base-2 format which aligns with values reported in ONTAP CLI, Storage Manager, and Unified Manager. It should be noted that ONTAP CLI displays base-2 capacity values, but labels these values using base-10 descriptors (e.g. GB/TB/PB).

CONFIGURATION				ENVIRONMENTAL	
Model:	ASA A90A	OnboardEthernetPorts:	0	Rack Units:	4 U
Nodes:	2	Onboard UTA2Ports:	0	System Weight:	118.00 lbs
				AC Power:	2433.35 W
Total Drives:	48	OnboardSASPorts:	0	Current Draw:	13.88 A
Drive Type:	15.3 TB NVMe SSD	Expansion Slots:	18	BTU/hr:	8304.79
Cluster Switches:	N/A	StgeSwitches:	N/A		

3 Solution Details

3.1 System Details

For rack elevation, please refer to the Storage Solution SVG Diagram

cluster1: netapp1/netapp2

Bill Of Materials				Total
	Description		Part Number	Qty
Systems				
	ASA A90A w/ 48x15.3TB NVMe SSD SED	9.16.1 ONTAP	X4028A	1
	Grand Total			1
Storage				
	Grand Total			0
Adapter Cards/ Flash Cache				
	Grand Total			0

3.2 Environmental Details

Line Voltage: 220

System Components	Qty	Rack Units	Current (Amps)		AC Power (Watts)		AC Power (VA)		Thermal Rating (BTU/hr)		Power (kWh/year)	
			Typical	Worst	Typical	Worst	Typical	Worst	Typical	Worst	Typical	Worst
ASA A90A w/ 48x15.3 TB NVMe SSDX4028A(2xControllers, 1xChassis)	1	4	13.88	18.51	2,433.35	3,638.33	2,561.42	3,829.82	8,304.79	12,417.27	21,330.29	31,892.92
Total	1	4	13.88	18.51	2,433.35	3,638.33	2,561.42	3,829.82	8,304.79	12,417.27	21,330.29	31,892.92

Median Power Usage

System Components	Qty	Median Current (Amps)	Median AC Power (Watts)	Median AC Power (VA)	Median Thermal Rating (BTU/hr)	Median Power (kWh/year)
ASA A90A w/ 48x15.3 TB NVMe SSDX4028A(2xControllers, 1xChassis)	1	9.31	1,862.2	1,960.21	6,350.1	16,323.7
Total	1	9.31	1,862.2	1,960.21	6,350.1	16,323.7

Note: Median power is based on actual power numbers reported by install base systems of similar configuration and represent the midpoint where half of the similar configurations consume less power and the other half consume more power. Typical and Worst-case power numbers are calculated based on product specifications and spot checked for accuracy. Typical power values are used when median power values are not available.

3.3 Storage Availability Zone: netapp1/netapp2

The information below provides details on the layout of the physical storage of proposed systema and allocation of capacity.

RAID Group	Devices	Total	Data	Parity	Spare
raidgroup1	15.36TB NVMe SSD	24	22	2	0
raidgroup2	15.36TB NVMe SSD	23	21	2	0
Spare	15.36TB NVMe SSD	1	0	0	1
		48	43	4	1

	Capacity (TiB) ¹	Capacity (TB) ²	Percentage (%)
Usable	567.60	624.08	84.99%
Root	0.75	0.82	0.11%
WAFL	29.92	32.90	4.48%
Parity	55.66	61.20	8.33%
Spare	13.92	15.31	2.08%
Total	667.85	734.31	100.0%

- Capacity values reported in this column are in base-2 format which aligns with values reported in ONTAP command line and System Manager.
- Capacity values reported in this column are in base-10 format and will not match any values reported by ONTAP. Those are provided for convenience only.

3.4 Storage Availability Zone

Zone	Workloads	Workload Type	Ratio	Storage Availability Usage	Usable (TiB)	Effective (TiB)
Zone 1	workload 1 - 100k IOPS	custom	2:1	0.00%	1.00	2.00
Zone 1	workload 2 - 100k IOPS	custom	2:1	0.00%	1.00	2.00
Zone 1	workload 3 - 100k IOPS	custom	2:1	0.00%	1.00	2.00
Zone 1	workload 4 - 100k IOPS	custom	2:1	0.00%	1.00	2.00
Zone 1	workload 5 - 100k IOPS	custom	2:1	0.00%	1.00	2.00

3.5 Workload Descriptions

							IO Percentages				IO Block Sizes (KB)				
Workload Name	Type	TPut IOPS	Effective Capacity (TiB)	Cold Data %	Protocol	Read Latency (MS)	Rand Read	Rand Write	Seq Read	Seq write	Rand Read	Rand Write	Seq Read	Seq Write	Working Set%
workload 1 - 100k IOPS	Custom	100,000.00 IOPS	2.00	N/A	FC_NVMe	1	70	30	0	0	16	16	64	64	5
workload 2 - 100k IOPS	Custom	100,000.00 IOPS	2.00	N/A	FC_NVMe	1	70	30	0	0	16	16	64	64	5
workload 3 - 100k IOPS	Custom	100,000.00 IOPS	2.00	N/A	FC_NVMe	1	70	30	0	0	16	16	64	64	5
workload 4 - 100k IOPS	Custom	100,000.00 IOPS	2.00	N/A	FC_NVMe	1	70	30	0	0	16	16	64	64	5
workload 5 - 100k IOPS	Custom	100,000.00 IOPS	2.00	N/A	FC_NVMe	1	70	30	0	0	16	16	64	64	5

4 Environmental Certifications

4.1 Statements & Certifications

- [Environmental Policy and Certifications](#)
- [US TSCA PBT Substances Declaration](#)
- [China and Taiwan Toxic and Hazardous Substances or Elements Table](#)
- [European Union WEEE and Battery Statement](#)
- [E-waste Program](#)
- [ISO 14001:2015 Certificate](#)
- [European Union REACH Article Notifications - Cords and Cables](#)
- [China RoHS Compliance Statement](#)
- [European Union RoHS Compliance Statement](#)
- [European Union REACH Compliance Statement](#)

5 Copyright

Refer to the [Interoperability Matrix Tool \(IMT\)](#) on the NetApp Support site to validate that the exact product and feature versions described in this document are supported for your specific environment. The NetApp IMT defines the product components and versions that can be used to construct configurations that are supported by NetApp. Specific results depend on each customer's installation in accordance with published specifications.

Copyright Information

Copyright © 1994-2025 NetApp, Inc. All rights reserved. Printed in the U.S. No part of this document covered by copyright may be reproduced in any form or by any means-graphic, electronic, or mechanical, including photocopying, recording, taping, or storage in an electronic retrieval system without prior written permission of the copyright owner.

Software derived from copyrighted NetApp material is subject to the following license and disclaimer:

THIS SOFTWARE IS PROVIDED BY NETAPP "AS IS" AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL NETAPP BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

NetApp reserves the right to change any products described herein at any time, and without notice. NetApp assumes no responsibility or liability arising from the use of products described herein, except as expressly agreed to in writing by NetApp. The use or purchase of this product does not convey a license under any patent rights, trademark rights, or any other intellectual property rights of NetApp.

The product described in this manual may be protected by one or more U.S. patents, foreign patents, or pending applications.

RESTRICTED RIGHTS LEGEND: Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (c)(1)(ii) of the Rights in Technical Data and Computer Software clause at DFARS 252.277-7103 (October 1988) and FAR 52-227-19 (June 1987).

Trademark Information

NETAPP, the NETAPP logo, and the marks listed at <http://www.netapp.com/TM> are trademarks of NetApp, Inc. Other company and product names may be trademarks of their respective owners.





NetApp Solution Technical Report

Manually Designed Solution

Report Generated:

19-Mar-2025

Project ID:

157dd848

TABLE OF CONTENTS

1 Business Requirements..... 3

2 Solution Summary 4

2.1 Proposed Solution Summary4

3 Solution Details..... 5

3.1 System Details5

3.2 Environmental Details6

3.3 Storage Availability Zone: netapp1/netapp2.....7

3.4 Storage Availability Zone9

3.5 Workload Descriptions10

4 Environmental Certifications 11

4.1 Statements & Certifications11

5 Copyright 12


1 Business Requirements

[Use this section to document the customer's high-level business requirements]

2 Solution Summary

2.1 Proposed Solution Summary

This is a summary of what the proposed solution will deliver.

THROUGHPUT	RAW CAPACITY	STORAGE EFFICIENCY***
500,000 IOPS / 15,625.00 MB/s	734.4 TB	2 : 1
AVERAGE UTILIZATION	USABLE CAPACITY	EFFECTIVE CAPACITY***
73%	567.6 TiB (623TB)	1,135.1934 TiB
MAXIMUM THROUGHPUT*	RAW CAPACITY HEADROOM**	USABLE VS EFFECTIVE
586,697 IOPS / 18,334.29 MB/s	0GB	 567.6 TiB 1,135.1934 TiB
*assumes best practice configuration of aggregates and workload to aggregate mapping	**assumes future expansion using drives of same capacity	***assumes use of storage efficiency technologies like compression and deduplication ***Lowest efficiencies have been applied to unused capacity within the cluster.

Note:Usable and effective capacity is calculated and reported in base-2 format which aligns with values reported in ONTAP CLI, Storage Manager, and Unified Manager. It should be noted that ONTAP CLI displays base-2 capacity values, but labels these values using base-10 descriptors (e.g. GB/TB/PB).

CONFIGURATION				ENVIRONMENTAL	
Model:	ASA A90A	OnboardEthernetPorts:	0	Rack Units:	4 U
Nodes:	2	Onboard UTA2Ports:	0	System Weight:	118.00 lbs
				AC Power:	2433.35 W
Total Drives:	48	OnboardSASPorts:	0	Current Draw:	13.88 A
Drive Type:	15.3 TB NVMe SSD	Expansion Slots:	18	BTU/hr:	8304.79
Cluster Switches:	N/A	StgeSwitches:	N/A		

3 Solution Details

3.1 System Details

For rack elevation, please refer to the Storage Solution SVG Diagram

cluster1: netapp1/netapp2

Bill Of Materials				Total
	Description		Part Number	Qty
Systems				
	ASA A90A w/ 48x15.3TB NVMe SSD SED	9.16.1 ONTAP	X4028A	1
	Grand Total			1
Storage				
	Grand Total			0
Adapter Cards/ Flash Cache				
	Grand Total			0

3.2 Environmental Details

Line Voltage: 220

System Components	Qty	Rack Units	Current (Amps)		AC Power (Watts)		AC Power (VA)		Thermal Rating (BTU/hr)		Power (kWh/year)	
			Typical	Worst	Typical	Worst	Typical	Worst	Typical	Worst	Typical	Worst
ASA A90A w/ 48x15.3 TB NVMe SSDX4028A(2xControllers, 1xChassis)	1	4	13.88	18.51	2,433.35	3,638.33	2,561.42	3,829.82	8,304.79	12,417.27	21,330.29	31,892.92
Total	1	4	13.88	18.51	2,433.35	3,638.33	2,561.42	3,829.82	8,304.79	12,417.27	21,330.29	31,892.92

Median Power Usage

System Components	Qty	Median Current (Amps)	Median AC Power (Watts)	Median AC Power (VA)	Median Thermal Rating (BTU/hr)	Median Power (kWh/year)
ASA A90A w/ 48x15.3 TB NVMe SSDX4028A(2xControllers, 1xChassis)	1	9.31	1,862.2	1,960.21	6,350.1	16,323.7
Total	1	9.31	1,862.2	1,960.21	6,350.1	16,323.7

Note: Median power is based on actual power numbers reported by install base systems of similar configuration and represent the midpoint where half of the similar configurations consume less power and the other half consume more power. Typical and Worst-case power numbers are calculated based on product specifications and spot checked for accuracy. Typical power values are used when median power values are not available.

3.3 Storage Availability Zone: netapp1/netapp2

The information below provides details on the layout of the physical storage of proposed systema and allocation of capacity.

RAID Group	Devices	Total	Data	Parity	Spare
raidgroup1	15.36TB NVMe SSD	24	22	2	0
raidgroup2	15.36TB NVMe SSD	23	21	2	0
Spare	15.36TB NVMe SSD	1	0	0	1
		48	43	4	1

	Capacity (TiB) ¹	Capacity (TB) ²	Percentage (%)
Usable	567.60	624.08	84.99%
Root	0.75	0.82	0.11%
WAFL	29.92	32.90	4.48%
Parity	55.66	61.20	8.33%
Spare	13.92	15.31	2.08%
Total	667.85	734.31	100.0%

- Capacity values reported in this column are in base-2 format which aligns with values reported in ONTAP command line and System Manager.
- Capacity values reported in this column are in base-10 format and will not match any values reported by ONTAP. Those are provided for convenience only.

3.4 Storage Availability Zone

Zone	Workloads	Workload Type	Ratio	Storage Availability Usage	Usable (TiB)	Effective (TiB)
Zone 1	workload 1 - 100k IOPS	custom	2:1	0.00%	1.00	2.00
Zone 1	workload 2 - 100k IOPS	custom	2:1	0.00%	1.00	2.00
Zone 1	workload 3 - 100k IOPS	custom	2:1	0.00%	1.00	2.00
Zone 1	workload 4 - 100k IOPS	custom	2:1	0.00%	1.00	2.00
Zone 1	workload 5 - 100k IOPS	custom	2:1	0.00%	1.00	2.00

3.5 Workload Descriptions

							IO Percentages				IO Block Sizes (KB)				
Workload Name	Type	TPut IOPS	Effective Capacity (TiB)	Cold Data %	Protocol	Read Latency (MS)	Rand Read	Rand Write	Seq Read	Seq write	Rand Read	Rand Write	Seq Read	Seq Write	Working Set%
workload 1 - 100k IOPS	Custom	100,000.00 IOPS	2.00	N/A	FC_NVMe	1	70	30	0	0	32	32	64	64	5
workload 2 - 100k IOPS	Custom	100,000.00 IOPS	2.00	N/A	FC_NVMe	1	70	30	0	0	32	32	64	64	5
workload 3 - 100k IOPS	Custom	100,000.00 IOPS	2.00	N/A	FC_NVMe	1	70	30	0	0	32	32	64	64	5
workload 4 - 100k IOPS	Custom	100,000.00 IOPS	2.00	N/A	FC_NVMe	1	70	30	0	0	32	32	64	64	5
workload 5 - 100k IOPS	Custom	100,000.00 IOPS	2.00	N/A	FC_NVMe	1	70	30	0	0	32	32	64	64	5

4 Environmental Certifications

4.1 Statements & Certifications

- [Environmental Policy and Certifications](#)
- [US TSCA PBT Substances Declaration](#)
- [China and Taiwan Toxic and Hazardous Substances or Elements Table](#)
- [European Union WEEE and Battery Statement](#)
- [E-waste Program](#)
- [ISO 14001:2015 Certificate](#)
- [European Union REACH Article Notifications - Cords and Cables](#)
- [China RoHS Compliance Statement](#)
- [European Union RoHS Compliance Statement](#)
- [European Union REACH Compliance Statement](#)

5 Copyright

Refer to the [Interoperability Matrix Tool \(IMT\)](#) on the NetApp Support site to validate that the exact product and feature versions described in this document are supported for your specific environment. The NetApp IMT defines the product components and versions that can be used to construct configurations that are supported by NetApp. Specific results depend on each customer's installation in accordance with published specifications.

Copyright Information

Copyright © 1994-2025 NetApp, Inc. All rights reserved. Printed in the U.S. No part of this document covered by copyright may be reproduced in any form or by any means-graphic, electronic, or mechanical, including photocopying, recording, taping, or storage in an electronic retrieval system without prior written permission of the copyright owner.

Software derived from copyrighted NetApp material is subject to the following license and disclaimer:

THIS SOFTWARE IS PROVIDED BY NETAPP "AS IS" AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL NETAPP BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

NetApp reserves the right to change any products described herein at any time, and without notice. NetApp assumes no responsibility or liability arising from the use of products described herein, except as expressly agreed to in writing by NetApp. The use or purchase of this product does not convey a license under any patent rights, trademark rights, or any other intellectual property rights of NetApp.

The product described in this manual may be protected by one or more U.S. patents, foreign patents, or pending applications.

RESTRICTED RIGHTS LEGEND: Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (c)(1)(ii) of the Rights in Technical Data and Computer Software clause at DFARS 252.277-7103 (October 1988) and FAR 52-227-19 (June 1987).

Trademark Information

NETAPP, the NETAPP logo, and the marks listed at <http://www.netapp.com/TM> are trademarks of NetApp, Inc. Other company and product names may be trademarks of their respective owners.

