

LICENCE

No. 22868 replaces No.22725

Issued to:
 Applicant:
Schréder S.A.
Rue de Mons, 3
4000 Liège
Belgium



Licensee:
Schréder SA
Rue de Lusambo, 67
1190 BRUXELLES
Belgium



Product : road, square and street lighting
 Trade name(s) : SCHREDER
 Type(s)/model(s) : IZYLUM LT 1 (IZYLLT11), IZYLUM LT 2 (IZYLLT12), IZYLUM LT 3 (IZYLLT13)

The product and any acceptable variation thereto is specified in the annex to this licence and the documents therein referred to.

SGS CEBEC hereby declares that the above-mentioned product has been certified on the basis of:


- a type test according to the standard specified in annex
- an inspection of the production location
- a certification agreement with the number 1173

SGS CEBEC hereby grants the right to use the CEBEC certification mark
 The ENEC/CEBEC certification mark may be applied to the product as specified in this licence for the duration of the ENEC/CEBEC certification agreement and under the conditions of the ENEC/CEBEC certification agreement.

This licence is issued on : 10/08/2023

Etienne Thibaut,
 Certification Manager

© Only integral publication of this certificate, including the annex, is allowed
 This certificate is only valid combined with the publication on the following web address: www.sgs.com/ee



SPECIFICATION OF THE CERTIFIED PRODUCT

Product data

Product	:	road, square and street lighting
Trade name(s)	:	SCHREDER
Type(s)/Model(s)	:	IZYLUM LT 1 (IZYLLT11), IZYLUM LT 2 (IZYLLT12), IZYLUM LT 3 (IZYLLT13)
description	:	Street lighting
rated voltage (Un)	:	220-240 V
nature of supply	:	ac
rated frequency	:	50-60 Hz
class	:	class I
degree of protection	:	IP66
resistance to impact (IK)	:	IK08

Product data - type IZYLUM LT 1 (IZYLLT11)

rated power	:	max. 88 W
rated ambient temperature (ta)	:	max. 55°C
rated current (In)	:	max. 1050 mA
lamp(s)	:	max. 36 LEDs (5050) max. 25 LEDs (Z5M4, LH351C)

Product data - type IZYLUM LT 2 (IZYLLT12)

rated power	:	max. 124 W
rated ambient temperature (ta)	:	max. 55°C
rated current (In)	:	max. 1050 mA
lamp(s)	:	max. 72 LEDs (5050) max. 50 LEDs (Z5M4, LH351C)

Product data - type IZYLUM LT 3 (IZYLLT13)

rated power	:	max. 203 W
rated ambient temperature (ta)	:	max. 55°C
rated current (In)	:	max. 1050 mA
lamp(s)	:	max. 144 LEDs (5050) max. 100 LEDs (LH351C)

TESTS

Test requirements

EN 60598-2-3:2003 + A1:2011
EN IEC 60598-1:2021 + A11:2022

Test results

The test results are laid down in certification file 633264/05.

Remarks


This certificate is based on test report No. P1613-14-lb.

Conclusion

The examination proved that all certification requirements were met.

Reviewed by, project leader : Christian Maes - 10/08/2023

Certification Manager : Etienne Thibaut - 2023-08-10



FACTORY LOCATION(S)

Schreder TOV
 Vul. Mykulynetska 46B
 46000 TERNOPIL
 Ukraine

Schreder (China) Lighting Industrial Co., Ltd
 No.40 Xinye 2 Street
 Tianjin Economic Technological Development Zone West Zone
 300462 Tianjin City, P.R.China
 China

Comatelec Schröder
 ZAC de l'échangeur 11 rue Louis BECHEREAU
 18000 Bourges
 France

Socelec S.A.
 Av. de Roanne, 66
 Poligono Industrial "EL HENARES"
 19180 MARCHAMALO (GUADALAJARA)
 Spain

Schröder Iluminação S.A.
 Rua da Fraternidade Operária, n° 3
 2794-089 CARNAXIDE, OEIRAS
 Portugal

Schröder Hungary Plc.
 Tópart 2
 2084 PILISSZENTIVAN
 Hungary