

# CHP-80/160

## CO<sub>2</sub> Incubator



## Features

1. Computer Control: Modular high precision.
2. Alarm devices: with CO<sub>2</sub>, sound and light alarm device.
3. Filtering devices: with the CO<sub>2</sub>, gas double filter.
4. Water-jacket-style: efficient heat insulation layer, temperature stability, energy-saving.
5. Door heating devices: glass doors to prevent condensation and pollution, easy to observe.
6. Incubators water jacket made of stainless steel welding production, durable, Liner semicircular curved corners for easy cleaning.

## Specifications

MODEL	CHP-80	CHP-160
Capacity	80L	160L
Power	680W	950W
Temperature range	RT+5-60°C	RT+5-60°C
Temperature accuracy	37°C±0.3°C	37°C±0.3°C
Temperature resolution	0.1°C	0.1°C
CO <sub>2</sub> range	0-20%	0-20%
CO <sub>2</sub> accuracy	0.1%	0.1%
CO <sub>2</sub> Uniformity	When 5%,±0.1%	When 5%,±0.1%
CO <sub>2</sub> Alarm	±1°C	±1°C
CO <sub>2</sub> Recovery Time	≤Concentration×1.2 min	≤Concentration×1.2 min
Heating mode	water jacket	water jacket
Temperature mode	Natural evaporation	Natural evaporation
Size mm	500×400×400	500×500×650