

Cross X1000ii HD Video for HDMI 200M Wireless Video Transmitter	Wireless HD video transmission for DSLR/DV -Support full-HD 1080P/60Hz video transmission with very low latency -Up to 200m/656ft.effective range line of sight -Support external Li-battery supply for mobile convenience -Support audio input nfrom external microphone -Hi-quality LCD screen display signal & battery status fo product	2015
UltraLITE Intercom Headsets Eartec UltraLITE HUB HD for 6 + 1	Standard – DECT 6.0 (Digital Enhanced Cordless Telecommunications) Frequency – 1920 – 1930MHz (USA), UK/EU Frequency: 1880 – 1900MHz (UK/EU) Weight – 450g Connector – 2.5mm 3.5mm plug in Dimensions – 5.5" w x 1.5" d x 3.75" h Channel Bandwidth: 1.728 GHz Modulation Type: GFSK Transmission Speed: 1.152 Mbps (Baud Rate) Duplexing: Time Division Duplex (TDD) Speech Encoding: ADPCM 32bit/s RF Accessing: Time Division Multiple Access (TDMA) Range: Up to 400m (Line of Sight) Power Supply: Rechargeable Lithium 3.7 V / 800 mAh 3.0 Wh Charger Power Supply: AC INPUT 110-240Vac OUTPUT 5.0V – 1 1000mA Charge Time: 3 hours Operation Time: Up to 4 hours Storage Temperature: -10 C to 60 C Warranty: 12 Months	2017

