




DIMENSIONS:

- Height: 435 ± 10 mm.
- Min. Dry Arcing Distance : 270 mm.
- Min. Creepage Distance: 680mm.
- Diameter Of The Rod: Ø18mm.
- Coupling Dimensions: Y-Clevis/Ball.
- Number Of Sheds: 5.

RAW MATERIALS:

1. End-fitting:

1.1 Material:

Socket: Cast Iron Or Cast Steel, Hot Dip Galvanized.

Ball: Forged Steel, Hot Dip Galvanized.

1.2 Minimum Thickness Of The Galvanization: 86 um.

2. Core:

2.1 Material: Epoxy & Glass Fiber, Acid-Resistant Type.

2.2 Diameter: Ø18mm.

3. Weather sheds:

3.1 Material: HTV Silicone .

3.2 Color: Gray.

MECHANICAL:

- Specified Mechanical Load (SML): 70 kN.
- Routine Test Load (RTL): 35kN.
- Standard: IEC 61109-2008 IEC 60120-1984

ELECTRICAL:

- Rated Voltage: 24kV.
- Critical Impulse Flashover Voltage (Pos/Neg): 200/200KV.
- Power Frequency Flashover Voltage (Dry/Wet): 80/75KV.
- Standard: IEC 61109-2008 IEC 60120-1984

						General Drawing			
Mark	Amount	Section	Modifying File NO.	Sign	Y M D				
Design		20.10.10	Standard			Stage Mark	Weight (kg)	Ratio	4890330 Composite Suspension Insulator
Check									
Verify									24kV70KN-435-201010001
Process			Approved			1 Page in all The 1st Page			