



VICTORIA

ICONIC ELECTRIC SUCTION UNIT

• EXTREMELY SILENT RUN

- 6 YEAR WARRANTY ON THE VACUUM PUMP
- LOW MAINTENANCE REQUIREMENTS
- MAINTENANCE-FREE GERMAN VACUUM PUMP
- DESIGNED FOR CONTINUOUS RUN
- RELIABLE AND VIBRATION-FREE RUN
- VACUUM PUMP IS COOLED BY EXTRA FAN
- INNOVATIVE EUROPEAN DESIGN

www.cheiron.eu

• EXTREMELY SILENT RUN

- 6 YEAR WARRANTY ON THE VACUUM PUMP
- LOW MAINTENANCE REQUIREMENTS
- MAINTENANCE-FREE GERMAN VACUUM PUMP
- DESIGNED FOR CONTINUOUS RUN
- RELIABLE AND VIBRATION-FREE RUN
- VACUUM PUMP IS COOLED BY EXTRA FAN
- INNOVATIVE EUROPEAN DESIGN



Overflow protection Vacuum gauge in kPa, mmHg and Bar, colour coded Illuminated on/off switch meets EU standard EN ISO 10079-1 Ergonomic vacuum regulator Casing is made of very sturdy material with UV protection Change-over valve shift the vacuum from one jar to the other with a single move - optional Π Jar holder is equipped with suction circuit holder The stainless eurorail ensures maximum flexibility. You can attach up to four jars of any size and/or any other accessories needed **MAKES LESS NOISE THAN YOUR PC!** A SPECIAL SYSTEM OF NOISE AND

VIBRATION DAMPENING FOR AN EXTREMELY QUIET AND SMOOTH OPERATION WITH AN INCREDIBLY SILENT RUN

> Non-marking casters with safety brakes. Antistatic casters - optional



VICTORIA VERSA

The most popular high performance model of Victoria especially suitable for wards, operating rooms, recovery rooms, ICUs, obstetrics and endoscopic applications, etc.

VICTORIA LIPOS

High performance solution designed particularly for liposuction and operating rooms.

VICTORIA PORTABLE

Quiet and effective model for medical practices, wards and endoscopic applications, as well suitable for fast suction in any situation.

VICTORIA THORAX

Model specially designed for common use as well as for thoraxic and abdominal surgery drainage and intensive care. The system can be used for long-term up to 30 days continuous drainage.

Thanks to a unique patented solution Victoria Thorax enables full suction output even during drainage.







TECHNICAL SPECIFICATIONS

TYPE		PORTABLE	VERSA	THORAX	LIPOS
Suction jar 2 l with press on cover		•	٠		•
Suction jar 2 I with screw cover				• 2 pcs	
Suction jar holder for 2 l jar for the side of the unit		•			
Suction jar holder for 2 l jar for eurorail			•	• 2 pcs	•
PVC suction circuit with stop valve		•	•	•	•
Mobile stand			•	•	•
Limiting water valve				0	
Free air flowrate - High flowrate	± 5 l/min	40 l/min	40 l/min	40 l/min	50 l/min
Vacuum level - High vacuum	±5 kPa	–92 kPa	–92 kPa	–92 kPa	–93 kPa
		(–690 mmHg)	(–690 mmHg)	(–690 mmHg)	(–698 mmHg)
		(–938 cmH ₂ O)	(–938 cmH ₂ O)	(–938 cmH ₂ O)	(–948 cmH ₂ O)
Input Power		110 VA (W)	110 VA (W)	110 VA (W)	110 VA (W)
Input Voltage		230V /50–60 Hz and models for 120V \pm 10% / 60Hz are also available			
Dimensions (w \times h \times l) in milimeters		$440\times300\times310$	$480\times900\times460$	$480\times900\times460$	$480\times900\times460$
Dimensions (w \times h \times l) in inches		20,1 × 11,8 × 13,4	18,1 × 18,9 × 39	18,1 × 18,9 x 39	18,1 × 18,9 x 39
Weight (without accessories)		12 kg (26,5 lb)	21 kg (46,3 lb)	24 kg (52,9 lb)	21 kg (46,3 lb)
Range of vacuum level thoracic d	rainage			$0 - 40 \text{ cmH}_{2}\text{O}$	



OPTIONAL ACCESSORIES



CHEIRÓN a.s., Kukulova 24, Břevnov 169 00 Prague 6, Czech Republic Branch office: Republikanska 1102/45, 312 00 Plzen, Czech Republic Tel.: +420 377 590 433, 422, Fax: +420 377 590 435 E-mail: export@cheiron.eu, www.cheiron.eu

In regard of the continuous research and evelopment Cheirón reserves the right to make changes which may affect the information contained in this brochure without prior notice.

www.cheiron.eu

