

Article No.: V000000000004 DERIPOX - VERDÜNNUNG  
Print date: 21.07.2022 Revision date: 12.02.2022 EN  
Version: 15.1 Issue date: 12.02.2022 Page 1 / 9

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. product identifiers

Article No. (manufacturer/supplier) V000000000004  
Trade name/designation DERIPOX - VERDÜNNUNG

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Relevant identified uses:

Thinner and cleaner for coating materials, described at the technical data sheets.

### 1.3. Details of the supplier of the safety data sheet

#### supplier (manufacturer/importer/downstream user/distributor)

DR.DEMUTH GmbH & Co.KG  
Hillerser Str. 8 Telephone: + 49 5551 97940  
D-37154 Northeim Telefax: +49 5551 979430

#### Department responsible for information:

Andreas Schießl  
E-mail A.Schiessl@dr-demuth.com

### 1.4. Emergency telephone number

Emergency telephone number + 442071880100

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

#### Classification according to Regulation (EC) No 1272/2008 [CLP]

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

Flam. Liq. 3 / H226	Flammable liquids	Flammable liquid and vapour.
Acute Tox. 4 / H312	Acute toxicity (dermal)	Harmful in contact with skin.
Acute Tox. 4 / H332	Acute toxicity (inhalative)	Harmful if inhaled.
Skin Irrit. 2 / H315	Skin corrosion/irritation	Causes skin irritation.
Eye Dam. 1 / H318	Serious eye damage/eye irritation	Causes serious eye damage.
STOT SE 3 / H335	STOT-single exposure	May cause respiratory irritation.
STOT SE 3 / H336	STOT-single exposure	May cause drowsiness or dizziness.
STOT RE 2 / H373	STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
Asp. Tox. 1 / H304	Aspiration hazard	May be fatal if swallowed and enters airways.

### 2.2. Label elements

#### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

#### Hazard pictograms



**Danger**

#### Hazard statements

H226	Flammable liquid and vapour.
H312 + H332	Harmful in contact with skin or if inhaled.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.
H304	May be fatal if swallowed and enters airways.

#### Precautionary statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260	Do not breathe vapour.
P280	Wear protective gloves and eye/face protection.
P301 + P310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER or doctor/physician.
P331	Do NOT induce vomiting.

Article No.: V000000000004 DERIPOX - VERDÜNNUNG  
Print date: 21.07.2022 Revision date: 12.02.2022 EN  
Version: 15.1 Issue date: 12.02.2022 Page 2 / 9

P370 + P378 In case of fire: Use extinguishing powder or sand to extinguish.  
P403 + P233 Store in a well-ventilated place. Keep container tightly closed.  
P403 + P235 Store in a well-ventilated place. Keep cool.

**Hazard components for labelling**

Reactionprodukt from ethylbenzene and xylenes  
butan-1-ol

**Supplemental hazard information**

not applicable

**2.3. Other hazards**

No information available.

**SECTION 3: Composition/information on ingredients**

**3.2. Mixtures**

**Description** Solvents/Thinner

**Classification according to Regulation (EC) No 1272/2008 [CLP]**

EC No.	REACH No.	weight-%
CAS No.	Designation	
Index No.	classification // Remark	
905-588-0	01-2119488216-32-XXXX Reactionprodukt from ethylbenzene and xylenes Acute Tox. 4 H312 / Acute Tox. 4 H332 / Skin Irrit. 2 H315 / Eye Irrit. 2 H319 / STOT SE 3 H335 / STOT RE 2 H373 / Asp. Tox. 1 H304 / Flam. Liq. 3 H226	70 - 100
200-751-6 71-36-3 603-004-00-6	01-2119484630-38-XXXX butan-1-ol Flam. Liq. 3 H226 / Acute Tox. 4 H302 / STOT SE 3 H335 / Skin Irrit. 2 H315 / Eye Dam. 1 H318 / STOT SE 3 H336	20 - 25

**Additional information**

Full text of classification: see section 16

**SECTION 4: First aid measures**

**4.1. Description of first aid measures**

**General information**

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

**In case of inhalation**

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

**Following skin contact**

Take off immediately all contaminated clothing. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

**After eye contact**

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

**Following ingestion**

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

**4.2. Most important symptoms and effects, both acute and delayed**

In all cases of doubt, or when symptoms persist, seek medical advice.

**4.3. Indication of any immediate medical attention and special treatment needed**

First Aid, decontamination, treatment of symptoms.

**SECTION 5: Firefighting measures**

**5.1. Extinguishing media**

Suitable extinguishing media

Article No.: V000000000004 DERIPOX - VERDÜNNUNG  
Print date: 21.07.2022 Revision date: 12.02.2022  
Version: 15.1 Issue date: 12.02.2022

EN  
Page 3 / 9

alcohol resistant foam, carbon dioxide, Powder, spray mist, (water)

**Unsuitable extinguishing media**

strong water jet

5.2. **Special hazards arising from the substance or mixture**

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.

5.3. **Advice for firefighters**

Provide a conveniently located respiratory protective device. Cool closed containers that are near the source of the fire. Do not allow water used to extinguish fire to enter drains, ground or waterways.

**SECTION 6: Accidental release measures**

6.1. **Personal precautions, protective equipment and emergency procedures**

Keep away from sources of ignition. Ventilate affected area. Do not breathe vapours.

6.2. **Environmental precautions**

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

6.3. **Methods and material for containment and cleaning up**

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13). Clean using cleansing agents. Do not use solvents.

6.4. **Reference to other sections**

Observe protective provisions (see section 7 and 8).

**SECTION 7: Handling and storage**

7.1. **Precautions for safe handling**

**Advices on safe handling**

Avoid formation of flammable and explosive vapour concentrations in the air and exceeding the exposure limit values. Only use the material in places where open light, fire and other flammable sources can be kept away. Electrical equipment must be protected meeting the accepted standard. Product may become electrostatically charged. Provide earthing of containers, equipment, pumps and ventilation facilities. Anti-static clothing including shoes are recommended. Floors must be electrically conductive. Keep away from heat sources, sparks and open flames. Use only spark proof tools. Avoid contact with skin, eyes and clothes. Do not inhale dusts, particulates and spray mist when using this preparation. Avoid respiration of swarf. When using do not eat, drink or smoke. Personal protection equipment: refer to section 8. Do not empty containers with pressure - no pressure vessel! Always keep in containers that correspond to the material of the original container. Follow the legal protection and safety regulations.

**Further information**

Vapours are heavier than air. Vapours form explosive mixtures with air.

7.2. **Conditions for safe storage, including any incompatibilities**

**Requirements for storage rooms and vessels**

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSiVO). Keep container tightly closed. Do not empty containers with pressure - no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks. Soils have to conform to the "Guidelines for avoidance of ignition hazards due to electrostatic charges (TRGS 727)".

**Hints on joint storage**

Keep away from strongly acidic and alkaline materials as well as oxidizers.

**Further information on storage conditions**

Take care of instructions on label. Store in a well-ventilated and dry room at temperatures between 5 °C and 30 °C. Protect from heat and direct sunlight. Keep container tightly closed. Remove all sources of ignition. Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

7.3. **Specific end use(s)**

Observe technical data sheet. Observe instructions for use.

**SECTION 8: Exposure controls/personal protection**

8.1. **Control parameters**

**Occupational exposure limit values:**

butan-1-ol

Article No.: V000000000004 DERIPOX - VERDÜNNUNG  
Print date: 21.07.2022 Revision date: 12.02.2022  
Version: 15.1 Issue date: 12.02.2022

EN  
Page 4 / 9

Index No. 603-004-00-6 / EC No. 200-751-6 / CAS No. 71-36-3

WEL, STEL: 154 mg/m<sup>3</sup>; 50 ppm  
Remark: (may be absorbed through the skin)

#### Xylene

Index No. 601-022-00-9 / EC No. 215-535-7 / CAS No. 1330-20-7

WEL, TWA: 220 mg/m<sup>3</sup>; 50 ppm  
WEL, STEL: 441 mg/m<sup>3</sup>; 100 ppm  
Remark: (may be absorbed through the skin)  
BMGV, TWA: 650 mmol/mol creatinine  
Remark: methyl hippuric acid; urine; end of exposure or end of shift

#### Additional information

TWA : Long-term occupational exposure limit value  
STEL : short-term occupational exposure limit value  
Ceiling : peak limitation

#### DNEL:

butan-1-ol

Index No. 603-004-00-6 / EC No. 200-751-6 / CAS No. 71-36-3

DNEL short-term oral (acute), Workers:  
DNEL long-term oral (repeated), Consumer: 3,125 mg/kg

Reactionprodukt from ethylbenzene and xylenes

EC No. 905-588-0

DNEL long-term dermal (systemic), Workers: 180 mg/kg  
DNEL acute inhalative (systemic), Workers: 289 mg/m<sup>3</sup>  
DNEL long-term inhalative (systemic), Workers: 77 mg/m<sup>3</sup>  
DNEL long-term oral (repeated), Consumer: 1,6 mg/kg  
DNEL long-term dermal (systemic), Consumer: 108 mg/kg  
DNEL acute inhalative (local), Consumer: 174 mg/m<sup>3</sup>  
DNEL acute inhalative (systemic), Consumer: 174 mg/m<sup>3</sup>  
DNEL long-term inhalative (systemic), Consumer: 14,8 mg/m<sup>3</sup>

#### PNEC:

butan-1-ol

Index No. 603-004-00-6 / EC No. 200-751-6 / CAS No. 71-36-3

PNEC sewage treatment plant (STP): 2476 mg/L

Reactionprodukt from ethylbenzene and xylenes

EC No. 905-588-0

PNEC aquatic, freshwater: 0,327 mg/L  
PNEC aquatic, marine water: 0,327 mg/L  
PNEC aquatic, intermittent release: 0,327 mg/L  
PNEC sediment, freshwater: 12,46 mg/L  
PNEC sediment, marine water: 12,46 mg/kg  
PNEC, soil: 2,31 mg/kg  
PNEC sewage treatment plant (STP): 6,58 mg/L

#### 8.2. Exposure controls

Provide good ventilation. This can be achieved with local or room suction. If this should not be sufficient to keep aerosol and solvent vapour concentration below the exposure limit values, a suitable respiratory protection must be used.

#### Personal protection equipment

##### Respiratory protection

If concentration of solvents is beyond the occupational exposure limit values, approved and suitable respiratory protection must be used. Use only respiratory protection equipment with CE-symbol including four digit test number.

##### Hand protection

For prolonged or repeated handling the following glove material must be used: PVA (Polyvinyl alcohol)

Thickness of the glove material > 0,4 mm ; Breakthrough time: > 480 min.

Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommended glove articles EN ISO 374

Article No.: V000000000004 DERIPOX - VERDÜNNUNG  
Print date: 21.07.2022 Revision date: 12.02.2022  
Version: 15.1 Issue date: 12.02.2022

EN  
Page 5 / 9

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

**Eye/face protection**

Wear closely fitting protective glasses in case of splashes.

**Body protection**

Wear antistatic clothing of natural fibers (cotton) or heat resistant synthetic fibers.

**Protective measures**

After contact clean skin thoroughly with water and soap or use appropriate cleanser.

**Environmental exposure controls**

Do not allow to enter into surface water or drains. See section 7. No additional measures necessary.

**SECTION 9: Physical and chemical properties**

9.1. Information on basic physical and chemical properties

**Appearance:**

**Physical state:**

**Liquid**

**Colour:**

**refer to label**

**Odour:**

**characteristic**

**Odour threshold:**

**not applicable**

**pH at 20 °C:**

**not applicable**

Method: DIN 19268

**Melting point/freezing point:**

**not practicable**

**Initial boiling point and boiling range:**

**117 °C**

Method: literature value

Source: butan-1-ol

**Flash point:**

**24 °C**

Method: EN ISO 1523

**Evaporation rate:**

**not applicable**

**flammability**

**Burning time:**

**not applicable**

**Upper/lower flammability or explosive limits:**

**Lower explosion limit:**

**1 Vol-%**

**Upper explosion limit:**

**7 Vol-%**

**Vapour pressure at 20 °C:**

**7,8 mbar**

Method: literature value

**Vapour density:**

**not applicable**

**Relative density:**

**Density at 20 °C:**

**0,86 g/cm<sup>3</sup>**

Method: calculated.

**Solubility(ies):**

**Water solubility at 20 °C:**

**partially soluble**

**Partition coefficient: n-octanol/water:**

**see section 12**

**Auto-ignition temperature:**

**372 °C**

Method: literature value

**Decomposition temperature:**

**not applicable**

**Viscosity at 20 °C:**

**< 12 s 4 mm**

Method: DIN 53211

**Explosive properties:**

**not applicable**

**Oxidising properties:**

**not applicable**

9.2. Other information

**Solid content:**

**0 weight-%**

**solvent content:**

**Organic solvents:**

**100 weight-%**

**Water:**

**0 weight-%**

Article No.: V000000000004 DERIPOX - VERDÜNNUNG  
Print date: 21.07.2022 Revision date: 12.02.2022  
Version: 15.1 Issue date: 12.02.2022

EN  
Page 6 / 9

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No information available.

### 10.2. Chemical stability

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7.

### 10.3. Possibility of hazardous reactions

Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions.

### 10.4. Conditions to avoid

Hazardous decomposition byproducts may form with exposure to high temperatures.

### 10.5. Incompatible materials

not applicable

### 10.6. Hazardous decomposition products

Hazardous decomposition byproducts may form with exposure to high temperatures, e.g.: carbon dioxide, carbon monoxide, smoke, nitrogen oxides.

## SECTION 11: Toxicological information

Classification according to Regulation (EC) No 1272/2008 [CLP]

### 11.1. Information on toxicological effects

#### Acute toxicity

Harmful in contact with skin.

Harmful if inhaled.

Reactionprodukt from ethylbenzene and xylenes

oral, LD50, Rat: 4300 mg/kg 4300

dermal, LD50, Rabbit: 3200 mg/kg 3200

inhalative (vapours), LC50, Rat (4 h)

#### Skin corrosion/irritation; Serious eye damage/eye irritation

Causes skin irritation.

Causes serious eye damage.

#### Respiratory or skin sensitisation

Based on available data, the classification criteria are not met.

#### CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

Based on available data, the classification criteria are not met.

#### STOT-single exposure; STOT-repeated exposure

May cause respiratory irritation.

May cause drowsiness or dizziness.

May cause damage to organs through prolonged or repeated exposure.

#### Aspiration hazard

May be fatal if swallowed and enters airways.

#### Practical experience/human evidence

Inhaling of solvent components above the MWC-value can lead to health damage, e.g. irritation of the mucous membrane and respiratory organs, as well as damage to the liver, kidneys and the central nerve system. Indications for this are: headache, dizziness, fatigue, amyosthenia, drowsiness, in serious cases: unconsciousness. Solvents may cause some of the aforementioned effects through skin resorption. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and/or absorption through skin. Splashing may cause eye irritation and reversible damage.

#### Overall assessment on CMR properties

The ingredients in this mixture do not meet the criteria for classification as CMR category 1A or 1B according to CLP.

## SECTION 12: Ecological information



Article No.: V000000000004 DERIPOX - VERDÜNNUNG  
Print date: 21.07.2022 Revision date: 12.02.2022  
Version: 15.1 Issue date: 12.02.2022

EN  
Page 7 / 9

Classification according to Regulation (EC) No 1272/2008 [CLP]  
Do not allow to enter into surface water or drains.

#### 12.1. Toxicity

Reactionprodukt from ethylbenzene and xylenes  
Fish toxicity, LC50: 26,7 mg/L (96 h)  
Daphnia toxicity, EC50: 3,82 mg/L (48 h)

#### 12.2. Persistence and degradability

Reactionprodukt from ethylbenzene and xylenes  
:  
Readily biodegradable (according to OECD criteria).

#### 12.3. Bioaccumulative potential

Toxicological data are not available.

#### 12.4. Mobility in soil

Toxicological data are not available.

#### 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

#### 12.6. Other adverse effects

No information available.

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

##### Appropriate disposal / Product Recommendation

Do not allow to enter into surface water or drains. This material and its container must be disposed of in a safe way. Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

##### List of proposed waste codes/waste designations in accordance with EWC

080111\* Waste paint and varnish containing organic solvents or other dangerous substances

\*Hazardous waste according to Directive 2008/98/EC (waste framework directive).

##### Appropriate disposal / Package Recommendation

Non-contaminated packages may be recycled. Vessels not properly emptied are special waste.

### SECTION 14: Transport information

#### 14.1. UN number

UN 1263

#### 14.2. UN proper shipping name

Land transport (ADR/RID):

Paint related material  
(XYLENES, BUTANOLE)

Sea transport (IMDG):

PAINT RELATED MATERIAL  
(XYLENES)

Air transport (ICAO-TI / IATA-DGR):

Paint related material  
(XYLENES)

#### 14.3. Transport hazard class(es)

3

#### 14.4. Packing group

III

#### 14.5. Environmental hazards

Land transport (ADR/RID)

not applicable

Marine pollutant

not applicable

#### 14.6. Special precautions for user

Transport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do in case of an accident or leakage.

Advices on safe handling: see parts 6 - 8

#### Further information

Article No.: V000000000004 DERIPOX - VERDÜNNUNG  
Print date: 21.07.2022 Revision date: 12.02.2022  
Version: 15.1 Issue date: 12.02.2022

EN  
Page 8 / 9

#### Land transport (ADR/RID)

Tunnel restriction code D/E

#### Sea transport (IMDG)

EmS-No. F-E, S-E

#### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

##### EU legislation

##### Directive 2010/75/EU on industrial emissions [Industrial Emissions Directive]

VOC-value (in g/L): 857,3

##### Directive 2004/42/EC on the limitation of emissions of volatile organic compounds

VOC product category: not applicable ; VOC limit value: 0

Maximum VOC content of the product in a ready to use condition (in g/L): 860,0

##### National regulations

##### Restrictions of occupation

Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.  
Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

#### 15.2. Chemical Safety Assessment

For the following substances of this mixture a chemical safety assessment has been carried out:

EC No. CAS No.	Designation	REACH No.
905-588-0	Reactionprodukt from ethylbenzene and xylenes	01-2119488216-32-XXXX
200-751-6	butan-1-ol	01-2119484630-38-XXXX
71-36-3		

### SECTION 16: Other information

#### Full text of classification in section 3

Acute Tox. 4 / H312	Acute toxicity (dermal)	Harmful in contact with skin.
Acute Tox. 4 / H332	Acute toxicity (inhalative)	Harmful if inhaled.
Skin Irrit. 2 / H315	Skin corrosion/irritation	Causes skin irritation.
Eye Irrit. 2 / H319	Serious eye damage/eye irritation	Causes serious eye irritation.
STOT SE 3 / H335	STOT-single exposure	May cause respiratory irritation.
STOT RE 2 / H373	STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
Asp. Tox. 1 / H304	Aspiration hazard	May be fatal if swallowed and enters airways.
Flam. Liq. 3 / H226	Flammable liquids	Flammable liquid and vapour.
Acute Tox. 4 / H302	Acute toxicity (oral)	Harmful if swallowed.
Eye Dam. 1 / H318	Serious eye damage/eye irritation	Causes serious eye damage.
STOT SE 3 / H336	STOT-single exposure	May cause drowsiness or dizziness.

#### Classification procedure

Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

Flam. Liq. 3	Flammable liquids	On basis of test data.
Acute Tox. 4	Acute toxicity (dermal)	Calculation method.
Acute Tox. 4	Acute toxicity (inhalative)	Calculation method.
Skin Irrit. 2	Skin corrosion/irritation	Calculation method.
Eye Dam. 1	Serious eye damage/eye irritation	Calculation method.
STOT SE 3	STOT-single exposure	Calculation method.
STOT SE 3	STOT-single exposure	Calculation method.
STOT RE 2	STOT-repeated exposure	Calculation method.
Asp. Tox. 1	Aspiration hazard	Calculation method.

#### Abbreviations and acronyms

ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
OEL	Occupational Exposure Limit Value
BLV	Biological Limit Value



**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) 2015/830

Article No.: V000000000004 DERIPOX - VERDÜNNUNG  
Print date: 21.07.2022 Revision date: 12.02.2022  
Version: 15.1 Issue date: 12.02.2022

EN  
Page 9 / 9

---

CAS	Chemical Abstracts Service
CLP	Classification, Labelling and Packaging
CMR	Carcinogenic, Mutagenic and Reprotoxic
DIN	German Institute for Standardization / German industrial standard
DNEL	Derived No-Effect Level
EAKV	European Waste Catalogue Directive
EC	Effective Concentration
EC	European Community
EN	European Standard
IATA-DGR	International Air Transport Association – Dangerous Goods Regulations
IBC Code	International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk
ICAO-TI	International Civil Aviation Organization Technical Instructions for the Safe Transport of Dangerous Goods by Air
IMDG Code	International Maritime Code for Dangerous Goods
ISO	International Organization for Standardization
LC	Lethal Concentration
LD	Lethal Dose
MARPOL	Maritime Pollution: The International Convention for the Prevention of Pollution from Ships
OECD	Organisation for Economic Cooperation and Development
PBT	persistent, bioaccumulative, toxic
PNEC	Predicted No Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
UN	United Nations
VOC	Volatile Organic Compounds
vPvB	very persistent and very bioaccumulative

**Further information**

Classification according to Regulation (EC) No 1272/2008 [CLP]

The information supplied on this safety data sheet complies with our current level of knowledge as well as with national and EU regulations. Without written approval, the product must not be used for purposes different from those mentioned in section 1. It is always the user's duty to take any necessary measures for meeting the requirements laid down by local rules and regulations. The details in this safety data sheet describe the safety requirements of our product and are not to be regarded as guaranteed attributes of the product.