



COMBO MODEL


Flexibility of the Flexmark combo configuration permits to mark any type of part.
Changing from bench machine to hand held takes less than 10 seconds, without any tools.

Technical specifications

Dimensions : (L x W x H) 400 x 350 x 600 mm	Weight : 11 kg
Capacity : <ul style="list-style-type: none"> Marking zone : 120 x 60 mm Tungsten carbide stylus with 90° sharpening angle (available with 60° and 120° angle) Adjustable marking height from 0.6 to 89.8 mm, in 0.2mm steps Font matrix: 5x7 ; 9x13 and continuous line Alphanumeric marking (text, symbol, serial number, variable, timestamp), logo* Linear, angular and circular marking RS232 and USB ports (host and device) Quick update, marking file transfer and "production files" (Txt. format) export via USB port Autodiagnosis menu with 5 control points Adjustable impact force with 5 levels and speed with 3 levels "Easy shift" function : preview of movements IDI Mark : intelligent driving impact Flexmark control box multilanguage : <ul style="list-style-type: none"> (L x W x H) 370 x 215 x 139 mm – 5.4 kg HD colour graphic screen (640 x 480 px) Memory capacity : up to 10 000 files Ergonomics : standing foot and transport handle 	Environment and power : <ul style="list-style-type: none"> Operating temperature : 0° to 45 ° (from 32°F to 115°F) Electrical power : 110v or 220v Power/ Frequency : 300 VA / 50 or 60 Hz Standards : <ul style="list-style-type: none"> Machinery directive: 2006/42/CE Electro-magnetic compatibility : 2004/108/CE Low power directive : 2006/95/CE FCC directive— chapter 15 Options : <ul style="list-style-type: none"> Software : <ul style="list-style-type: none"> FlexLOG (Logo design) FlexWINDOWS (File design with PC) External start cycle command (switch box/pedal) End of bar tool Part support Plate support D axis : high or simple capability Maintenance kit Transport trolley

*Optional logo marking, available with FlexLOG software

→ Production capacity up to 500 parts/day, depending on validation of the application by our technical service



Delivered with :

- Bench kit with screw type "Z" axis
- Handle with cycle start trigger and eccentric nut
- 3 m cable
- Control box power cable
- Adjustable foot

ITEM CODE : NME0-FXM

3, Allée Michaël FARADAY
Parc d'Activités STELYTEC
42400 SAINT-CHAMOND (France)

Tel : +33 (0)4 77 31 04 02
Fax : +33 (0)4 77 22 38 93
E-mail : info@flexmark-marking.com

www.flexmark-marking.com

FLEXMARK™ is a brand of Technomark Group

VERSION 1.1 - 24/07/2013 V : SJ