

VIVI 400 GX53 LED

LARGE SIZE

Modern luminaries made of shockproof resin material, UV-rays stabilized, rust and corrosion-free. Suitable for post top, wall and hanging installation. Equipped with TÜV approved, long-life and efficient **GX53 LED modular system** in different wattages. Designed according to the international regulations against light pollution (standard UNI 10819). Insulation class II, Protection rating IP65.

*Diffusore moderno realizzato in resina antiurto, stabilizzato ai raggi UV, inattaccabile da ruggine e corrosione. Idoneo per il montaggio a palo, a sospensione o a parete. Provvisto di **sistema modulare a LED GX53** approvato TÜV di lunga durata ed alta efficienza disponibile in diverse potenze. Progettato in ottemperanza alle norme internazionali contro l'inquinamento luminoso (standard UNI 10819). Classe di isolamento II, grado di protezione IP65.*



V50.000.D6L



VIVI 400 GX53 LED - COMPONENTS

IP65



ROOF made of shockproof resin material one piece only, UV-rays stabilized, rust and corrosion-free.

***TETTO** in un unico pezzo, realizzato in resina antiurto, stabilizzata ai raggi UV, inattaccabile da ruggine e corrosione.*



DIFFUSER made of UV-rays stabilized polymethylmethacrylate (PMMA), one piece only, available in clear or opal colour.

***DIFFUSORE** realizzato in polimetilmetacrilato (PMMA) stabilizzato ai raggi UV, disponibile in colore trasparente o opale.*



Decorative connection **RING** to be fixed on the luminaires diffuser.

***ANELLO** decorativo di connessione da fissare sul diffusore dell'apparecchio.*

VIVI 400 GX53 LED

V50.000 *



Dimensions and weight

Height: 420 mm
Diameter: 480 mm
Weight: 4,9 Kg
Junction to support: Ø 60 mm
Area expose to wind pressure:
CxS = m² 0,1449

Moulded colours:

Black White Grey

Diffuser PMMA:

Clear Opal

GX53 LED



- **COST SAVING:** long-life and efficient LED light sources.
- **BUILT-IN DRIVER:** quick and easy lamp replacement
- **GREAT FLEXIBILITY:** GX53 standard lamp holder.
- **FUTURE-PROOFED LUMINARIES:** performances easy to upgrade to latest technology developments.
- **SUITABLE FOR OUTDOOR USE:** built-in driver fully protected against heat and humidity by silicone paste.

*ADD. SUFFIX

Luminaries supplied with white resin CEILING provided with TÜV approved, long-life and efficient **6x GX53 LED lamps included**. Each lamp can be quickly and easily replaced individually, making the luminaries maintenance very simple.



6x 7W
42W

4800 Lm

4000 K .C6L

3000 K .C6R

6x 10W
60W

7200 Lm

4000 K .D6L

3000 K .D6R



LED LAMPS



More technical details about TÜV approved Fumagalli LED Lamps on page 512.

* ADD THESE SUFFIXES TO THE REFERENCES MENTIONED IN THE CATALOGUE

PHOTOMETRIC DATA SAMPLE - VIVI 400 GX53 LED



**6x10W GX53 LED
60W**
(power consumption)

Area: 10x10mt
Height: 3,5mt
37 lux

**SAVE
-48%**

=



**HQL 100W
112W**
(power consumption)

Area: 10x10mt
Height: 3,5mt
38 lux

VIVI 400

LARGE SIZE





MIDIPILAR/VIVI400
V50.254

Pcs 1
Kg 5,5
mc 0,092

NEW LOT/VIVI400
V50.115

Pcs 1
Kg 5,2
mc 0,071

VIVI 400
V50.000

Pcs 1
Kg 4,9
mc 0,09

MARIO/VIVI400
V50.129

Pcs 1
Kg 5,2
mc 0,07

EKTOR 3000 MIDIPILAR/VIVI400 1L	AKILLE 3000 MIDIPILAR/VIVI400 1L
V50.364.A10	V50.414.A10
Pcs 1 Kg 34 mc 0,262	

EKTOR 4000 MIDIPILAR/VIVI400 1L	AKILLE 4000 MIDIPILAR/VIVI400 1L
V50.371.A10	V50.421.A10
Pcs 1 Kg 41 mc 0,314	
EKTOR 3500 MIDIPILAR/VIVI400 1L	AKILLE 3500 MIDIPILAR/VIVI400 1L
V50.367.A10	V50.417.A10
Pcs 1 Kg 37,5 mc 0,284	

EKTOR 2500 MIDIPILAR/VIVI400 1L
V50.361.A10

Pcs 1
Kg 30,6
mc 0,235

VIVI 400

LARGE SIZE



