

# RIODET PERMISSIBLE

Permissible RIODET are electric detonators, suitable for use in potentially explosive atmospheres.

Permissible RIODET are provided in three delay period series, Instant (Z), Micro delay (M) and Long Period delay (D):

Permissible RIODET Micro delay are provided in 18 delay periods providing flexibility in short period blast designs.

Permissible RIODET Long Period delays are provided in 12 delay periods providing flexibility in long period blast designs.


The wide range of accurate delay times allows for a wider variety of blast design possibilities and assures better breakage, fragmentation and reduced vibration.

Permissible RIODET is ideal for environments that are susceptible to explosive air ignition such as underground coal mining and is offered in three sensitivities, depending on specific conditions: **S – Sensitive, I – Insensitive, and H – Highly Insensitive.**


Permissible RIODET are rigorously tested with 100m water column pressure for 48 hours, making the RIODET series optimal for difficult conditions.

## Advantages

- Safe, reliable and user friendly.
- Permissible for underground coal mining applications.
- Accurate delay timing.
- Highly visible delay tags.
- Water resistant.
- #8 strength detonator ensures reliable initiation of all cap-sensitive explosives.
- High pressure resistance.




1. Colour coded wire for high visibility underground and easy identification of delay series.



2. #8 strength copper shell detonator fitted with a double crimp.



3. The fastening band is easy to break manually in order to achieve a quicker loading operation.



4. Water resistant label which includes Delay Period, Timing, Length and Lot Number.

## Delay Times (Nominal values)

### Micro Delay (30ms) Series

Nº	Time (ms)
0	-
1	30
2	60
3	90
4	120
5	150
6	180
7	210
8	240
9	270
10	300
11	330
12	360
13	390
14	420
15	450
16	480
17	510
18	540

### Long Period Delay Series

Nº	Time (ms)
0	-
1	500
2	1.000
3	1.500
4	2.000
5	2.500
6	3.000
7	3.500
8	4.000
9	4.500
10	5.000
11	5.500
12	6.000

## Electrical Characteristics (Nominal values)

	Type S	Type I	Type H
Bridge Resistance (ohms)	1,2-1,6	0,3-0,5	0,03-0,05
Firing pulse (mW.s/ohm)	0,8-3	8-16	1.100-2.500
Safety Current A	0,20	0,45	4
Recommended trigger current (in series A)	1,2	2,5	25

## Standard Packaging, Class 1.1B (Nominal values)

Length (m)	Units per Box	Net Weight (kg)	Gross Weight (kg)	Application
3	500	17	19	For use in potentially explosive atmospheres.
5	250	12	14	
7	250	18	20	
10	250	22	24	

## Colour Code

	Type S	Type I	Type H
Instant	Red/white	Pink/White	Green/White
Long Period Delay	Red/Blue	Pink/Blue	Green/Blue
Micro Delay (30ms)	Red/Yellow	Pink/Yellow	Green/Yellow



Contact your local MAXAM representative for further information.

Transport Classification	Standard Packaging	Special Packaging	
Class	1.1B	1.4B	1.4S
UN Number	UN 0030	UN 0255	UN 0456

### SAFETY WARNING

Read the Instructions Safety Sheet and the Material Safety Data Sheet provided carefully before using RIODET. MAXAM strongly recommends not to use RIODET products with detonators and/or initiation systems supplied by other manufacturers in the same blast and declines all liability in these cases.

RIODET detonators must be stored at moderate temperatures in a dry and well ventilated place.

### LEGAL WARNING AND EXCLUSION OF LIABILITY

The information contained herein (the "Information") is not exhaustive and subject to periodical review. The data contained herein may vary on account of the particular operating and maintenance conditions and of external factors, such as humidity, temperature, or pressure. Maxam Europe, S.A. and/or its affiliates ("MAXAM") do not warrant or make any representation regarding the accuracy or completeness of the Information. MAXAM further reserves the right, in its sole discretion and without prior written notice, to modify the products described herein (the "Products") and/or their specifications. The use of the Products is an intrinsically dangerous activity and must, consequently, be restricted to qualified and trained users in possession of any necessary permits and licenses, and comply at all times with appropriate safety and risk prevention measures and with the applicable law. The use, storage, or otherwise handling, of the Products may be subject to local regulations and restrictions, which must be examined and observed by the user.

This document and any accompanying information (the "Documentation") is not intended to constitute, and shall not be construed as, an offer or contractual commitment on MAXAM's side. MAXAM expressly disclaims any liability towards third parties with regard to the Documentation. For further information about the Products, please contact your distributor or sales representative directly.

Distributor: