



Omada Industrial Easy Managed Switch

Datasheet

IES210GPP



Omada 10-Port Gigabit Industrial Easy Managed Switch with 6-Port PoE+ and 2-Port PoE++



Highlights

- 8× Gigabit RJ45 Ports (2× PoE++, 6× PoE+)
- 2× Gigabit Combo RJ45/SFP Slots
- 240W Power Budget* with up to 60W for Each PoE++ Port
- Professional Industrial-Grade Design: -40~75°C Operating Temperature, 6kV Lighting Protection, and 1+1 Redundant Power Input
- Abundant Features: Up to 820ft PoE,** VLAN, QoS, and STP/RSTP
- Centralized Cloud Management via the Web or Omada App[†]
- Durable IP40 Aluminum Casing and DIN-rail / Wall-mount Design

Product Pictures



Specifications

Hardware Features & Performance		
Model		IES210GPP
General	Interface	2× 10/100/1000 Mbps PoE++ RJ45 Ports 6× 10/100/1000 Mbps PoE+ RJ45 Ports 2× Gigabit SFP/RJ45 Combo Ports
	Flash	64 Mbit
	Port Standard	IEEE 802.3i:10BASE-T Ethernet IEEE 802.3u:100BASE-X Fast Ethernet IEEE 802.3ab:1000BASE-T Gigabit Ethernet IEEE 802.3z: 1000BASE-X Gigabit Ethernet (Optical fiber) IEEE 802.3x: Flow Control IEEE 802.1p: Traffic Class Expediting and Dynamic Multicast Filtering IEEE 802.1q: Virtual Bridged Local Area Networks IEEE 802.1d: Spanning Tree Protocol IEEE 802.1w: Rapid Spaning Tree Protocol IEEE 802.1ab: Station and Media Access Control Connectivity Discovery (LLDP)
PoE	PoE Standard	802.3 af/at/bt
	PoE Ports	Port 1-2, up to 60 W per port Port 3-8, up to 30 W per port
	PoE Power Budget	60 W (Input: 12 V / 7.2 A - 21 V / 3.7 A) 120 W (Input: 21 V / 6.7 A - 46 V / 3.1 A) 240 W (Input: 46 V / 5.7 A - 57 V / 4.4 A)
Performance	Switching Capacity	20 Gbps
	Packet Forwarding Rate	14.88 Mpps
	MAC Address Table	8K
	Packet Buffer	4 Mbit
	Transmission Method	Store and Forward
	Jumbo Frame	15 KB
Power Supply	Power Input	12-57V Dual Redundant DC Power Input
	Overload Current Protection	Yes
	Overload Voltage Protection	Yes
	Reverse Polarity Protection	Yes
	Standby Power Consumption	5.64 W max @ 12 VDC 6.17 W max @ 24 VDC 5.95 W max @ 48 VDC
	Max Power Consumption	85.74 W (with 60 W PD connected @ 12 VDC) 139.75 W (with 120 W PD connected @ 24 VDC) 258.33 W (with 240 W PD connected @ 48 VDC)
Fault Relay		24 V / 1 A Max. (Normally closed contact)

Hardware Features & Performance

Model		IES210GPP
Physical & Environment	MTBF	446898h @ 25°C
	Max Heat Dissipation	291.52 BTU/hr (with 60 W PD connected @ 12 VDC) 475.15 BTU/hr (with 120 W PD connected @ 24 VDC) 878.32 BTU/hr (with 240 W PD connected @ 48 VDC)
	Dimensions (W x D x H)	6.1 × 4.7 × 2.4 in (155 × 120 × 60 mm)
	Fan Quantity	Fanless
	Installation	DIN-rail mounting / Wall mounting
	IP Rating	IP40
	Operating Temperature	-40 °C to 75 °C (-40 °F to 167 °F)
	Storage Temperature	-40 °C to 85 °C (-40 °F to 185 °F)
	Operation Humidity	5% to 95% RH, non-condensing
	Storage Humidity	5% to 95% RH, non-condensing
	Surge Protection	±6 kV in common mode for Ethernet ports ±4 kV in common mode for DC power input ports
	ESD Protection	Air: ±8 kV, Contact: ±6 kV
	Certification	CE, FCC, RoHS
	EMC	IEC 61000-4-2 ESD: Contact: 6 kV; Air: 8 kV IEC 61000-4-3 RS: 80 MHz to 1 GHz: 20 V/m IEC 61000-4-4 EFT: Power: 2 kV; Signal: 2 kV IEC 61000-4-5 Surge: Power: 4 kV; Signal: 6 kV IEC 61000-4-6 CS: 10 V IEC 61000-4-8 PFMF: 100 A/m EN 55032/35 EN61000-6-2 EN61000-6-4
	Shock	IEC 60068-2-27
	Freefall	IEC 60068-2-32
	Vibration	IEC 60068-2-6

Software Features	
Model	IES210GPP
SDN Support	• Support Hardware Controller, Software Controller, Cloud-Based Controller • Automatic Device Discovery • Batch Configuration • Batch Firmware Upgrading • Unified Configuration
L2 Features	• Link Aggregation - Static Link Aggregation - Up to 4 aggregation groups and up to 6 ports per group • Loopback Detection • Flow Control - 802.3x Flow Control • Mirroring - Port Mirroring - One-to-One - Many-to-One - Ingress/Egress/Both • Port Statistics - Port Mirror Status - Traffic Statistics • 802.1ab LLDP • Spanning Tree - STP (802.1d) - RSTP (802.1w)
L2 Multicast	• IGMP Snooping - IGMP v1/v2/v3 Snooping - Fast Leave
VLAN	• MTU VLAN • Port-Based VLAN • 802.1Q Tag VLAN - Max 32 VLAN Groups - 4K VID
QoS	• 802.1p DSCP Priority • 8 Priority Queues • Priority Schedule Mode - WRR (Weighted Round Robin) • Queue Weight Config • Bandwidth Control - Port-Based Rate Limit • Storm Control - Multiple Control Modes (kbps/pps) - Broadcast/Multicast/Unknown-Unicast Control
Management	• Web-based GUI • DHCP Client • Cable Diagnostics • Digital Diagnostic Monitoring (DDM)

[†]Centralized cloud management functions require the use of the Omada SDN Controller. Zero-Touch Provisioning requires the use of the Omada Cloud-Based Controller. Go to the Omada Cloud-Based Controller Product List to find all the models supported by the Omada Cloud-Based Controller.

*The PoE budget is based on lab tests and may vary due to power supply, client limitations, and environmental factors.

**The speed of the ports that support 250m PoE transmission will be downgraded to 10 Mbps. Actual transmission distance may vary depending on the quality of the cables.

Specifications are subject to change without notice. All brands and product names are trademarks or registered trademarks of their respective holders. © 2025 TP-Link