

DECLARATION OF PERFORMANCE
DOP - SU364B

1. Unique identification code of the product-type:	Silicone Acetate Universal
2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):	BATCH NUMBER: SEE PRODUCT PACKAGING
3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:	SEALANT FOR FACADE ELEMENTS : EN-15651-1: F-EXT-INT-CC SEALANT FOR GLAZING EN-15651-2: TYPE G-CC SEALANTS FOR SANITARY JOINTS : EN-15651-3 : S1
4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):	Beorol d.o.o., Kirovljeva 10/26, Belgrade, Serbia
5. Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2):	NOT RELEVANT
6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:	SYSTEM 3 ; SYSTEM 3 FOR REACTION TO FIRE Notified Body: 1292 Notified Body : 2184 (fire)
7. In case of the declaration of performance concerning a construction product covered by a harmonized standard:	EN 15651-1 EN 15651-2 EN 15651-3
8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:	NOT RELEVANT
9. Declared performance	See Table 1

DECLARATION OF PERFORMANCE
DOP - SU364B

CONDITIONING: PROCEDURE A (ACCORDING TO ISO 8340)

SUBSTRATE: Glass (without primer) /Aluminum (with primer)

Table 1

Essential Characteristic	Declared Performance	Harmonized Standard
Reaction to Fire	Class E	-
Resistance to flow	≤3 mm	EN 15651-1,2,3
Loss of Volume	≤ 40 %	EN 15651-1,2,3
Adhesion / Cohesion at maintained extension after immersion in water	No Failure	EN 15651 -1,3
Adhesion / Cohesion at maintained extension for non-structural sealants used in joints in cold climate areas (-30 °C)	No Failure	EN 15651-1,2
Adhesion / cohesion properties after exposure to heat, water and artificial light	Pass Glass	EN 15651-2
Elastic Recovery	≥60%	EN 15651-2
Microbiological Growth	1	EN 15651-3
Durability	Pass	EN 15651-1,2,3

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Belgrade, 2025

Signature

