

SONICA® 45 Litres

Product	t name	Code
----------------	--------	------

SONICA 45L EP S3 *	090.003.0038
--------------------	--------------

Ultrasonic Cleaner

Accessories

Stainless steel wire basket Internal. dim. 460x260x190mm	090.004.0011
Stainless steel lid	090.004.0027
Stainless steel auxiliary tank SONICA 5300 Indicative dim. 500x300x200mm	090.004.0048
Stainless steel auxiliary tank SONICA 5200 Indicative dim. 500x300x150mm	090.004.0047
Stainless steel auxiliary tank SONICA 3300 Indicative dim. 300x240x150mm	090.004.0044
Stainless steel auxiliary tank SONICA 3200	090.004.0042

Indicative dim. 300x240x100mm

Also possible with Auxiliary tank 2400 series 090.004.0041



Special stainless steel tank made in AISI 316Ti thickness 20/10 with round tank corners for a better removing of dirt residuals after cleaning process. The tank is welded with TIG process

Further accessories on request

General Characteristics

Ultrasonic Cleaning is a safe and efficient modern procedure, which ensures perfect cleaning within the shortest time possible. It has many advantages over ordinary cleaning methods. Ultrasonics can remove even the most tenacious deposits from parts which would be difficult to reach by hand, it also reduces the risk of injury or infection which may occur during manual cleaning.

Notes for use as "Medical Devices"

Denomination: Ultrasonic Cleaning Equipment EMDN: Z12011302 **Field of application**: Ultrasonic Cleaning Equipment for surgical and dental instruments **Classification** Medical Devices Regulation Class I rule 13, Active MD, Non Invasive MD, Non Implantable MD

SOLTEC S.r.l.

Uffici Commerciali e Sede Legale: Via G. Röntgen 16 - 20136 Milano Tel. +39 02 58 308 378 - Fax +39 02 58 308 595 - www.soltec.it - info@soltec.it Produzione e Magazzino: Via G. Castelbarco, 17 - 20136 Milano - Tel. +39 02 58 324 131

Cod. fisc. e P.IVA: IT11127210158

N. Mecc.: MI 221750 - C.C.I.A.A. Milano N. 1441548

Iscr. Trib. Mi Reg. Soc. N. 343391/8444/41

Cap. Soc. Euro 110.500 i.v. - Iscr. Registro AEE Nr. IT08020000000435









SONICA® 45 Litres

Technical Data

Technical specification subject to change

Main line voltage	230/240V~50/60Hz	
Main input power/consumption	600 W	
Main input power with heating	1600 W	
Peak HF Ultrasound Power	1200 W	
US frequency	39 kHzh ± 1 kHz with SWEEP SYSTEM Technology	
Liquid drain	1/2"	
Transducers	12 (2 Piezoelectric ceramics each)	
Tank capacity [L]	45	
Weight [KG]	21	
Installation category	Class II according to EN 61010-1	
Environmental conditions	Temperature Rel. Hum. 80% up to 31°C with linear	
	decrease up to 50% at 40°C	
IP grade	IP 22	

IP 22

CE-compliant

EMC (EN 61326-1)

LV (EN 61010-1 EN 61010-2-040)

2017/745/UE Medical Device Regulation

Risk Class I according to the rule 13 to the MDR

Overheat switch: Automatic bimetallic Thermostat operating at 140°C fixed on the heating element

Effective Tank Internal Dimensions


External Appliance Dimensions

W/D/H (mm)	500 / 300 / 300	W/D/H (mm)	600 / 340 / 525
Max filling volume tank	45 L	Max operating tank volume	40 L

Constructive Materials

Housing Stainless steel AISI 304

Tank Stainless steel AISI 316Ti 20/10



Control panel available series

M MH ETH EP

NOT NOT NOT NOT AVAILABLE AVAILABLE





EP serie: The most technologically advanced of the SONICA range: Sweep System generator; modern digital display control panel window; degas time setting; cleaning times from 0 to 99 minutes; tank liquid temperature setting up to 70°C; memory for 9 cleaning programmes; jet program function to start quickly and easily cleaning cycle.