



SP912/BY35



excellent handling



high degree intensity



non-skid design



- ◇.Designed for construction and mining road, and short haul
- ◇.Special deep pattern improves the traction and braking performance
- ◇.Reduce heat-producing, enhance the service durability
- ◇.Strengthened steel belts protect the tyre body from puncture
- ◇.Extra deep tread pattern can increase mileage 20%

SIZE	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
7.50R16LT	6.00H	14PR	122/118	K	14.5	1500/1320	770
8.25R16LT	6.50H	16PR	128/124	K	15.0	1800/1600	770
8.25R20	6.5	16PR	139/137	K	16.5	2430/2300	930
9.00R20	7.0	16PR	144/142	K	16.5	2800/2650	900
10.00R20	7.5	18PR	149/146	K	18.5	3250/3000	930
11.00R20	8.0	18PR	152/149	K	20.5	3550/3250	930
12.00R20	8.5	18PR	154/151	J	21.5	3750/3450	830
	8.5	20PR	156/153	J	21.5	4000/3650	900
12R22.5	9.00	18PR	152/149	K	22.0	3550/3250	930