

Fiber Optic Light Cables

for Cold Light Fountains



Fiber Optic Light Cable with Straight Connector

| | |
|---------------------|---|
| 495 NE | Fiber Optic Light Cable , diameter 4.8 mm, length 300 cm |
| 495 NCS | Fiber Optic Light Cable , extremely heat-resistant, diameter 4.8 mm, length 250 cm |
| NEW 495 NCSC | Fiber Optic Light Cable , extremely heat-resistant, with safety locking device, diameter 4.8 mm, length 250 cm |
| 495 NB | Fiber Optic Light Cable , diameter 4.8 mm, length 180 cm |
| 495 ND | Fiber Optic Light Cable , diameter 3.5 mm, length 300 cm |
| 495 NA | Fiber Optic Light Cable , diameter 3.5 mm, length 230 cm |
| NEW 495 NAC | Fiber Optic Light Cable , with safety locking device, diameter 3.5 mm, length 230 cm |
| 495 NL | Fiber Optic Light Cable , diameter 3.5 mm, length 180 cm |
| 495 NTA | Fiber Optic Light Cable , diameter 2.5 mm, length 230 cm |
| 495 NT | Fiber Optic Light Cable , diameter 2.5 mm, length 180 cm |
| NEW 495 TIP | Fiber Optic Light Cable , highly heat resistant, diameter 4.8 mm, length 300 cm, optimized for 3D TIPCAM®1 and TIPCAM® |



Fiber Optic Light Cable with 90° Deflection to the Light Source

| | |
|---------|--|
| 495 NWL | Fiber Optic Light Cable , with 90° deflection to the cold light fountain on the fountain side, diameter 3.5 mm, length 300 cm |
| 495 NWM | Fiber Optic Light Cable , with 90° deflection to the cold light fountain on the fountain side, diameter 3.5 mm, length 230 cm |
| 495 NW | Fiber Optic Light Cable , with 90° deflection to the cold light fountain on the fountain side, diameter 3.5 mm, length 180 cm |
| 495 NTX | Fiber Optic Light Cable , with 90° deflection to the cold light fountain on the fountain side, diameter 2.5 mm, length 230 cm |
| 495 NTW | Fiber Optic Light Cable , with 90° deflection to the cold light fountain on the fountain side, diameter 2.5 mm, length 180 cm |



495 NVC



495 NV/NVL/NVB

Fiber Optic Light Cable with 90° Deflection to the Instrument

| | |
|--------------------|---|
| NEW 495 NVC | Fiber Optic Light Cable , with 90° deflection to the instrument, very narrow radius of curvature, diameter 4.8 mm, length 300 cm |
| 495 NVB | Fiber Optic Light Cable , with 90° deflection to the instrument, diameter 4.8 mm, length 300 cm |
| 495 NVL | Fiber Optic Light Cable , with 90° deflection to the instrument, diameter 3.5 mm, length 300 cm |
| 495 NV | Fiber Optic Light Cable , with 90° deflection to the instrument, diameter 3.5 mm, length 230 cm |



Light Adaptor, angled 90°

| | |
|--------|---|
| 495 EW | Light Adaptor , angled 90°, diameter 4.8 mm, free rotatable, to connect with standard telescopes |
|--------|---|

Adaptor for connecting KARL STORZ fiber optic light cables with endoscopes and light sources from other manufacturers, see page TP 132