

Fluidmatic XLD FE

Automatic Transmission Fluid

KEY DATA



MEETS THE REQUIREMENTS OF

- ALLISON C4 TES-228
- FORD Mercon V
- GM Dexron IIIG / IIH
- Mercedes-Benz: MB 236.6
- JASO M315-1A

MANUFACTURER APPROVALS

- ZF TE-ML 04D/14B/16L/20B/25B
- VOITH H55.6336.xx/H55 6335.xx
- MAN 339 Type V1/V2/Z2/Z11
- Daimler Trucks: DTFR 13C170
- Volvo 97341
- DANA-OHTM-ATF (Approval ID 23C-0004)

SUITABLE FOR

- Allison TES-389/TES-295
- VW G 052 162, 052 990, 055 025
- MAN 339 Type L1
- Mercedes-Benz: MB 236.1, 236.2, 236.5H, 236.7, 236.10, 236.11, 236.81
- Daimler Trucks: DTFR 13C100, DTFR 13C120, DTFR 13C140, DTFR 13C110, DTFR 13C160, DTFR 13C180
- Volvo 97340
- ZF TE-ML 05L/09/11A/11B/16L/17C
- Aisin Warner: JWS 3309; JWS 3314; JWS 3317
- BMW: P/N ETL 7045E; P/N LA 2634; P/N LT 71141; 5 Series,
- Honda: ATF Z-1
- Hyundai: SP-II; SP-III
- Mitsubishi: ATF J-2
- Mazda: ATF M-III; ATF M-V
- Nissan: Matic D; Matic J; Matic K; P/N 402
- Subaru: ATF; ATF-HP
- Toyota: TYPE T; TYPE T-II; TYPE T-III; TYPE T-IV;

TECHNOLOGY

Life-boost technology

Your peace of mind solution.

Life-boost technology will maximize the durability of the components and parts of the driveline equipment of your vehicle.

Our products will offer the best services as your vehicle will require drastically less maintenance providing reduced Total Cost Ownership (TCO) with on top a significant extended drain interval. A solution which offers a peace of mind throughout the normal lifetime of your vehicle.



APPLICATIONS

New generation automatic transmission fluid based on an advanced synthetic technology allowing extra-long drain and very high performance needed for the demanding requirements of modern heavy-duty automatic gearboxes.

Is particularly recommended for use on heavy duty automatic transmissions (found on buses, refuse trucks, utility vehicles etc.) manufactured by Voith and ZF requiring maximal drain intervals.

Can be used in Asian step-automatic transmissions requiring strong anti-shudder durability, including following OEMS: Nissan (Matic D,J,K), Mazda (M-III, M-V), Honda (Z-1), Toyota (T-IV, JWS3309), Hyundai, Kia, Mitsubishi (SP-II / SP-III).

And also, for the lubrication of materials used in Public Works or Quarries.

PERFORMANCES & CUSTOMER BENEFITS

- 🔥 Outstanding oxidation and thermal stability resulting in lower deposit and harmful acidic by-product formation, for a maximal drain interval capability.
- 🔥 Very stable viscosity profile, even under very severe constraints of shear, to ensure adequate lubrication all over time.
- 🔥 Excellent filterability allowing the reduction of filter change intervals, thus reducing operating costs.
- 🔥 Great foaming resistance for optimal lubrication condition and hydraulic efficiency
- 🔥 Very good protection against wear corrosion
- 🔥 Superior friction stability, to maintain and excellent shifting quality over a very long time.
- 🔥 Improved anti-wear technology compared to previous ATF technologies, for a better protection of components under the continuously increasing load constraints and a maximal efficiency of power transmission for better fuel economy.
- 🔥 Very good seal compatibility preventing oil leakages.
- 🔥 Enhanced friction modifiers improving driver comfort with smooth, efficient and no-shudder shifting.

CHARACTERISTICS*

TEST	UNIT	TEST METHOD	RESULT
Density at 15°C	kg/m ³	ISO 3675	850
Kinematic viscosity at 40°C	mm ² /s	ISO 3104	33.93
Kinematic viscosity at 100°C	mm ² /s	ISO 3104	7.155
Viscosity index	-	ISO 2909	183
Pour point	°C	ISO 3016	-45
Flash Point	°C	ISO 2592	212

*The characteristics given above are obtained with a standard tolerance threshold during production and may not be considered specifications.

RECOMMENDATIONS FOR USE

Before using the product, the vehicle's maintenance guide should be checked. Oil changes should be carried out in accordance with the manufacturer's recommendations.

The product should not be stored at temperatures over 60°C. It should be kept away from sunlight, intense cold and extreme temperature fluctuations. If possible, the packaging should not be exposed to the elements. Otherwise, the drums should be laid horizontally in order to avoid any contamination from water and to prevent the product's label from rubbing off.

HEALTH, SAFETY AND THE ENVIRONMENT

Based on the toxicological information available, this product should not cause any adverse health effects, provided it is used for its intended purpose and in accordance with the recommendations laid out in the Safety Data Sheet (SDS).

This can be obtained on request from your local reseller and is available for consultation at <https://ms-sds.totalenergies.com>.

This product should not be used for any purposes other than the ones for which it is intended.



TotalEnergies Lubricants / Last update of this datasheet: January 25

Some variations can be expected under normal production conditions, but these should not affect the product's expected performance irrespective of the site. The information contained in this document is subject to change without notice. Our products can be viewed on our website at www.lubricants.totalenergies.com.