

Air Top 2000 STC

The simple and cost-effective solution



The Air Top 2000 STC air heater impresses with its wide range of applications and low fuel consumption.

Thanks to its compact design, it can be installed in the shortest possible time. It can be mounted either inside or outside of the vehicle. Thanks to the stepless heating power control, the heater quietly and quickly heats the air in the vehicle interior or cargo area and constantly maintains the individually desired temperature. The user can select between air recirculation or fresh air mode.

Key benefits at a glance:

- 2 kW heating capacity
- Sturdy heater with compact dimensions and low fuel consumption
- Provides fast heat-up times, even and quiet heating operation thanks to stepless heating power control and fuel pump DP42
- Easy to service and maintain
- Suitable for continuous heating
- Suitable for use in vehicles for transporting hazardous materials (ADR)



Truck

Light
vehicles

Bus



Off-Highway

Specialty
vehicles

Technical specifications

	Air Top 2000 STC		
	Diesel		Gasoline
ECE Approval Number ECE R122 (Heating System)	E1 00 0216		
ECE Approval Number ECE R10 (EMC)	E1 06 1085		
Heat output, control range (kW)	0.9 – 2.0		1.0 – 2.0
Fuel consumption, control range (l/h)	0.12 – 0.24		0.14 – 0.27
Rated voltage (V)	12	24	12
Rated power consumption, control range (W)	15 – 30	13 – 28	15 – 30
Heating air volume flow against 0.5 mbar, control range (m³/h)	93		
Fuels*	Diesel EN 590, B100 FAME EN 14214 HVO DIN EN 15940		Gasoline EN 228, DIN 51626-1
Operating temperature range (°C)	-40 bis +40		
Dimensions L x W x H (mm)	310 x 120 x 118		
Weight (kg)	2.6		

* Other fuels on request.

Scope of delivery

- Heater
- Fuel pump DP42
- Fixing materials
- Technical documentation

Installation kit

- Cable harness
- Combustion air / exhaust gas kit
- Fuel pipe / fuel extractor
- Fixing materials

Recommended controls**

ThermoConnect

- Control of the heater via smartphone
- Status display on smartphone and pushbutton in vehicle
- Multiple switch-on times per day, programmable 7 days in advance
- Intelligent heating time management for selected departure time



UniControl

- Status display via multicolored LED
- 3 selectable switch-on times per day, programmable 7 days in advance
- Suitable for ADR
- Installation in universal mounting slot



MultiControl HD

- Status display via multicolored LED
- 3 selectable switch-on times per day, programmable 7 days in advance
- Universal installation without modifications to dashboard
- Diagnostic interface for Webasto Thermo Test



Rotary selector

- Status display via LED
- Stepless adjustment of heating power
- Suitable for ADR
- Installed in dash (requires drilling)



** Please see our Product Catalog for further controls.



Contact details

webasto.com