

Specificații tehnice (F 4.1)

Numărul procedurii de achiziție : ocds-b3wdp1-MD-1705502538213 din 31.01.2024
Obiectul achiziției : : „ Echipament tehnic pentru TV „Moldova 2”, CPV: 32300000-6 - Receptoare de televiziune și de radio și aparate de înregistrare sau de redare a sunetului sau a imaginii . Cererea ofertelor de prețuri (bunuri)

Nr	Denumirea bunurilor/serviciilor	Denumirea modelului bunului/serviciului	Țara de origine	Producătorul	Specificarea tehnică deplină solicitată de către autoritatea contractantă	Specificarea tehnică deplină propusă de către ofertant	Standarde de referință
1	2	3	4	5	6	7	
	Bunuri/ servicii						
	Lotul 1						
1	1.1. Camera Video	FX6 Full-Frame Cinema Camera (Body Only)	PRC	Sony	Imaging Lens Communication - Yes, with Autofocus Support Sensor Resolution - Actual: 12.9 Megapixel, Effective: 10.2 Megapixel Image Sensor - Full-Frame CMOS Image Stabilization - Supplies Stabilization Metadata Built-In ND Filter - 2 to 7 Stop Electronic ND Filter Internal Filter Holder - No Capture Type - Video Only Exposure Control Shutter Type - Electronic Rolling Shutter Shutter Type - Electronic Rolling Shutter Shutter Speed - 1/8000 to 1 Second ISO Sensitivity Range - 800 to 12,800 (Extended: 409,600) Gain - -3 to 30 dB (Native) Shutter Angle - 5.6 to 360° Advertised Dynamic Range 15 Stops White Balance - 2000 to 15,000K, Presets: ATW, Set A, Set B	Imaging Lens Communication - Yes, with Autofocus Support Sensor Resolution - Actual: 12.9 Megapixel, Effective: 10.2 Megapixel Image Sensor - Full-Frame CMOS Image Stabilization - Supplies Stabilization Metadata Built-In ND Filter - 2 to 7 Stop Electronic ND Filter Internal Filter Holder - No Capture Type - Video Only Exposure Control Shutter Type - Electronic Rolling Shutter Shutter Type - Electronic Rolling Shutter Shutter Speed - 1/8000 to 1 Second ISO Sensitivity Range - 800 to 12,800 (Extended: 409,600) Gain - -3 to 30 dB (Native) Shutter Angle - 5.6 to 360° Advertised Dynamic Range 15 Stops White Balance - 2000 to 15,000K, Presets: ATW, Set A, Set B	

				<p>Video Capture Internal Recording Modes XAVC-I DCI 4K (4096 x 2160) up to 59.94 fps [240 to 600 Mb/s VBR] UHD 4K (3840 x 2160) up to 59.94/100/120 fps [240 to 600 Mb/s VBR] 1920 x 1080p up to 59.94/100/120/150/200/240 fps [89 to 223 Mb/s VBR] XAVC-L UHD 4K (3840 x 2160) up to 59.94/100/120 fps [100 to 150 Mb/s] 1920 x 1080p up to 59.94/100/120/150/200/240 fps [35 to 50 Mb/s] External Recording Modes Raw 16-Bit via SDI/BNC 4096 x 2160 at 23.98/24.00/25/29.97/50/59.94 fps 3840 x 2160 at 23.98/24.00/25/29.97/50/59.94 fps Raw 16-Bit via HDMI 4264 x 2408 at 23.98/25/29.97/50/59.94 fps 4240 x 2385 at 23.98/25/29.97/50/59.94 fps Sensor Crop While Recording - 3840 x 2160 When Recording in Raw / Slow-Mo Fast-/Slow-Motion Support - Yes Gamma Curve - HDR-HLG, Rec709, S Cinetone, Standard Built-In Microphone Type Mono Audio Recording - 4-Channel 24-Bit 48 kHz LPCM Audio IP Streaming - Yes Interface Media/Memory Card Slot Dual Slot: CFexpress Type A / SD Video I/O - 1 x BNC (12G-SDI) Output, 1 x HDMI 1.0 Output Audio I/O - 2 x XLR 3-Pin Mic/Line (+48 V Phantom Power) Input on Included Handle 1 x 3.5 mm TRS Stereo Microphone Output Power I/O - 1 x Barrel (19.5VDC) Input Other I/O - 1 x USB-C (USB 3.2 / 3.1 Gen 1), 1 x Multi/Micro-USB Data, 1 x BNC (Timecode), 1 x 2.5 mm Sub-Mini Control,</p>	<p>Video Capture Internal Recording Modes XAVC-I DCI 4K (4096 x 2160) up to 59.94 fps [240 to 600 Mb/s VBR] UHD 4K (3840 x 2160) up to 59.94/100/120 fps [240 to 600 Mb/s VBR] 1920 x 1080p up to 59.94/100/120/150/200/240 fps [89 to 223 Mb/s VBR] XAVC-L UHD 4K (3840 x 2160) up to 59.94/100/120 fps [100 to 150 Mb/s] 1920 x 1080p up to 59.94/100/120/150/200/240 fps [35 to 50 Mb/s] External Recording Modes Raw 16-Bit via SDI/BNC 4096 x 2160 at 23.98/24.00/25/29.97/50/59.94 fps 3840 x 2160 at 23.98/24.00/25/29.97/50/59.94 fps Raw 16-Bit via HDMI 4264 x 2408 at 23.98/25/29.97/50/59.94 fps 4240 x 2385 at 23.98/25/29.97/50/59.94 fps Sensor Crop While Recording - 3840 x 2160 When Recording in Raw / Slow-Mo Fast-/Slow-Motion Support - Yes Gamma Curve - HDR-HLG, Rec709, S Cinetone, Standard Built-In Microphone Type Mono Audio Recording - 4-Channel 24-Bit 48 kHz LPCM Audio IP Streaming - Yes Interface Media/Memory Card Slot Dual Slot: CFexpress Type A / SD Video I/O - 1 x BNC (12G-SDI) Output, 1 x HDMI 1.0 Output Audio I/O - 2 x XLR 3-Pin Mic/Line (+48 V Phantom Power) Input on Included Handle 1 x 3.5 mm TRS Stereo Microphone Output Power I/O - 1 x Barrel (19.5VDC) Input Other I/O - 1 x USB-C (USB 3.2 / 3.1 Gen 1), 1 x Multi/Micro-USB Data, 1 x BNC (Timecode), 1 x 2.5 mm Sub-Mini Control, 1 x 3.5 mm Control, 1 x Proprietary Wireless - 2.4 / 5 GHz Wi-Fi 5 (802.11ac), NFC</p>	
--	--	--	--	--	---	--

					<p>1 x 3.5 mm Control, 1 x Proprietary Wireless - 2.4 / 5 GHz Wi-Fi 5 (802.11ac), NFC</p> <p>Monitor Display Size - 3.5" Resolution - 1280 x 720 (2,760,000 Dot) Display Type - Included External Touchscreen LCD</p> <p>Focus Focus Type - Auto and Manual Focus Autofocus Points - Phase Detection: 627</p> <p>General Battery Type BP-U Series (2 x included) Power Consumption 18 W Shoe Mount 1 x Intelligent Hot Shoe Tripod Mounting Thread 1 x 1/4"-20 Female, 1 x 3/8"-16 Female Accessory Mounting Thread 10 x 1/4"-20 on Camera Body 7 x 1/4"-20 on Included Handle Material of Construction Magnesium Alloy Media Card Reader 1 x CFexpress Type A / SD (included) SDXC Card,Storage Capacity 64 GB, Bus Type UHS-II, Speed Class 10, UHS Speed Class U3, Video Speed Class V90 (4x Included)</p>	<p>Monitor Display Size - 3.5" Resolution - 1280 x 720 (2,760,000 Dot) Display Type - Included External Touchscreen LCD</p> <p>Focus Focus Type - Auto and Manual Focus Autofocus Points - Phase Detection: 627 Battery Type Ş BP-U Series Power Consumption 18 W Shoe Mount 1 x Intelligent Hot Shoe Tripod Mounting Thread 1 x 1/4"-20 Female, 1 x 3/8"-16 Female Accessory Mounting Thread 10 x 1/4"-20 on Camera Body 7 x 1/4"-20 on Included Handle Material of Construction Magnesium Alloy</p> <p>Include : 1. Digital Power BP-U60 Li-Ion 5200mAh (2 buc) acumulator pentru SONY, Voltaj : 14.4 V 4 indicatoare cu led si touch pentru verificarea nivelului de incarcare ; Energie Nominala : 74.9 Wh Dimensiuni 50 mm x 40 mm x 50 mm Greutate : 396 g 2. Lexar Professional CFexpress Type A / SD USB 3.2 Gen 2 Reader (1 buc) 3. Lexar 64GB Professional 2000x UHS-II SDXC Memory Card (4 buc) Card Type : SDXC Storage Capacity : 64 GB Bus Type : UHS-II Speed Class : 10 UHS Speed Class : U3 Video Speed Class : V90 Speed (X-rating) : 2000x Read Speed Maximum: 300 MB/s Write Speed : Maximum: 260 MB/s Garanție : 36 luni</p>	
	Lotul 2						
2	2.1 Camera Video	FX3 Full-Frame Cinema Camera	PRC	Sony	<p>Imaging Lens Communication Yes, with Autofocus Support Sensor Resolution Actual: 12.1 Megapixel, Effective: 10.2 Megapixel</p>	<p>Imaging Lens Communication Yes, with Autofocus Support Sensor Resolution Actual: 12.1 Megapixel, Effective: 10.2 Megapixel</p>	

				<p>Image Sensor - 35.6 x 23.8 mm (Full-Frame) CMOS Image Stabilization Sensor-Shift, 5-Axis Built-In ND Filter – No; Internal Filter Holder – No; Capture Type - Stills & Video Exposure Control Shutter Type - Mechanical Focal Plane Shutter and Electronic Rolling Shutter Shutter Speed - 1/8000 to 1/4 Second in Movie Mode; 1/8000 to 1/60 Second in Auto Mode; 1/8000 to 30 Seconds in Manual Mode Bulb/Time Mode - Bulb Mode ISO Sensitivity Range - Video, 80 to 102,400 in Manual Mode (Extended: 80 to 409,600) Advertised Dynamic Range 15 Stops Exposure Modes - aperture Priority, Auto, Manual, Program, Shutter Priority Metering Range - -3 to 20 EV; White Balance - 2500 to 9900K Presets: Auto, Cloudy, Custom, Daylight, Flash, Fluorescent, Incandescent, Shade, Underwater Continuous Shooting - Up to 10 fps Interval Recording No Video Capture Internal Recording Modes H.265 Long GOP/XAVC HS 4:2:2 10-Bit UHD 4K (3840 x 2160) at 1/2/3/4/6/8/12/15/23.98/25/29.97/50/59.94/100/120 fps [50 to 280 Mb/s] H.265 Long GOP/XAVC HS 4:2:0 10-Bit 3840 x 2160 at 1/2/3/4/6/8/12/15/23.98/25/29.97/50/59.94/100/120 fps [30 to 150 Mb/s] MPEG-4 AVC/XAVC S 4:2:2 10-Bit 3840 x 2160 at 1/2/3/4/6/8/12/15/23.98/25/29.97/50/59.94/100/120 fps [100 to 280 Mb/s] 1920 x 1080p at 1/2/3/4/6/8/12/15/23.98/25/29.97/50/59.94/100/120/200/240 fps [50 Mb/s] MPEG-4 AVC/XAVC S 4:2:0 8-Bit 3840 x 2160 at 1/2/3/4/6/8/12/15/23.98/25/29.97/50/59.94/100/120 fps [60 to 200 Mb/s]</p>	<p>Image Sensor - 35.6 x 23.8 mm (Full-Frame) CMOS Image Stabilization Sensor-Shift, 5-Axis Built-In ND Filter – No; Internal Filter Holder – No; Capture Type - Stills & Video Exposure Control Shutter Type - Mechanical Focal Plane Shutter and Electronic Rolling Shutter Shutter Speed - 1/8000 to 1/4 Second in Movie Mode; 1/8000 to 1/60 Second in Auto Mode; 1/8000 to 30 Seconds in Manual Mode Bulb/Time Mode - Bulb Mode ISO Sensitivity Range - Video, 80 to 102,400 in Manual Mode (Extended: 80 to 409,600) Advertised Dynamic Range 15 Stops Exposure Modes - aperture Priority, Auto, Manual, Program, Shutter Priority Metering Range - -3 to 20 EV; White Balance - 2500 to 9900K Presets: Auto, Cloudy, Custom, Daylight, Flash, Fluorescent, Incandescent, Shade, Underwater Continuous Shooting - Up to 10 fps Interval Recording No Video Capture Internal Recording Modes H.265 Long GOP/XAVC HS 4:2:2 10-Bit UHD 4K (3840 x 2160) at 1/2/3/4/6/8/12/15/23.98/25/29.97/50/59.94/100/120 fps [50 to 280 Mb/s] H.265 Long GOP/XAVC HS 4:2:0 10-Bit 3840 x 2160 at 1/2/3/4/6/8/12/15/23.98/25/29.97/50/59.94/100/120 fps [30 to 150 Mb/s] MPEG-4 AVC/XAVC S 4:2:2 10-Bit 3840 x 2160 at 1/2/3/4/6/8/12/15/23.98/25/29.97/50/59.94/100/120 fps [100 to 280 Mb/s] 1920 x 1080p at 1/2/3/4/6/8/12/15/23.98/25/29.97/50/59.94/100/120/200/240 fps [50 Mb/s] MPEG-4 AVC/XAVC S 4:2:0 8-Bit 3840 x 2160 at 1/2/3/4/6/8/12/15/23.98/25/29.97/50/59.94/100/120 fps [60 to 200 Mb/s]</p>	
--	--	--	--	--	--	--

				<p>1920 x 1080p at 1/2/3/4/6/8/12/15/23.98/25/29.97/50/59.94/100/ 120/200/240 fps [16 to 100 Mb/s] MPEG-4 AVC/XAVC S-I 4:2:2 10-Bit 4096 x 2160 at 1/2/3/6/12/23.98/24.00/29.97/48.00/59.94 fps UHD 4K (3840 x 2160) at 1/2/3/4/6/8/12/15/23.98/25/29.97/59.94/100/120 fps [240 to 600 Mb/s] 1920 x 1080p at 1/2/3/4/6/8/12/15/23.98/25/29.97/50/59.94/100/ 120/200/240 fps [89 to 222 Mb/s] XAVC Proxy 1920 x 1080 [9 to 16 Mb/s] 1280 x 720 [6 Mb/s] External Recording Modes Raw 16-Bit via HDMI 4264 x 2408 at 23.98/25/50/59.94 fps; 3840 x 2160 at 23.98/25/50/59.94 fps; 1920 x 1080p at 23.98/25/50/59.94 fps; 1920 x 1080i at 50/59.94 fps Sensor Crop Modes Super35 / APS-C, 1080p (1920 x 1080) Fast-/Slow-Motion Support Yes Gamma Curve - HDR-HLG, S Cinetone, Standard Built-In Microphone Type - Stereo Audio Recording - 4-Channel 24-Bit LPCM Audio, 2-Channel 24-Bit LPCM Audio IP Streaming - Yes Still Image Capture Image Sizes - 16:9 JPEG /Raw, 12 MP, 5.1 MP, 3 MP, 1.3 MP, 11 MP, 4.6 MP, 2.7MP, 1.1MP, 10MP, 4.3MP, 2.6 MP, 8 MP, 3.4 MP, 2 MP, 0.8 MP Aspect Ratio 1:1, 3:2, 4:3, 16:9; Image File Format - HEIF, JPEG, Raw Interface Media/Memory Card Slot Dual Slot: CFexpress Type A / SD Video I/O - 1 x HDMI (Unspecified Signal) Output Audio I/O - 2 x XLR /1/4" TRS Combo Mic/Line Input on Included Handle 1 x 1/8" / 3.5 mm TRS Stereo Microphone Input on Camera Body</p>	<p>1920 x 1080p at 1/2/3/4/6/8/12/15/23.98/25/29.97/50/59.94/100/120 /200/240 fps [16 to 100 Mb/s] MPEG-4 AVC/XAVC S-I 4:2:2 10-Bit 4096 x 2160 at 1/2/3/6/12/23.98/24.00/29.97/48.00/59.94 fps UHD 4K (3840 x 2160) at 1/2/3/4/6/8/12/15/23.98/25/29.97/59.94/100/120 fps [240 to 600 Mb/s] 1920 x 1080p at 1/2/3/4/6/8/12/15/23.98/25/29.97/50/59.94/100/120 /200/240 fps [89 to 222 Mb/s] XAVC Proxy 1920 x 1080 [9 to 16 Mb/s] 1280 x 720 [6 Mb/s] External Recording Modes Raw 16-Bit via HDMI 4264 x 2408 at 23.98/25/50/59.94 fps; 3840 x 2160 at 23.98/25/50/59.94 fps; 1920 x 1080p at 23.98/25/50/59.94 fps; 1920 x 1080i at 50/59.94 fps Sensor Crop Modes Super35 / APS-C, 1080p (1920 x 1080) Fast-/Slow-Motion Support Yes Gamma Curve - HDR-HLG, S Cinetone, Standard Built-In Microphone Type - Stereo Audio Recording - 4-Channel 24-Bit LPCM Audio, 2-Channel 24-Bit LPCM Audio IP Streaming - Yes Still Image Capture Image Sizes - 16:9 JPEG /Raw, 12 MP, 5.1 MP, 3 MP, 1.3 MP, 11 MP, 4.6 MP, 2.7MP, 1.1MP, 10MP, 4.3MP, 2.6 MP, 8 MP, 3.4 MP, 2 MP, 0.8 MP Aspect Ratio 1:1, 3:2, 4:3, 16:9; Image File Format - HEIF, JPEG, Raw Interface Media/Memory Card Slot Dual Slot: CFexpress Type A / SD Video I/O - 1 x HDMI (Unspecified Signal) Output Audio I/O - 2 x XLR /1/4" TRS Combo Mic/Line Input on Included Handle 1 x 1/8" / 3.5 mm TRS Stereo Microphone Input on Camera Body 1 x 1/8" / 3.5 mm TRS Stereo Headphone Output</p>
--	--	--	--	---	---

				<p>1 x 1/8" / 3.5 mm TRS Stereo Headphone Output on Camera Body Power I/O - 1 x USB-C Input Other I/O - 1 x USB-C (Ethernet, USB 3.2 / 3.1 Gen 1) (Shared with Power Input), 1 x Multi/Micro-USB Wireless - 2.4 / 5 GHz Wi-Fi 5 (802.11ac), Bluetooth, NFC Mobile App Compatible Yes: Android & iOS</p> <p>Monitor Display Size - 3"; Resolution - 1,440,000 Dot Display Type - Articulating Touchscreen LCD</p> <p>Focus Focus Type - Auto and Manual Focus Focus Mode - Automatic, Continuous-Servo AF, Manual Focus Autofocus Points - Phase Detection: 627 Built-In Flash/Light - No Maximum Sync Speed - 1/125 Second Dedicated Flash System - TTL External Flash Connection Shoe Mount</p> <p>General Battery Type - Z-Series (3 x included) Tripod Mounting Thread - 1/4"-20 Female Accessory Mounting Thread 5 x 1/4"-20 on Camera Body, 3 x 1/4"-20 on Included Handle Material of Construction Magnesium Alloy Card Reader SDXC UHS II Read/Write speeds up to 260MB/190MB (included) SDXC Card Storage - Capacity 128 GB, Bus Type UHS-II, Speed Class 10, UHS Speed Class U3, Video Speed Class V90 (4x Included)</p>	<p>on Camera Body Power I/O - 1 x USB-C Input Other I/O - 1 x USB-C (Ethernet, USB 3.2 / 3.1 Gen 1) (Shared with Power Input), 1 x Multi/Micro-USB Wireless - 2.4 / 5 GHz Wi-Fi 5 (802.11ac), Bluetooth, NFC Mobile App Compatible Yes: Android & iOS</p> <p>Monitor Display Size - 3"; Resolution - 1,440,000 Dot Display Type - Articulating Touchscreen LCD</p> <p>Focus Focus Type - Auto and Manual Focus Focus Mode - Automatic, Continuous-Servo AF, Manual Focus Autofocus Points - Phase Detection: 627 Built-In Flash/Light - No Maximum Sync Speed - 1/125 Second Dedicated Flash System - TTL External Flash Connection Shoe Mount Tripod Mounting Thread - 1/4"-20 Female Accessory Mounting Thread 5 x 1/4"-20 on Camera Body, 3 x 1/4"-20 on Included Handle Material of Construction Magnesium Alloy</p> <p>Include : 1. Digital Power NP-FZ100 Sony 2280mAh Li-Ion Battery (3 buc) Tip acumulator Li-Ion NP-FZ100 Capacitate 2280 mAh / 16.4Wh Voltaj 7.2 V Dimensiuni 52 cm x 38 cm x 23 cm Greutate 85 g 2. Transcend RDF9 UHS-II Card Reader SDXC UHS II (1 buc) 1x SDXC (UHS-II [312 MB/s]) 1x microSDXC (UHS-I [104 MB/s]) 1x CompactFlash Type I (UDMA 7 [167 MB/s]) Micro-USB 3.1 Gen 1 Interface Supports SD/SDHC/SDXC Cards Supports UHS-II & UHS-I Standards Max. Read/Write Speed: 260 MB/s/190 MB/s System Connection : USB-A Male [3.0 / 3.1/3.2 Gen 1 (5 Gb/s). Includes Micro-USB to USB Type-A Cable 3. Lexar 64GB Professional 2000x UHS-II</p>	
--	--	--	--	--	---	--

						SDXC Memory Card (4 buc) Card Type : SDXC Storage Capacity : 64 GB Bus Type : UHS-II Speed Class : 10 UHS Speed Class : U3 Video Speed Class : V90 Speed (X-rating) : 2000x Read Speed Maximum: 300 MB/s Write Speed : Maximum: 260 MB/s Garanție : 36 luni	
	Lot nr.3						
3	3.1 Adaptor	Canon EF/EF-S Lens to Sony E Mount T Smart Adapter (Fifth Generation)	China	Meta bones	Camera Mount Sony E Lens Mount Canon EF/EF-S Electronic Communication Yes Display No	Camera Mount : Sony E Lens Mount : Canon EF/EF-S Electronic Communication Yes Display No Garanție : 36 luni	
	Lot nr.4						
4	4.1 Filter	67mm Variable Neutral Density Filter	USA	Tiffen	Filter Type Variable ND Density 0.6 (2-Stop) to 2.4 (8-Stop) Circular Size 67 mm Rear Filter Thread Front Accessory Thread / Bayonet Unthreaded Coatings None Filter Thickness 0.35" / 9 mm Filter Material Glass	Filter Type Variable ND Density 0.6 (2-Stop) to 2.4 (8-Stop) Circular Size 67 mm Rear Filter Thread Front Accessory Thread / Bayonet Unthreaded Coatings None Filter Thickness 0.35" / 9 mm Filter Material Glass Garanție : 36 luni	
	Lot nr.5						
5	5.1 Filter	77mm Variable Neutral Density Filter	USA	Tiffen	Filter Type Variable ND Density 0.6 (2-Stop) to 2.4 (8-Stop) Circular Size 77 mm Rear Filter Thread Front Accessory Thread / Bayonet Unthreaded Coatings None Filter Thickness 0.35" / 9 mm Filter Material Glass	Filter Type Variable ND Density 0.6 (2-Stop) to 2.4 (8-Stop) Circular Size 77 mm Rear Filter Thread Front Accessory Thread / Bayonet Unthreaded Coatings None Filter Thickness 0.35" / 9 mm Filter Material Glass Garanție : 36 luni	
	Lot nr.6						
6	6.1 Filter	Advanced UV Filter with 67mm diameter	Italia Japan	Man frotto	Specifications Filter Type UV CoatingType antireflective, oil repellent, scratch resistant, water repellent Filter Diameter 67 mm	Specifications Filter Type UV CoatingType antireflective, oil repellent, scratch resistant, water repellent Filter Diameter 67 mm	

					Number Of Coating Layers 12 Light Transmission 98.8% Filter Accessories Included Plastic carry case	Number Of Coating Layers 12 Light Transmission 98.8% Filter Accessories Included Plastic carry case Garanție : 36 luni	
	Lot nr.7						
7	7.1 Filter	Essential UV Filter with 77mm diameter	Italia Japan	Man frotto	Specifications Filter Type UV Coating Type antireflective, water repellent Filter Diameter 77 mm Number Of Coating Layers 10 Light Transmission 99% Filter Accessories Included Plastic carry case	Specifications Filter Type UV Coating Type antireflective, water repellent Filter Diameter 77 mm Number Of Coating Layers 10 Light Transmission 99% Filter Accessories Included Plastic carry case Garanție : 36 luni	
	Lot nr.8						
8	Obiectiv	FE 24-105mm f/4 G OSS Lens	PRC	Sony	Maximum Aperture f/4 Minimum Aperture f/22 Lens Mount Sony E Lens Format Coverage Full-Frame Angle of View 84° to 23° Minimum Focus Distance 38 cm Maximum Magnification 0.31x Optical Design 17 Elements in 14 Groups Diaphragm Blades 9, Rounded Focus Type Autofocus Image Stabilization Yes Filter Size 77 mm (Front)	Maximum Aperture: f/4 Minimum Aperture : f/22 Lens Mount : Sony E Lens Format Coverage : Full-Frame Angle of View : 84° to 23° Minimum Focus Distance : 1.25' / 38 cm Maximum Magnification : 0.31x Optical Design : 17 Elements in 14 Groups Diaphragm Blades : 9, Rounded Focus Type : Autofocus Image Stabilization : Yes Filter Size : 77 mm (Front) Dimensions (ø x L) : 3.28 x 4.46" / 83.4 x 113.3 mm Length at Maximum Extension : 6.2" / 157.5 mm Weight ; 1.46 lb / 663 g Garanție : 36 luni	
	Lot nr.9						
9	Obiectiv	FE 50mm f/1.4 GM Lens (Sony E)	PRC	Sony	Maximum Aperture f/1.4 Minimum Aperture f/16 Lens Mount Sony E Lens Format Coverage Full-Frame Angle of View 47° Minimum Focus Distance 41 cm Maximum Magnification 0.16x Optical Design 14 Elements in 11 Groups Diaphragm Blades 11, Rounded Focus Type Autofocus Image Stabilization No Filter Size 67 mm (Front)	Maximum Aperture : f/1.4 Minimum Aperture : f/16 Lens Mount : Sony E Lens Format Coverage : Full-Frame Angle of View : 47° Minimum Focus Distance : 16.1" / 41 cm Maximum Magnification : 0.16x Optical Design : 14 Elements in 11 Groups Diaphragm Blades : 11, Rounded Focus Type : Autofocus Filter Size : 67 mm (Front) Dimensions (ø x L) : 3.2 x 3.8" / 80.6 x 96 mm Weight ; 18.2 oz / 516 g	

						Garanție : 36 luni	
	Lotul nr.10						
10	10.1 Camera Cage	Camera Cage Basic Kit v2 for Sony FX3 & FX30 (Black)	PRC	Tilta	Mounting Battery Plate Type No Accessory Mounting - Multiple x Anti-Twist 1/4"-20 Female Thread, Multiple x - ARRI Anti-Twist 3/8"-16 Female Thread Camera Mounting 1/4"-20 Male Screw Tripod Mounting - Cage: 3/8"-16 Female Thread, Built-In Arca-Type Plate Shoe Mounting - 1 x Cold Shoe; Rosettes - No Rail Mounting - Side Plate: 1 x NATO Rail Cable Clamp - 1 x HDMI Clamp General Support Type - Cage Grip Type - Single Handgrip Camera Compatibility - Compatible whit Materials Aluminum, Silicone	Mounting Battery Plate Type No Accessory Mounting - Multiple x Anti-Twist 1/4"-20 Female Thread, Multiple x - ARRI Anti-Twist 3/8"-16 Female Thread Camera Mounting 1/4"-20 Male Screw Tripod Mounting - Cage: 3/8"-16 Female Thread, Built-In Arca-Type Plate Shoe Mounting - 1 x Cold Shoe; Rosettes - No Rail Mounting - Side Plate: 1 x NATO Rail Cable Clamp - 1 x HDMI Clamp General Support Type - Cage Grip Type - Single Handgrip Camera Compatibility - Compatible whit Materials Aluminum, Silicone Garanție : 36 luni	
	Lot nr.11						
11	11.1 Tripod	Ace XL MS CF	Ger Mania / Mexic	Sachtler	Payload Capacity Fluid Head: 2 to 8 kg Tripod: 20 kg, with appropriate head Height Range Complete System: 79 to 170 cm Folded Length Complete System: 86 cm Counterbalance 8 steps Pan / Tilt Drag 3 steps + zero Sliding Balance Plate Travel 10.4 cm Tilt Range +90 to -75° Head Attachment Fitting 75 mm bowl, integrated flat base Leveling Bubble Illuminated Operating Temperature -30 to 60°C Material of Construction Fluid Head: Aluminum Tripod: Carbon fiberFeet: Rubber	Payload Capacity Fluid Head: 2 to 8 kg Tripod: 20 kg, with appropriate head Height Range Complete System: 79 to 170 cm Folded Length Complete System: 86 cm Counterbalance 8 steps Pan / Tilt Drag 3 steps + zero Sliding Balance Plate Travel 10.4 cm Tilt Range +90 to -75° Head Attachment Fitting 75 mm bowl, integrated flat base Leveling Bubble Illuminated Operating Temperature -30 to 60°C Material of Construction Fluid Head: Aluminum Tripod: Carbon fiberFeet: Rubber Garanție : 36 luni	
	Lot nr.12						
12	Adaptor	Blue D-Tap To Sony a7S III Dummy Battery NP-FZ100 Cable	PRC	Kondor	The DTAP to dummy battery NP-FZ100 cable is 1m long. Length min 50 cm Connector type 1 D-TAP Connector type 2 NP-FZ100	The DTAP to dummy battery NP-FZ100 cable is 1m long. Length min 50 cm Connector type 1 D-TAP Connector type 2 NP-FZ100	

						Garanție : 36 luni	
	Lot nr.13						
13	V-mount plate	Compact V-Mount Battery Mounting System Cod: 4064	PRC	SmallRig	General (Compatibil with position 2) Physical Mounting - 2 x V-Mount Plate, Multiple x 1/4"-20 Threads, 1 x Arca-Swiss Plate Load Capacity - 5 kg Color - Black Material of Construction Aluminum Alloy, Stainless Steel	General (Compatibil with position 2) Physical Mounting - 2 x V-Mount Plate, Multiple x 1/4"-20 Threads, 1 x Arca-Swiss Plate Load Capacity - 5 kg Color - Black Material of Construction Aluminum Alloy, Stainless Steel Garanție : 36 luni	
	Lot nr.14						
14	V-mount plate	Battery Plate for Sony FX6 (V-Mount)	PRC	Tilta	Power Power Input V-Mount: VDC Power Output - D-Tap: VDC, LEMO 2-Pin: VDC, USB-A: VDC General Camera Power Method Connector Inputs/Outputs - 1 x Barrel Connector Plate Front / Battery Mount - V-Mount Number of Battery Bays - 1 Material of Construction - Aluminum, Stainless Steel	Power Power Input V-Mount: VDC Power Output - D-Tap: VDC, LEMO 2-Pin: VDC, USB-A: VDC General Camera Power Method Connector Inputs/Outputs - 1 x Barrel Connector Plate Front / Battery Mount - V-Mount Number of Battery Bays - 1 Material of Construction - Aluminum, Stainless Steel Garanție : 36 luni	
	Lot nr.15						
15	Mic	ECM-VG1 Electret Condenser Shotgun Microphone	PRC	Sony	Microphone Form Factor - Stand/Boom Mount Intended Sound Sources - Vocals, Room Ambiance Sound Field – Mono; Element Type - 1 x Electret Condenser Polar Pattern - Supercardioid Performance Frequency Range - 40 Hz to 20 kHz Maximum SPL - 127 dB SPL (1 kHz, 1% THD) Off-Axis Rejection - >3 dB at 60°, >15 dB at 120°, 20 dB at 180° Sensitivity - -33 dBV/Pa at 1 kHz Dynamic Range - 109 dB; Signal-to-Noise Ratio - 76 dB A-Weighted (1 kHz) Connectivity Output Connector - 1 x XLR 3-Pin Male Cable Length - 50 cm	Form Factor - Stand/Boom Mount Intended Sound Sources - Vocals, Room Ambiance Sound Field – Mono; Element Type - 1 x Electret Condenser Polar Pattern - Supercardioid Performance Frequency Range - 40 Hz to 20 kHz Maximum SPL - 127 dB SPL (1 kHz, 1% THD) Off-Axis Rejection - >3 dB at 60°, >15 dB at 120°, 20 dB at 180° Sensitivity - -33 dBV/Pa at 1 kHz Dynamic Range - 109 dB; Signal-to-Noise Ratio - 76 dB A-Weighted (1 kHz) Connectivity Output Connector - 1 x XLR 3-Pin Male Cable Length - 50 cm Power Power Sources - Phantom Power Operating Voltage - 40 to 52 V (Phantom Power)	

					Power Power Sources - Phantom Power Operating Voltage - 40 to 52 V (Phantom Power) Physical Mounting Thread Size - 5/8"-27 Female	Physical Thread Size - 5/8"-27 Female Garanție : 36 luni	
	Lot nr.16						
16	Battery V Mount	NERO M 14.8V Li-Ion V-Mount Battery (150Wh)	PRC	Hedbox	Mount Type : V – Mount (V-lock holder) Power Meter : Blue Color 4-LED Power Monitor (Display 100%, 75%, 50%, or 25% SOC capacity) Product Color : Dark Grey Bat. Cell Model : LG High Load Stand 18650 x 16 Bat. Cell Chemistry : Lithium-Ion Output Voltage :14.8V DC Minimum Out Voltage : 10.0V DC (Auto Power Control) Capacity : 10400 mAh / 150 Wh Maximum Load : 13A / 190W USB Output : 5V, 12W / 2.4A max (Dust Protection Cover) D-Tap Output : 14.8V, 100W / 6.8A max (Dust Protection Cover) Internal Protection : Cells Framing Construction System Maximum Charge : 16.8V / 3.0A	Mount Type : V – Mount (V-lock holder) Power Meter : Blue Color 4-LED Power Monitor (Display 100%, 75%, 50%, or 25% SOC capacity) Product Color : Dark Grey Bat. Cell Model : LG High Load Stand 18650 x 16 Bat. Cell Chemistry : Lithium-Ion Output Voltage :14.8V DC Minimum Out Voltage : 10.0V DC (Auto Power Control) Capacity : 10400 mAh / 150 Wh Maximum Load : 13A / 190W USB Output : 5V, 12W / 2.4A max (Dust Protection Cover) D-Tap Output : 14.8V, 100W / 6.8A max (Dust Protection Cover) Internal Protection : Cells Framing Construction System Maximum Charge : 16.8V / 3.0A Garanție : 36 luni	
	Lot nr.17						
17	Backpack	Axis V2 Backpack (Black, 24L)	PRC	Tenba	Backpack Exterior (L x W x H) - 55 x 37 x 35 cm Interior (L x W x H) - 52 x 35 x 22 cm Soft padding – Yes; Hard padding - Yes Suitable for – Camera; Color - Black Zippers Blue YKK® zippers Nylon lining – Yes; Removable dividers – Yes; Pocket(s) outside – Yes Net inside – Yes; Carrying handle – Yes; Tablet compartment – Yes rainProtector - Yes Material 1000d Cordura	Backpack Dimensiuni Exterior: 32 cm x 52 cm x 22 cm Interior: 29 cm x 47 cm x 15 cm Compartiment laptop: 25 cm x 37 cm x 2 cm Greutate 2.1 kg Volum 24 litri Culoare Negru Tip inchidere Fermoar Material Nailon balistic 1680D (exterior), nailon ripstop (interior) Optiuni de transport Maner deasupra / Curele de umar captusite / Curea de piept Capacitate transport 1-2 camere mirrorless sau DSLR sau Cine, 6-8 obiective de pana la 500mm 4.0, un laptop de 16 inchii si o drona compacta gen DJI Mavic	

						1 x rucsac Tenba Axis V2 (Black, 24L); 1 x husa de ploaie Garanție : 36 luni
	Lot nr.18					
18	18.1 LED	S-2241 Bi-color SMD On-camera LED light	PRC	SWIT	153pcs ultra bright long-life LEDs Surface mounted LED technology 120°(half-declined 68°) wide beam angle 3200K-5600K continuously adjustable 20W power, 640Lux @ 1 meter center 10%-100% flick-free dimming Super high CRI Ra≥93, TLCI≥97 Interchangeable various DV battery plates (included 1 S-7004F, included 1 S-7004U) Support DC 6-17V input from D-tap Provide ball head, diffuser, and bag	Item Type : 1x LED Light Panel 153 ultra-bright, bi-color, surface-mounted LEDs Wide beam angle of 120° (half-declined at 68°) Color Temperature : 3200 to 5600K +/- 200K Dimming :Built-In Dimmer • 10 to 100% Cooling System : Fan CRI Ra≥93, TLCI≥97 Photometric : 60 fc / 640 Lux at 3.3' / 1 m* Beam Angle : 120° Included Filters : Diffusion Included Storage Case : 1x Case Included Adapter : 1x Ball Head Mount: Accessory Foot to 1/4"-20 Male Screw Included Adapter / Cable : 1x D-Tap to Barrel / Coax Cable Include : 1 S-7004F-1 buc ; 1 S-7004U-1 buc Garanție : 36 luni
	Lot nr.19					
19	19.1 LED	COB 200x S Bi-Color LED Monolight	PRC	Amaran	Light Fixture Item Type - 1 x COB LED Monolight; Included Light Modifier - 1 x Reflector Included Storage Case – No; Lumens - 17,000 Photometrics 111° at 3200K: 523 fc / 5630 Lux at 3.3' / 1 m; 62 fc / 675 Lux at 9.8' / 3 m 25 fc / 275 Lux at 16.4' / 5 m 111° at 5600K: 594 fc / 6400 Lux at 3.3' / 1 m; 70 fc / 764 Lux at 9.8' / 3 m 27 fc / 291 Lux at 16.4' / 5 m 26° at 3200K: 3734 fc / 40,200 Lux at 3.3' / 1 m (with Reflector) 382 fc / 4120 Lux at 9.8' / 3 m (with Reflector) 135 fc / 1455 Lux at 16.4' / 5 m (with Reflector) 26° at 5600K: 4217 fc / 45,400 Lux at 3.3' / 1 m (with Reflector) 430 fc / 4630 Lux at 9.8' / 3 m (with Reflector) 151 fc / 1635 Lux at 16.4' / 5 m (with Reflector) 430 fc / 4630 Lux at 9.8' / 3 m (with Reflector)	Light Fixture Item Type - 1 x COB LED Monolight; Included Light Modifier - 1 x Reflector Included Storage Case – No; Lumens - 17,000 Photometrics 111° at 3200K: 523 fc / 5630 Lux at 3.3' / 1 m; 62 fc / 675 Lux at 9.8' / 3 m 25 fc / 275 Lux at 16.4' / 5 m 111° at 5600K: 594 fc / 6400 Lux at 3.3' / 1 m; 70 fc / 764 Lux at 9.8' / 3 m 27 fc / 291 Lux at 16.4' / 5 m 26° at 3200K: 3734 fc / 40,200 Lux at 3.3' / 1 m (with Reflector) 382 fc / 4120 Lux at 9.8' / 3 m (with Reflector) 135 fc / 1455 Lux at 16.4' / 5 m (with Reflector) 26° at 5600K: 4217 fc / 45,400 Lux at 3.3' / 1 m (with Reflector) 430 fc / 4630 Lux at 9.8' / 3 m (with Reflector) 151 fc / 1635 Lux at 16.4' / 5 m (with Reflector) Color Temperature - 2700 to 6500K; Color Modes

					<p>151 fc / 1635 Lux at 16.4' / 5 m (with Reflector) Color Temperature - 2700 to 6500K; Color Modes - Daylight, Tungsten Color Accuracy Standard - CRI 95, TLCI 98, CQS 97, SSI 90 at 3200K, SSI 89 at 5600K, TM-30 Rf 97, TM-30 Rg 100 Dimming - Built-In Dimmer (Continuous), • 0 to 100% Cooling System - Fan Beam Angle - 26° with Included Reflector, 111° Unmodified Umbrella Mount – Yes; Front Accessory Mount - Bowens S Connectivity Wireless Remote Control Type - Bluetooth Wireless Range - 100 m (Bluetooth) Power & I/O Power Source - AC to DC Adapter (Included) Battery Plate Type - 2 x V-Mount Battery - 2 x V-Mount Rechargeable AC Input Power - 100 to 240 VAC, 50 / 60 Hz; DC Input Power - 48 VDC Included Adapter / Cable 1 x Edison Plug to Unspecified AC to DC Adapter Inline Switch – No; Power Pass-Thru - No Power Consumption - 229 W (Maximum) Mounting Fixture Mounting - 1 x 5/8" Receiver General Display - LCD</p>	<p>- Daylight, Tungsten Color Accuracy Standard - CRI 95, TLCI 98, CQS 97, SSI 90 at 3200K, SSI 89 at 5600K, TM-30 Rf 97, TM-30 Rg 100 Dimming - Built-In Dimmer (Continuous), • 0 to 100% Cooling System - Fan Beam Angle - 26° with Included Reflector, 111° Unmodified Umbrella Mount – Yes; Front Accessory Mount - Bowens S Connectivity Wireless Remote Control Type - Bluetooth Wireless Range - 100 m (Bluetooth) Power & I/O Power Source - AC to DC Adapter (Included) Battery Plate Type - 2 x V-Mount Battery - 2 x V-Mount Rechargeable AC Input Power - 100 to 240 VAC, 50 / 60 Hz; DC Input Power - 48 VDC Included Adapter / Cable 1 x Edison Plug to Unspecified AC to DC Adapter Power Consumption - 229 W (Maximum) Mounting Fixture Mounting - 1 x 5/8" Receiver General Display - LCD Garantie : 36 luni</p>	
	Lotnr.20						
20	20.1 LED	LS 60x Bi-Color LED Focusing Flood Light	PRC	Aputure	<p>Light Fixture Item Type – 1 x LED Focusing Flood Light Included Light Modifier – 1 x Barndoors Included Storage Case – 1 x Case Photometrics 15° at 3200K: 2799 fc / 30,132 Lux at 3.3' / 1 m; 352 fc / 3794 Lux at 9.8' / 3 m 124 fc / 1339 Lux at 16.4' / 5 m 45° at 3200K: 497 fc / 5357 Lux at 3.3' / 1 m; 60 fc / 647 Lux at 9.8' / 3 m 20 fc / 223 Lux at 16.4' / 5 m</p>	<p>Light Fixture Item Type – 1 x LED Focusing Flood Light Included Light Modifier – 1 x Barndoors Included Storage Case – 1 x Case Photometrics 15° at 3200K: 2799 fc / 30,132 Lux at 3.3' / 1 m; 352 fc / 3794 Lux at 9.8' / 3 m 124 fc / 1339 Lux at 16.4' / 5 m 45° at 3200K: 497 fc / 5357 Lux at 3.3' / 1 m; 60 fc / 647 Lux at 9.8' / 3 m 20 fc / 223 Lux at 16.4' / 5 m</p>	

				<p>15° at 5600K: 3110 fc / 33,480 Lux at 3.3' / 1 m; 393 fc / 4241 Lux at 9.8' / 3 m 134 fc / 1451 Lux at 16.4' / 5 m</p> <p>45° at 5600K: 539 fc / 5803 Lux at 3.3' / 1 m; 65 fc / 703 Lux at 9.8' / 3 m 24 fc / 268 Lux at 16.4' / 5 m</p> <p>Color Temperature 2700 to 6500K Color Modes – Daylight, Tungsten Color Accuracy Standard – CRI 95, TLCI 95 Dimming - App-Controlled / Built-In Dimmer (Continuous), • 0 to 100% Cooling System – Fan; Beam Angle – 15 to 45°; Built-In Flash – No Umbrella Mount – No Front Accessory Mount – Proprietary</p> <p>Connectivity Wireless Remote Control Type – Bluetooth Wireless Range – 80 m</p> <p>Power & I/O Power Source – AC to DC Adapter (Included) Inputs/Outputs – 1 x Built-In Cable with Proprietary Power Input Battery Plate Type -2 x L-Series / NP-F (Included), 1 x V-Mount (Included) Battery 2 x Type L-Series / NP-F Rechargeable, 12 to 16.8 VDC or 1 x Type L-Series / NP-F Rechargeable, 6 to 8.4 VDC or 1 x D-Tap Rechargeable, 12 to 16.8 VDC AC Input Power – 100 to 240 VAC, 50 / 60 Hz DC Input Power – 6 to 19 VDC Included Adapter / Cable 1 x Edison Plug to Proprietary AC to DC Adapter 1 x D-Tap to Proprietary Cable Inline Switch – No; Power Pass-Thru – No Power Consumption 90 W (Maximum)</p> <p>Mounting Yoke Type – Manually-Operated Yoke Fixture Mounting – 1 x 5/8" Receiver (Via Yoke Mount)</p> <p>General Display – OLED Certifications – RoHS, CE, CE RED, KC, PSE,</p>	<p>15° at 5600K: 3110 fc / 33,480 Lux at 3.3' / 1 m; 393 fc / 4241 Lux at 9.8' / 3 m 134 fc / 1451 Lux at 16.4' / 5 m</p> <p>45° at 5600K: 539 fc / 5803 Lux at 3.3' / 1 m; 65 fc / 703 Lux at 9.8' / 3 m 24 fc / 268 Lux at 16.4' / 5 m</p> <p>Color Temperature 2700 to 6500K Color Modes – Daylight, Tungsten Color Accuracy Standard – CRI 95, TLCI 95 Dimming - App-Controlled / Built-In Dimmer (Continuous), • 0 to 100% Cooling System – Fan; Beam Angle – 15 to 45°; Built-In Flash – No Umbrella Mount – No Front Accessory Mount – Proprietary</p> <p>Connectivity Wireless Remote Control Type – Bluetooth Wireless Range – 80 m</p> <p>Power & I/O Power Source – AC to DC Adapter (Included) Inputs/Outputs – 1 x Built-In Cable with Proprietary Power Input Battery Plate Type -2 x L-Series / NP-F (Included), Include : Acumulator Digital Power V-mount BP-150W Li-Ion 14.8V / 150Wh : Tip acumulator V-mount/BP-150W Li-Ion Voltaj 14.8 V Capacitate 10400 mAh Dimensiuni 96 mm x 152 mm x 53 mm 2 x Type L-Series / NP-F Rechargeable, 12 to 16.8 VDC or 1 x Type L-Series / NP-F Rechargeable, 6 to 8.4 VDC or 1 x D-Tap Rechargeable, 12 to 16.8 VDC AC Input Power – 100 to 240 VAC, 50 / 60 Hz DC Input Power – 6 to 19 VDC Included Adapter / Cable 1 x Edison Plug to Proprietary AC to DC Adapter 1 x D-Tap to Proprietary Cable Inline Switch – No; Power Pass-Thru – No Power Consumption 90 W (Maximum)</p> <p>Mounting Yoke Type – Manually-Operated Yoke Fixture Mounting – 1 x 5/8" Receiver (Via Yoke Mount)</p>	
--	--	--	--	---	---	--

					FCC, BIS Materials – Aluminum (Housing)	General Display – OLED Certifications – RoHS, CE, CE RED, KC, PSE, FCC, BIS Materials – Aluminum (Housing) Pachetul include: 1x LS 60x Lamp Head 1x LS 60d/x Barndoors 1x Power Supply 1x IEC Power Cable 1x Dual Sony NP-F Battery Plate Adapter for LS 60 1x D-Tap Power Cable (4-pin) 1x Bowens Mount to LS 60 Adapter 1x Carrying Case Garanție : 36 luni	
	Lotnr.21						
21	21.1 LED	F22x 2x2 Bi-Color LED Flexible Mat (V- Mount)	PRC	Amaran	Light Fixture Item Type 1 x LED Flexible Light Included Light Modifier 1 x Softbox with Removable Grid Included Storage Case 1 x Case Photometrics 3200K:562 fc / 6050 Lux at 3.3' / 1 m; 5600K:646 fc /6960 Lux at 3.3' /1 m Color Temperature - 2500 to 7500K; Color Modes - Daylight, Tungsten Color Accuracy Standard CRI 95 at 5600K, TLCI 98 at 5600K, CQS 96 at 5600K, SSI 81 at 5600K Dimming - Controller Included (Continuous), • 0 to 100% Cooling System – Passive; Expected Lamp Life - 50,000 Hours Built-In Flash - No Front Accessory Mount Proprietary Connectivity Wireless Remote Control Type – Bluetooth; Wireless Range - 80 m (Bluetooth) Power & I/O Power Source - AC to DC Adapter (Included) Inputs/Outputs - 1x USB-C DMX Input, *Adapter Required 1 x XLR 3-Pin Power Input, 1 x Proprietary Power Output Battery Plate Type - 1 x V-Mount (Built-In)	Light Fixture Item Type 1 x LED Flexible Light Included Light Modifier 1 x Softbox with Removable Grid Included Storage Case 1 x Case Photometrics 3200K:562 fc / 6050 Lux at 3.3' / 1 m; 5600K:646 fc /6960 Lux at 3.3' /1 m Color Temperature - 2500 to 7500K; Color Modes - Daylight, Tungsten Color Accuracy Standard CRI 95 at 5600K, TLCI 98 at 5600K, CQS 96 at 5600K, SSI 81 at 5600K Dimming - Controller Included (Continuous), • 0 to 100% Cooling System – Passive; Expected Lamp Life - 50,000 Hours Built-In Flash - No Front Accessory Mount Proprietary Connectivity Wireless Remote Control Type – Bluetooth; Wireless Range - 80 m (Bluetooth) Power & I/O Power Source - AC to DC Adapter (Included) Inputs/Outputs - 1x USB-C DMX Input, *Adapter Required 1 x XLR 3-Pin Power Input, 1 x Proprietary Power Output Battery Plate Type - 1 x V-Mount (Built-In)	

					<p>Battery - 1 x Rechargeable, 14.4 to 28.8 VDC AC Input Power - 100 to 240 VAC, 50 / 60 Hz DC Input Power - 48 VDC at 2.5 A Included Adapter /Cable 1x Edison Plug to XLR 3-Pin AC to DC Adapter,• 48 VDC Inline Switch – No; Power Pass-Thru – No; Power Consumption - 240 W</p> <p>Mounting Fixture Mounting 1 x 5/8" Receiver Included Adapter 1 x Non-Swivel Mount: 5/8" Receiver to 5/8" Receiver 2 x Non-Swivel Mount: 5/8" Stud to 5/8" Stud</p> <p>General Display – OLED; Certifications - CE, FCC, RoHS, cTUVus Materials - Plastic (Housing)</p>	<p>Include : 1.Acumulator Digital Power V-mount BP-150W Li-Ion 14.8V / 150Wh : Tip acumulator V-mount/BP-150W Li-Ion Voltaj 14.8 V Capacitate 10400 mAh Dimensiuni 96 mm x 152 mm x 53 mm</p> <p>2. Amaran USB-C to DMX Adapter with USB-C Input AC Input Power - 100 to 240 VAC, 50 / 60 Hz DC Input Power - 48 VDC at 2.5 A Included Adapter /Cable 1x Edison Plug to XLR 3-Pin AC to DC Adapter,• 48 VDC Inline Switch – No; Power Pass-Thru – No; Power Consumption - 240 W</p> <p>Mounting Fixture Mounting 1 x 5/8" Receiver Included Adapter 1 x Non-Swivel Mount: 5/8" Receiver to 5/8" Receiver 2 x Non-Swivel Mount: 5/8" Stud to 5/8" Stud</p> <p>General Display – OLED; Certifications - CE, FCC, RoHS, cTUVus Materials - Plastic (Housing)</p> <p>Pachetul include: Amaran F22x 2x2 Bi-Color LED Flexible Mat (V-Mount) F22x Control Box with V-Mount Plate F22 9.8" Head Extension Cable F22 Support Bracket Flex Light Right Angle Baby Pin Adapter Flex Light Straight Baby Pin Adapter Tilting Stand Mount F22 Softbox Frame F22 Diffusion Cloth 1 (1/2 Grid Cloth) F22 Diffusion Cloth 2 (2.5 Stop) F22 Light Control Grid Multi-Voltage AC Power Supply AC Power Cable Carrying Case</p> <p>Garanție : 36 luni</p>	
	Lotnr.22						
22	22.1 LED	Nova P300c RGB LED Light Panel	PRC	Aputure	<p>Light Fixture Item Type - 1 x LED Array LED Light Panel Included Filters - Diffusion (Built-In)</p>	<p>Light Fixture Item Type - 1 x LED Array LED Light Panel Included Filters - Diffusion (Built-In)</p>	

				<p>Included Storage Case No</p> <p>Photometrics 120° at 2700K: - 692 fc / 7450 Lux at 3.3' / 1 m, 82 fc / 890 Lux at 9.8' / 3 m, 32 fc / 350 Lux at 16.4' / 5 m 120° at 3200K: - 761 fc / 8200 Lux at 3.3' / 1 m, 89 fc / 960 Lux at 9.8' / 3 m, 34 fc / 370 Lux at 16.4' / 5 m 120° at 4300K: - 798 fc / 8600 Lux at 3.3' / 1 m, 92 fc / 1000 Lux at 9.8' / 3 m, 36 fc / 395 Lux at 16.4' / 5 m 120° at 5500K: - 836 fc / 9000 Lux at 3.3' / 1 m, 102 fc / 1100 Lux at 9.8' / 3 m, 39 fc / 430 Lux at 16.4' / 5 m Color Temperature - 2000 to 10,000K Color Modes - RGB Color Accuracy Standard - CRI 95, TLCI 95, CQS 92 at 2500K, CQS 97 at 10000K, SSI 85 at 3200K, SSI 74 at 5500K Dimming App-Controlled / Controller Included / DMX (Continuous), • 0 to 100% Cooling System - Fan Beam Angle - 120°; Built-In Flash – No; Umbrella Mount - No Front Accessory Mount - Proprietary</p> <p>Connectivity Wireless Remote Control Type - Bluetooth</p> <p>Power & I/O Power Source - AC Power (Cable Included)</p> <p>Inputs/Outputs 1 x XLR 5-Pin DMX Input, 1 x powerCON Power Input, 1 x XLR 3-Pin Battery Input 1 x powerCON Power Input Battery - 1 x Rechargeable, 48 VDC AC Input Power - 100 to 240 VAC, 50 / 60 Hz at 4 A DC Input Power - 24 to 48 VDC Included Adapter / Cable - 1 x Edison Plug to powerCON Cable Inline Switch – No; Power Pass-Thru - No Power Consumption - 360 W</p> <p>Mounting Yoke Type - Manually-Operated Yoke Fixture Mounting - 1 x 1-1/8" Stud with 5/8"</p>	<p>Included Storage Case No</p> <p>Photometrics 120° at 2700K: - 692 fc / 7450 Lux at 3.3' / 1 m, 82 fc / 890 Lux at 9.8' / 3 m, 32 fc / 350 Lux at 16.4' / 5 m 120° at 3200K: - 761 fc / 8200 Lux at 3.3' / 1 m, 89 fc / 960 Lux at 9.8' / 3 m, 34 fc / 370 Lux at 16.4' / 5 m 120° at 4300K: - 798 fc / 8600 Lux at 3.3' / 1 m, 92 fc / 1000 Lux at 9.8' / 3 m, 36 fc / 395 Lux at 16.4' / 5 m 120° at 5500K: - 836 fc / 9000 Lux at 3.3' / 1 m, 102 fc / 1100 Lux at 9.8' / 3 m, 39 fc / 430 Lux at 16.4' / 5 m Color Temperature - 2000 to 10,000K Color Modes - RGB Color Accuracy Standard - CRI 95, TLCI 95, CQS 92 at 2500K, CQS 97 at 10000K, SSI 85 at 3200K, SSI 74 at 5500K Dimming App-Controlled / Controller Included / DMX (Continuous), • 0 to 100% Cooling System - Fan Beam Angle - 120°; Built-In Flash – No; Umbrella Mount - No Front Accessory Mount - Proprietary</p> <p>Connectivity Wireless Remote Control Type - Bluetooth</p> <p>Power & I/O Power Source - AC Power (Cable Included)</p> <p>Inputs/Outputs 1 x XLR 5-Pin DMX Input, 1 x powerCON Power Input, 1 x XLR 3-Pin Battery Input 1 x powerCON Power Input Battery - 1 x Rechargeable, 48 VDC : Aperture 2-Bay Battery Power Station AC Input Power - 100 to 240 VAC, 50 / 60 Hz at 4 A DC Input Power - 24 to 48 VDC Included Adapter / Cable - 1 x Edison Plug to powerCON Cable Inline Switch – No; Power Pass-Thru - No Power Consumption - 360 W</p> <p>Mounting Yoke Type - Manually-Operated Yoke</p>
--	--	--	--	---	---

					Receiver (Via Yoke Mount) General Display – LCD; Certifications - CE, FCC	Fixture Mounting - 1 x 1-1/8" Stud with 5/8" Receiver (Via Yoke Mount) General Display – LCD; Certifications - CE, FCC Garanție : 36 luni	
--	--	--	--	--	--	---	--

Semnat: _____ Numele, Prenumele: Cîrlig Ion În calitate de: director

Ofertantul: WEST BUY SRL Adresa: mun.Chisinau bd.Mirecea cel Batrin 39 ap 143

Data : 07.02.2024