

Ultrasonic-Cleaners

Digital, Degas Function

DC-POWER FULL SERIES

Digital Ultrasonic Cleaner-set, with Wire Basket & Lid, Highly Effective & Efficient Cleaning, Stainless Steel, up to 70°C, 0-99min., Frequency 40KHz

- ▶ Useful for Cleaning to Remove Dirt, Grease, Waxes and Oil from all Lab instruments by Ultrasonic Frequency.
- ▶ Microprocessor Control: Timer, Temperature and Output Control.
- ▶ Frequency: up to 40kHz.
- ▶ Temperature Range from Ambient to 70°C.
- ▶ Temperature accuracy: $\pm 3^{\circ}\text{C}$.
- ▶ Convenient Pre-set Function: Heating and Timer.
- ▶ Bottom - Mounted Drain (Except DC-80H & DC-120H).
- ▶ Maximum 99 minutes Set Cleaning Time.
- ▶ Include Basket & Lid.



DCG-H SERIES, DIGITAL ULTRASONIC CLEANERS WITH DEGAS FUNCTION

Features:

- ▶ Turbo power: Normal and soft function to resolve the cleaning blind spot
- ▶ Auto-degas function for laboratory purposes
- ▶ Memory function
- ▶ Automatically ultrasonic frequency tracking
- ▶ LED display for temperature and timer
- ▶ Timer: 1-99 minutes
- ▶ Temperature: 0-80°C, Temperature Accuracy: $\pm 3^{\circ}\text{C}$
- ▶ SUS304 tank. Stamping tank without welding gap for better waterproof
- ▶ User-friendly and clear panel.
- ▶ High-performance transducer systems
- ▶ Drainage and cool fan are available for 6L and above volume models, convenient to use.
- ▶ Ultrasonic Frequency: 40KHz.

Applications:

- ▶ Hospital and Dental Clinics ▶ Optical Stores and Makers ▶ Biology and Chemical Labs ▶ Jewelry Store & Maker ▶ Watch Service Shops ▶ Mobilephone and Electronics Service Shops ▶ Shooting Clubs & Printing Shops ▶ Automotive shop ▶ Hardware ▶ Tattoo ▶ Aerospace & marine parts.

MODEL - DIGITAL	DC-80H	DC-120H	DC-150H	DC-200H	DC-250H	DC-300H	DC-400H
MODEL - DEGASING	DCG-80H	DCG-120H	DCG-150H	DCG-200H	DCG-250H	DCG-300H	DCG-400H
Operating frequency	40 KHz						
Tank Capacity (Liters)	2	3	6	9	13	20	27
Internal tank size (LxWxH) (mm)	150x140x100	240x140x100	300x155x150	300x240x150	330x300x150	500x300x150	500x300x200
External dimension (LxWxH) (mm)	190x170x220	270x170x240	330x180x310	330x270x310	360x330x310	550x330x310	550x330x360
Internal tank stuff	SUS 304 #1.0t						
External stuff	Steel plate toast paint						
LID cover stuff	Stainless steel SUS 304						
Timer	1-99min						
Ultrasonic power	50W	100W	150W	200W	300W	400W	500W
Heating Power	100W	100W	300W	300W	400W	500W	500W
Net weight	1.9kg	2.9kg	5.8kg	8.8kg	10.2kg	13.2kg	14.9kg
Drainage	None	None	Have				
Power source	AC100~120V/AC220~240V 50/60Hz						