

Condor Grass Randweg 14, 8061 RW P.O. Box 21, 8060 AA Hasselt, The Netherlands W www.condor-group.eu

(+31) 38 477 89 11 F (+31) 38 477 89 22 Е info@condorgrass.com

Estancia		
Туре	Tufted filled synthetic grass carpet	
Material	Polypropylene (UV Stabilized)	
Yarn type	7.500 / 1 dTex fibrillated curled	
Yarn quality	Environmental friendly, free of lead and cadmium	
Primary backing	100% PP black with fleece, UV Stabilized, Weight 146 gr/m2	
Secondary backing	Black Latex compound with a base of styrenebutadiene (SBR), Weight 988 gr/m2	
Waterpermeability	60 liter/min/m2	
Pile height	12 mm	
Face weight	1.120 gr/m2	± 10%
Total weight	2.254 gr/m2	± 10%
Tuft gauge	3/16 gauge	
Stitches per 10 cm linear	19	± 1
Stitches per m2	39.900	± 10%
Filaments per m2	79.800	± 10%
Colour	Green	
UV stability	Meets DIN 53387 Standard (6000 hours)	
Colour fastness	Xenon Test: Blue Scale > 7, Grey-scale > 4	
Colour lining	Not Applicable	
Roll width	400 cm	
Roll length	20-25m, As per project plan	
Applications	Golf, Multifunctional, Tennis, Terraces	
Infill advice	Silica sand, gradation 0,5 - 1,0 mm, 80% roundshaped, appr 17 kg/m2	
Comments	Before installation make sure the rolls are from the same production code (first five digits of the roll number) Project.	









