



DLAB DM0636 Multi-Purpose Low-speed Centrifuge is ideal for the centrifugation of samples in clinical chemistry, cytology, research laboratories, industrial laboratories, etc. This centrifuge is suitable for tubes with caps, blood collection or urine tubes. Swing-out bucket rotors and adapters can be compatible with standard tubes up to 100mL at low speed.

DM0636

Multi-Purpose Low-speed Centrifuge

Features

- Speed can be set from 300- 6000rpm
- Maximum capacity of the centrifuge: 100 mLx4
- 9 Acceleration/10 Brake speed settings to ensure optimal separation
- A wide range of rotors optional(fixed angle and swing-out bucket rotors)
- Automatic rotor identification
- Timers can be set up to 99 min or HD for continuous running
- Pulse Key for quick spin function
- 9 procedures stored in memory makes the operation much simplified
- Maintenance-free brushless DC motors



Specifications

DM0636	
Speed range	300-6000rpm increment:10rpm
Max. RCF	4020xg
Speed accuracy	±20rpm
Max. Capacity	100mLx4
Run Time	30sec-99mins/continuous
Motor	Brushless DC
Display	LCD
Program Memory	9
Safety Devices	Door Imbalance protection Over speed & Over temperature detection
Acceleration/Deceleration	9 ↑ /10 ↓ steps
Power	660W; Single-phase AC220V-240V, 50Hz/60Hz, 6.3A; AC110V-120V,50Hz/60Hz,10A
Dimension[WxDxH]	445x579x269mm
Weight	36kg
Certification - CE	Noise - 62dB(A)
Advanced features	speed/rcf switch; Rotor identification

Available rotors



Cat. No. 19400062

S2-MP**DM0636**

Max. speed: 4000rpm

Max. RCF: 2200×g

Rotor capacity: Micro-plates 384-PCR/96-PCR/Elisa
plates×8pcs; Deep well plates×4pcs

Rotor material: stainless steel body and aluminum buckets



Cat. No. 19400036

AS12-PCR8**DM0636**

Max. speed: 6000rpm

Max. RCF: 4020×g

Rotor capacity: PCR 8 trips×12

Rotor material: aluminum

Biosealing: Yes



Cat. No. 19400034

AS30-2**DM0636**

Max. speed: 6000rpm

Max. RCF: 4020×g

Rotor capacity: 2mL×30

Rotor material: aluminum

Biosealing: Yes



Cat. No. 19400037

AS60-2**DM0636**

Max. speed: 6000rpm

Max. RCF: 4020×g

Rotor capacity: 2mL×60

Rotor material: aluminum

Biosealing: Yes

Available rotors



Cat. No. 19400038

AS6-50V (cone bottom)

DM0636

Max. speed: 6000rpm

Max. RCF: 4020×g

Rotor capacity: 50mLx6 or 15mLx6

Rotor material: aluminum

Biosealing: Yes



Cat. No. 19400035

AS18-5V (cone bottom)

DM0636

Max. speed: 6000rpm

Max. RCF: 4020×g

Rotor capacity: 5mLx18

Rotor material: stainless steel body and aluminum buckets

Biosealing: Yes



Cat. No. 19400039

A8-50 (round bottom)

DM0636

Max. speed: 5000rpm

Max. RCF: 3960×g

Rotor capacity: 50mLx8 or 15mLx16

Rotor material: aluminum body and stainless steel adapter

Default adapters: SE100P31x8, SE100P17x6



Cat. No. 19400040

A30-15 (round bottom)

DM0636

Max. speed: 4500rpm

Max. RCF: 3210×g

Rotor capacity: 15mLx30

Rotor material: aluminum body and stainless steel

adapter Bio-safe(Biosealing): Yes

Default adapters: SE100P17x30

Rotor	Capacity	Hole Diameter (mm)	Hole Depth (mm)	Max. Tube Height (mm)	Max. Speed (rpm)
AS30-2	2mLx30	11.2	39	43	6000
AS60-2	2mLx60	11.2	39	43	6000
AS6-50V	50mLx6	31	87.8	118	6000
AS18-5V	5mLx18	17.5	51	56	6000
A8-50	50mLx8	35	85.8	118	5000
	15mLx16	17.5	98	123	
A30-15	15mLx30	17.5	98	123	4500
S2-MP	Micro platex8/ Deep well platex4	-	-	-	4000