

ArmaTrac 1054E/E+

| | |
|---|---|
| ENGINE | |
| Normal Mode - Boost Mode (Max. HP / kW) | 103 - 111 HP / 75 - 82 kW |
| Engine Type | NEF STAGE-V (ECAPRA) |
| Engine Speed to Achieve Maximum Torque | 1400 rpm |
| Rated Speed in RPM | 2100 rpm |
| Normal Mode - Boost Mode Max. Torque (Nm) | 428 - 450 Nm |
| Emission Level | Stage V |
| Cylinder No. / Aspiration | 4 / Turbo Intercooler |
| Cylinder Volume (LT) | 3.5 liter |
| Fuel Tank (Liter) | 110 litre |
| Fuel Injection System | Common Rail Injection |
| AdBlue Tank Capacity | 20 Liter |
| TRANSMISSION | |
| Transmission Type | Cararo Full Synchro |
| Gear Box | 12F-12R |
| Gear Box Optional | 24F-24R |
| Auto front differential lock | Mechanic |
| Rear Differential Lock | Mechanic |
| 4wd Remote System | Electro-Hydraulic |
| Creeper Option | Optional for 24F-24R |
| Min - Max Speed (km/h) | 1,50-32,78 km/hr (12F-12R) 0,43-32,78 km/h (24F-24R) |
| ELECTRIC SYSTEM | |
| Battery Capacity | 105 amp |
| HYDRAULIC SYSTEM | |
| Hydraulic Control Type | Mechanic |
| Automatic Lifting System | Standard |
| Hydraulic Power Output | 6 |
| Hydraulic Pressure (Bar) | 190 Bar |
| Max. Hydraulic Lift Capacity (E/E+) | 3400 kg / 3400 kg |
| PTO | |
| Type | Independent 2V |
| PTO Speed Synchronized with Wheel Speed | Standard |
| PTO Speed | 540, 540E, 750 rpm |
| MEASURES | |
| Wheelbase | 2327 mm |
| Total Length | 4112 mm |
| Width | 1990 mm |
| Max. Height in Platform | 2720 mm |
| Max. Height in Cabin | 2720 mm |
| Front track width | 1500-1900 mm |
| Rear track width | 1500-1900 mm |
| WEIGHTS | |
| Total Tractor Weight (W/O Additional Weights, Canopy) | - |
| Total Tractor Weight (W/O Additional Weights, Cabin) | 3750 Kg |
| Total Front Weights | 10 x 30 (for 4WD) |
| Total Rear Weights | 6 x 50 |
| STANDARD TYRE MEASURES | |
| 1st Option - Front | 13,6-24 |
| 1st Option - Rear | 16,9-34 |
| 2nd Option - Front | 11,2-28 |
| 2nd Option - Rear | 13,6-38 |
| 3rd Option - Front | 320/85/R24 |
| 3rd Option - Rear | 460/85/R30 |
| 4th Option - Rear | 320/85/R28 |
| 4th Option - Rear | 380/85/R38 |
| COMFORT PROPERTIES | |
| Cabin | Standard |
| 4WD System Air Conditioning | Standard Standard Standard (+) Standard (+) |
| Air Compressor System for E+ Top Link (For E+ only) | |

Erkut Tractor Industries, Inc.

Organize Sanayi Bölgesi Bahçelievler Cad. No:2 Sincan Ankara/TURKEY
T: +903122674488 (pbx) F: +903122674491
www.armac.com - info@armac.com