

TUNGTECH INDUSTRIAL LIMITED

1610, No.3 Ri Yuan Er Li, Huli District, Xiamen 361012, China www.tungtech.com



DD45 Adult Audiometric headset

- ◆ Headband: HBA, foldable
- ◆ Transducer: DD52
- ◆ Impedance: $10 \Omega \pm 1.0 \Omega$
- ◆ Frequency response: 100 Hz - 8 kHz
- ◆ Sensitivity: $108 \pm 3\text{dB SPL@1000 Hz @ 1mW}$
- ◆ Cable length: 2 meter
- ◆ Plug type: 30°, 2 x 6.3mm gold-plated mono jack
- ◆ Environmental: RoHS compatible



TDH39 Audiometric headset

- ◆ Headband: HB-7
- ◆ Transducer: DD52
- ◆ Impedance: $10 \Omega \pm 1.0 \Omega$
- ◆ Frequency response: 100 Hz - 8 kHz
- ◆ Sensitivity: $108 \pm 3\text{dB SPL@1000 Hz @ 1mW}$
- ◆ Cable length: 2 meter
- ◆ Plug type: 30°, 2 x 6.3mm gold-plated mono jack
- ◆ Environmental: RoHS compatible



ME71 Audiometric headset

- ◆ Transducer: DD52
- ◆ Impedance: $10 \Omega \pm 1.0 \Omega$
- ◆ Frequency response: 100 Hz - 8 kHz
- ◆ Sensitivity: $108 \pm 3\text{dB SPL@1000 Hz @ 1mW}$
- ◆ Cable length: 2 meter
- ◆ Plug type: straight, 2 x 6.3mm gold-plated mono jack
- ◆ Environmental: RoHS compatible

TUNGTECH INDUSTRIAL LIMITED

1610, No.3 Ri Yuan Er Li, Huli District, Xiamen 361012, China www.tungtech.com



X5A Audiometric headset

- ◆ Headband: 3M X5A
- ◆ Transducer: DD52
- ◆ Impedance: $10 \Omega \pm 1.0 \Omega$
- ◆ Frequency response: 100 Hz - 8 kHz
- ◆ Sensitivity: $108 \pm 3\text{dB SPL@1000 Hz @ 1mW}$
- ◆ Cable length: 2 meter
- ◆ Plug type: straight mini jack 3.5mm gold-plated
- ◆ Environmental: RoHS compatible



H7A Audiometric headset

- ◆ Headband: 3M H7A
- ◆ Transducer: DD52
- ◆ Impedance: $10 \Omega \pm 1.0 \Omega$
- ◆ Frequency response: 100 Hz - 8 kHz
- ◆ Sensitivity: $108 \pm 3\text{dB SPL@1000 Hz @ 1mW}$
- ◆ Cable length: 2 meter
- ◆ Plug type: straight mini jack 3.5mm gold-plated
- ◆ Environmental: RoHS compatible



H7A Audiometer headset

- ◆ Headband: 3M H7A
- ◆ Transducer: DD52
- ◆ Impedance: $10 \Omega \pm 1.0 \Omega$
- ◆ Frequency response: 100 Hz - 8 kHz
- ◆ Sensitivity: $108 \pm 3\text{dB SPL@1000 Hz @ 1mW}$
- ◆ Cable length: 2 meter
- ◆ Plug type: 30°, 2 x 6.3mm gold-plated mono jack
- ◆ Environmental: RoHS compatible

TUNGTECH INDUSTRIAL LIMITED

1610, No.3 Ri Yuan Er Li, Huli District, Xiamen 361012, China www.tungtech.com



H7A Audiometer headset

- ◆ Headband: 3M H7A
- ◆ **Transducer: DD450**
- ◆ Impedance: $40 \pm 15 \text{ Ohm}$
- ◆ Frequency response: 20 Hz - 20 kHz
- ◆ Sensitivity: $97 \pm 3 \text{ dB SPL@1000 Hz}$
- ◆ Cable length: 2 meter
- ◆ Plug type: 30°, 2 x 6.3mm gold-plated mono jack
- ◆ Environmental: RoHS compatible



HB-7 Headband

- ◆ Headband with 2 yokes
- ◆ Environmental: RoHS compatible
- ◆ Black



DD52 Transducer

- ◆ Standard: IEC60318-3
- ◆ Impedance: $10 \Omega \pm 1.0 \Omega$
- ◆ Rated Power: 1000mW
- ◆ Frequency response: 100 Hz - 8 kHz
- ◆ Sensitivity: $108 \pm 3 \text{ dB SPL@1000 Hz @ 1mW}$
- ◆ Harmonic distortion: Below 1% @120 dB SPL, f=1 kHz
- ◆ Environmental: RoHS compatible



Ear cushion

TUNGTECH INDUSTRIAL LIMITED

1610, No.3 Ri Yuan Er Li, Huli District, Xiamen 361012, China www.tungtech.com



P4432 Dual mono earphone cable

- ◆ Cable length: 2 meter
- ◆ Plug type: 30°, 2 x 6.3mm gold-plated mono jack
- ◆ Environmental: RoHS compatible



P4434 Dual mono earphone cable

- ◆ Cable length: 2 meter
- ◆ Plug type: 30°, 2 x 6.3mm gold-plated mono jack
- ◆ Environmental: RoHS compatible



Two-pin BC cable

- ◆ Cable length: 2 meter
- ◆ Plug type: 30°, 6.3mm gold-plated mono jack
- ◆ Environmental: RoHS compatible



B71 Bone conductor headband

TUNGTECH INDUSTRIAL LIMITED

1610, No.3 Ri Yuan Er Li, Huli District, Xiamen 361012, China www.tungtech.com



B-71 Bone conduction Vibrator

- ◆ Nominal power: 1.5 W
- ◆ Impedance: $4\Omega \pm 15\%$ test at 200Hz, 3 v
- ◆ Resonance frequency: 300 Hz - 19 kHz
- ◆ Average working voltage: 3.7 V
- ◆ Current consumption (max.): 600 mA
- ◆ Distortion: less 5%
- ◆ Environmental: RoHS compatible



Patient switches