

Specificații tehnice

[Acest tabel va fi completat de către ofertant în coloanele 2, 3, 4, 6, 7, iar de către autoritatea contractantă – în coloanele 1, 5,]

Numărul procedurii de achiziție ocds-b3wdp1-MD-1718101186078 din 11 iun 2024
Obiectul achiziției: Imprimantă pentru carduri de acces, inclusiv consumabile

Denumirea bunurilor	Denumirea modelului bunului/serviciului	Țara de origine	Producătorul	Specificarea tehnică deplină solicitată de către autoritatea contractantă	Specificarea tehnică deplină propusă de către ofertant	Standarde de referință
1	2	3	4	5	6	7
Lotul 4						
Imprimantă pentru carduri de acces, inclusiv consumabile	CR805 Duplex Retransfer Printer (125-Card Input Hopper, Loosely Coupled Identive Smart Card Contact/Contactless Reader/Encoder) with Dual Laminator	USA	Entrust	Conform caietului de sarcini anexat	Print technology - Retransfer pigment ink Print capabilities - Single or dual-sided, over-the-edge printing Print resolution - 600 dots per inch (dpi) Print speed - Single-sided (CMYK) – up to 110 cards per hour (cph) Color modes - True color (ICC) – prints color as close as possible to image as defined in the card design Legacy SR/CR – prints as close as possible to the SR200, SD300, and SR300e card printers Vivid – prints colors with higher saturation and contrast. Card capacity - Input hopper – up to 125 cards Output hopper – up to 25 cards (optional 125-card hopper) Card input size – 0.030 inches to 0.040 inches (0.76 mm to 1.01 mm) Deployment method - On-premises	https://www.entrust.com/products/issuance-systems/instant/id-card/artista-cr805-with-lamination-module

					Operating environment - 15°C-35°C Physical dimensions - Printer only: L 54.3 cm x W 25.5 cm x H 39.7 cm Printer in box:L 63.8 cm x W 36.3 cm x H 57.2 cm Weight: 12.7 kg Connectivity: USB and Ethernet Warranties: Printer: 36-month standard warranty Printhead: Limited lifetime warranty Optional Features Magnetic stripe encoding - ISO/IAT magnetic stripe encoding Multi-hopper - 125-card hoppers WiFi type: 802.11g/n Authentication modes: None, WPA2 Personal Dual-band: 2.4GHz and 5GHz Smart card encoding - Single wire – Contact ISO 7816 T=0, 1 Contactless ISO 14443 A/B Protocols, MIFARE Protocols & Felica (DES & AES) Loosely coupled – Contact ISSO 7816 T=-, 1 HID ICLASS, read/write or read-only encoder PC prox Supplies Primerless color panel ribbons and retransfer film: CMYK 1,000 images single-sided (500 dual-sided) CMYK-K 1,000 images dual-sided Clear retransfer film 1,000 images single-sided (500 dual-sided) DuraGard Laminate, 1.0 mil, clear, full card DuraGard OptiSelect Laminate, 1.0 mil, “secure globe” full card Card, Plastic, CR80/030, PVC Graphics, White, Tray, Contains (500) Instant ID Software License Plus Edition SMA	
--	--	--	--	--	--	--

Semnat: **Victoria CECHINA** Numele, Prenumele: **Victoria CECHINA** În calitate de: **Administrator**

Ofertantul: **Societatea cu Răspundere Limitată "ELBIT"** Adresa: MD-2012, strada A. Șciusev 80, ap. 15, mun. Chișinău, Republica Moldova_