

EU TYPE EXAMINATION CERTIFICATE

Certificate No: 2163-PPE-1463

BM PORTAVITA S.R.L.

Republic Moldova, Chisinau, str. Petricani 17/22

It is certified that the manufacturer's technical file (Dated 01.04.2020) and the PPE product, detailed below, have been assessed and found to meet the applicable Essential Health and Safety Requirements in Annex II of Regulation (EU) 2016/425 based on the evaluation on technical documentation and relevant test reports.

Identification of the Personal Protective Equipment Brand Name: Portavita, Model: ZK3B-53L

The coverall is with hood fitted with elastic around the face, zipper closure system covered with placket; kimono sleeves finished with elastic for adjustment on the hand and trousers that at the end have attached overshoes (boots). The coverall is available in 6 nominal sizes. Coverall have 4 variants, which ensures the equal protective performance.

The following harmonised standards have been applied:

EN ISO 13688:2013, (General requirements for protective clothing)
EN 14605:2005+A1:2009, (Chemical protective clothing offering limited protective performance against liquid chemicals) Type 3, Type 4, limited wear life clothing.
EN ISO 13982-1:2004/A1:2010, (Chemical protective clothing providing protection to the full body against airbone solid particulates) Type 5, limited wear life clothing,
EN 13034:2005+A1:2009, (Chemical protective clothing offering limited protective performance against liquid chemicals) Type 6, limited wear life clothing,
EN 14126:2003/AC:2004, (Protective clothing against infective agents) for Type 3-B, 4-B, 5-B, 6-B.

Here by the manufacturer is allowed to use notified body number (2163) and can fix CE mark, as shown below, on the Category III product models given above, with the below requirements;

- Issuing an appropriate EU Declaration of Conformity according to Personal Protective Equipment Regulation (EU) 2016/425 Annex 9.
- Ongoing successful performance in fulfilment of the requirements set out in Personal Protective Equipment Regulation (EU) 2016/425 and harmonised standards, ensured by assessments based on Annex 7 (Module C2) or Annex 8 (Module D) of the regulation

This certificate is initially issued on 18/09/2020 and will be valid for 5 years from the issue date.





Suat KACMAZ
UNIVERSAL CERTIFICATION
Director





TECHNICAL EVALUATION REPORT

REPORT DATE / NO: 30.11.2020 / 2163-KKD-1463 R1

The initial report was dated on 18.09.2020. The report is updated for the small design change request of the PPE, which do not effect the protective performans of the PPE, by the manufacturer. The design change and explanation of the variants explained in the technical file Edition 1 dated 02.11.2020 is evaluated and found to be appropriate. The updated (added) text within this report is given in italic.

Manufacturer: BM PORTAVITA S.R.L.

Address: Republic Moldova, Chisinau, str. Petricani 17/22

Introduction

This report is prepared based on the evaluations on the technical file of the manufacturer dated 01 August, 2020 Version 00, and the test reports obtained from the laboratories for the analysis referenced by the applied harmonised standards for the personal protective equipment identified below. A list to the test reports is given below which are referenced within this report. The samples for evaluation are provided by the manufacturer for type examination and samples are delivered to the laboratories under UNIVERSAL supervision. The test results and all evaluations within this report belongs to the samples provided.

This report is prepared for the PPE with the guidance of the harmonised standards which are claimed to be applied by the manufacturer and the evaluation is conducted for the verification of fulfilment of Essential Health and Safety Requirements of PPE regulation, those applies for the product.

PPE Identification: The coverall is with hood fitted with elastic around the face, zipper closure system covered with placket; kimono sleeves finished with elastic for adjustment on the hand and trousers that at the end have attached overshoes (boots). The coverall is available in 6 nominal sizes. Coverall has base model and 4 different variants available on the market.

Component and Materials:

Fabric: Spunbond nonwoven laminated with PE film, with a mass of about 66 gsm (Gram / m2) of 100% polypropylene. (40 gsm non -wowen spunbond + 23 gsm PE film + 3 gsm hotmelt glue)
All joints are made by sewing with 100% polyester sewing thread and sealed with heat-sealed tape.

Coverall Type: Type 3-B / Type 4-B / Type 5-B / Type 6-B

Brand Name: Portavita Model: ZK3B-53L

Sizes Available: M - L - XL - 2XL - 3XL - 4XL

Variants of the model;

1. ZK3B-53L: Base Model as identified above.

- 2. ZK3B-53L VAR1: The hood is designed as 3 parts.
- 3. ZK3B-53L VAR2: The hood is designed as 3 parts, do not include overshoe components
- 4. ZK3B-53L VAR3: The hood is designed as 2 parts, include cuffs
- 5. ZK3B-53L VAR4: The hood is designed as 2 parts, do not include overshoe components

Applied Harmonised Standards

EN ISO 13688:2013, (General requirements for protective clothing)

EN 14605:2005+A1:2009, (Chemical protective clothing protective performance against chemicals in the forms liquid and spray) Type 3 and Type 4, limited wear life clothing,

EN ISO 13982-1:2004/A1:2010, (Chemical protective clothing providing protection to the full body against airbone solid particulates) Type 5, limited wear life clothing,

EN 13034:2005+A1:2009, (Chemical protective clothing offering limited protective performance against liquid chemicals) Type 6, limited wear life clothing,

Managorec



EN 14126:2003/AC:2004, (Protective clothing against infective agents) for Type 3-B, 4-B, 5-B, 6-B, limited life, This report is prepared on the basis of applicable Essential Health and Safety Requirements with the references annexed to each applied harmonised standard given above.

TEST REPORT INFORMATION

Report #	Laboratory Name	Report Date and Number	Competency Reference
1	Ekoteks Laboratuar ve Gözetim Hizmetleri A.Ş.	Dated 08.09.2020 Number: 20031096-Ing	Holds TURKAK Accreditation with No: AB-0583-T
2	GCNTR – Global Technology Laboratory	Dated 01.09,2020 # GTL-TLM-0052/20	Holds TURKAK Accreditation with No: AB-1252-T
3	GCNTR – Global Technology Laboratory	Dated 01.09.2020 # GTL-TLM-052-A/20	Holds TURKAK Accreditation with No: AB-1252-T
4	GCNTR – Global Technology Laboratory	Dated 11.09.2020 # GTL-TLM-0058A/20	Holds TURKAK Accreditation with No: AB-1252-T
5	GCNTR - Global Technology Laboratory	Dated 11.09.2020 # GTL-TLM-0058/20	Holds TURKAK Accreditation with No: AB-1252-T
6	Çevre Endüstriyel Analiz Laboratuari	Dated 01.09.2020 Number: 2020845E	Holds TURKAK Accreditation with No: AB-0363-T

The laboratories are contracted bodies with UNIVERSAL and the technical competence of the laboratories is also under supervision / assessment of UNIVERSAL based on the provisions of EN ISO/IEC 17065 Requirements for bodies certifying products, processes and services standard.







Technical Assessment of EN ISO 13688: 2013 Standard and other Standards it refers to, Clauses Corresponding to the Essential Health and Safety Requirements given above

22312	Essential Healt EN ISO 13688		-				
Article 4.2	EHSR Ref 1.2.1.1; The manufacturer declares in this specific PPE do not adverthat the materials do not, in known to be toxic, carcinoger Ref: Technical File Article 2.	his technica ersely affect the foresees nic, mutagen	al file that the the health of able conditions.	ne materials or hygiene cons of norm	used in the roof the user. To	The manufac ase substanc	cturer claim es generally
Article 4.4	EHSR Ref 1.2.1.2; The comfort of the PPE was surfaces that irritate or injure of the PPE was subject to even 17491-4 testing standard and complete the excercises. Ref: Test Reports.	the user and aluation du	d found to b ring the pra	e appropriat ctical exerci	e for use. In se testing as	addition suc defined in	the EN ISC
Article 5.3	EHSR Ref 1.2.1; The samples received from the conducted on the dimensional Ref: Technical File Product M	l change due	to cleaning		single use.	No further (evaluation i
and the state of t	EHSR Ref 2.12; The coverall is available in 6 manufacturer. The given dim Annex D of the standard.						
	Size	M	L	XL	XXL	XXXL	4XL
Article 6	Body height,	170-176	176-182 cm	182-188 cm	188-194 cm	194-200 cm	200-206 cm
	Bust circumference, cm	104-112 cm	112-120 cm	120-128 cm	128-136 cm	134-144 cm	144-152 cm
Article 7	Ref: Technical File Annex U EHSR Ref 2.12; Each piece of coverall have n Name / trademark o Size of the coverall Applied product star Applied protection p The markings on the covera marking rules are explained the marking requirements of this report.	narking with f the manufa ndards (Type pictograms w all / label a in the mark	the following the defining provith standard free found to ing section of the following section o	of product roduct standal references be easily vof the techni	ards) visible and cical file. For	further clar	ifications fo
Article 8	EHSR Ref 1.4; The information supplied by This information includes e defined user information text Name / trademark o Applied standards a Pictograms and expl	explanation of the techror of the manufactor of the manufactor of the manufactor of the technology of	required by nical file inc acturer, its a	all applied ludes the fol ddress,	product sta lowing data;	ndard requi	Market Control of the



EN ISO 13688 Standard Requirements Evaluation

- Coverall constituent materials used
- Instructions for use, controls before use, how to wear / unwear, limitations, instructuions for storage conditions, complementary PPEs, re-usability, instructions for disposal
 The above user information text is available in English







ESSENTIAL HEALTH and SAFETY REQUIREMENTS GIVEN IN EUROPEAN UNION REGULATION EU 2016/425 CORRESPONDING to Annex ZA of EN 14605:2005 + A1:2009 STANDARD

1. GENERAL REQUIREMENTS APPLICABLE TO ALL PPE

1.1. Design principles

1.1.1. Ergonomics

PPE must be designed and manufactured so that, in the foreseeable conditions of use for which it is intended, the user can perform the risk-related activity normally whilst enjoying appropriate protection of the highest level possible.

1.2. Innocuousness of PPE

1.2.1. Absence of inherent risks and other nuisance factors

PPE must be designed and manufactured so as not to create risks or other nuisance factors under foreseeable conditions of use.

1.2.1.1. Suitable constituent materials

The materials of which the PPE is made, including any of their possible decomposition products, must not adversely affect the health or safety of users

1.2.1.2. Satisfactory surface condition of all PPE parts in contact with the use

Any part of the PPE that is in contact or is liable to come into contact with the user when the PPE is worn must be free of rough surfaces, sharp edges, sharp points and the like which could cause excessive irritation or injuries.

1.2.1.3. Maximum permissible user impediment

Any impediment caused by PPE to the actions to be carried out, the postures to be adopted and sensory perceptions shall be minimised. Furthermore, use of the PPE must not engender actions which might endanger the user.

1.3. Comfort and effectiveness

1.3.2. Lightness and strength

PPE must be as light as possible without prejudicing its strength and effectiveness. PPE must satisfy the specific additional requirements in order to provide adequate protection against the risks for which it is intended and PPE must be capable of withstanding environmental factors in the foreseeable conditions of use.

1.3.3. Compatibility of different types of PPE intended for simultaneous use

If the same manufacturer places on the market several PPE models of different types in order to ensure the simultaneous protection of adjacent parts of the body, they must be compatible.

1.4. Manufacturer's instructions and information

In addition to the name and address of the manufacturer, the instructions that must be supplied with the PPE must contain all relevant information on:

- a) instructions for storage, use, cleaning, maintenance, servicing and disinfection. Cleaning, maintenance or disinfectant products recommended by manufacturers must have no adverse effect on the PPE or the user when applied in accordance with the relevant instructions;
- b) performance as recorded during relevant technical tests to check the levels or classes of protection provided by the PPE;
- c) where applicable, accessories that may be used with the PPE and the characteristics of appropriate spare parts;
- d) where applicable, the classes of protection appropriate to different levels of risk and the corresponding limits of use;
- e) where applicable, the month and year or period of obsolescence of the PPE or of certain of its components;
- f) where applicable, the type of packaging suitable for transport;
- g) the significance of any markings (see point 2.12);
- h) the risk against which the PPE is designed to protect;
- i) the reference to this Regulation and, where applicable, the references to other Union harmonisation legislation;
- j) the name, address and identification number of the notified body or bodies involved in the conformity assessment of the PPE;
- k) references to the relevant harmonised standard(s) used, including the date of the standard(s), or references to the other technical specifications used;
- 1) the internet address where the EU declaration of conformity can be accessed.



The information referred to in points (i), (j), (k) and (l) need not be contained in the instructions supplied by the manufacturer if the EU declaration of conformity accompanies the PPE.

2. ADDITIONAL REQUIREMENTS COMMON TO SEVERAL TYPES OF PPE

2.12. PPE bearing one or more identification markings or indicators directly or indirectly relating to health and safety

Where PPE bears one or more identification markings or indicators directly or indirectly relating to health and safety, those identification markings or indicators must, if possible, take the form of harmonised pictograms or ideograms. They must be perfectly visible and legible and remain so throughout the foreseeable useful life of the PPE. In addition, those markings must be complete, precise and comprehensible so as to prevent any misinterpretation. In particular, where such markings include words or sentences, the latter must be written in a language easily understood by consumers and other end-users, as determined by the Member State where the PPE is made available on the market.

Where PPE is too small to allow all or part of the necessary marking to be affixed, the relevant information must be mentioned on the packaging and in the manufacturer's instructions.

2.3. PPE for the face, eyes and respiratory system

Any restriction of the user's face, eyes, field of vision or respiratory system by the PPE shall be minimised.

The screens for those types of PPE must have a degree of optical neutrality that is compatible with the degree of precision and the duration of the activities of the user. If necessary, such PPE must be treated or provided with means to prevent misting-up. Models of PPE intended for users requiring sight correction must be compatible with the wearing of spectacles or contact lenses.

2.4. PPE subject to ageing

If it is known that the design performance of new PPE may be significantly affected by ageing, the month and year of manufacture and/or, if possible, the month and year of obsolescence must be indelibly and unambiguously marked on each item of PPE placed on the market and on its packaging.

If the manufacturer is unable to give an undertaking with regard to the useful life of the PPE, his instructions must provide all the information necessary to enable the purchaser or user to establish a reasonable obsolescence month and year, taking into account the quality level of the model and the effective conditions of storage, use, cleaning, servicing and maintenance.

Where appreciable and rapid deterioration in PPE performance is likely to be caused by ageing resulting from the periodic use of a cleaning process recommended by the manufacturer, the latter must, if possible, affix a marking to each item of PPE placed on the market indicating the maximum number of cleaning operations that may be carried out before the equipment needs to be inspected or discarded. Where such a marking is not affixed, the manufacturer must give that information in his instructions.

3. ADDITIONAL REQUIREMENTS SPECIFIC TO PARTICULAR RISKS

3.10. Protection against substances and mixtures which are hazardous to health and against harmful biological agents

3.10.2. Protection against cutaneous and ocular contact

PPE intended to prevent the surface contact of all or part of the body with substances and mixtures which are hazardous to health or with harmful biological agents must be capable of preventing the penetration or permeation of such substances and mixtures and agents through the protective integument under the foreseeable conditions of use for which the PPE is intended.

To this end, the constituent materials and other components of those types of PPE must be chosen or designed and incorporated so as to ensure, as far as possible, complete leak-tightness, which will allow where necessary prolonged daily use or, failing this, limited leak-tightness necessitating a restriction of the period of wear.

Where, by virtue of their nature and the foreseeable conditions of their use, certain substances and mixtures which are hazardous to health or harmful biological agents possess high penetrative power which limits the duration of the protection provided by the PPE in question, the latter must be subjected to standard tests with a view to their classification on the basis of their performance. PPE which is considered to be in conformity with the test specifications must bear a marking indicating, in particular, the names or, in the absence of the names, the codes of the substances used in the tests and the corresponding standard period of protection. The manufacturer's instructions must also contain, in particular, an explanation of the codes (if necessary), a detailed description of the standard tests and all appropriate information for the determination of the maximum permissible period of wear under the different foreseeable conditions of use.



Technical Assessment of EN 14605:2005 + A1:2009 Standard and other Standards it refers to, Clauses Corresponding to the Essential Health and Safety Requirements given above

EN 14605:2005 + A1:2009 Standard Requirements Evaluation

EHSR Ref 1.2.1.1, 1.3.2, 3.10.2;

The coverall material performance are tested according to EN 14325:2018 standard for the following properties, since the coverall is claimed to be for single use no cleaning cycle is applied;

Property of Material EN 14325:2018		Resi Classifi			SHARIT STEEL	Requirement of EN ISO 13034	Evaluation
4.4 Abrasion Resistance	No Abrasion @)2000 r	evs	Class	6	Class 1 or above	Success
4.5 Flex cracking resistance	> 40.000 (Cycles		Class	5	Class 1 or above	Success
4.7 Trapezoidal tear resistance	Width 2 Length 4			Class	s 2	Class 1 or above	Success
4.9 Tensile Strength	W 49.6 L 125.			Clas	s 1	Class 1 or above	Success
4.10 Puncture Resistance	6.41	N		Clas	s 1	Class 1 or above	Success
	Chemical	Ip	Class	Ir	Class		Walter Comment
4.11 Resistance to	Sulfuric Acid (H ₂ SO ₄ %30 concentration)	0%	3	93.6%	3		
Permeation of Liquids	Sudium Hydroxide (NaOH %10 concentration)	0%	3	86.3%	2	Class 1 or above	Success
	O-xylene	0%	3	96.2%	3	71.11.11.11.11.11.11.11.11.11.11.11.11.1	

Article 4.1

The above results are derived from the test report, in the reference below. In the evaluation of the test report it was stated that all the tests are conducted with the completion of conditioning requirements as (20 ± 2) C° and (65 ± 5) % relative humidity for 24 hours. Since the PPE are single use no cleaning or disinfection process is applied. The results fulfils the minimum requirements of the standard. The manufacturer do not claim a performance for the resistance to ignition or flammability of the product, in the user information sheet it is explained that the coveralls must be kept away of fire. Other requirements refered for skin compatibility, no irritation or adverse effects are evaluated in EN ISO 13688 section of this report.

Ref: Laboratory Test Report 1, Technical File







EN 14605:2005 + A1:2009 Standard Requirements Evaluation

EHSR Ref 1.3.2, 3.10.2;

The affects of seams to the performance of the coverall in penetration of liquids through sealed stitch holes are evaluated in the jet and spray tests of whole suit and evaluated in Article 4.3 of this section. In addition the seam strength and permeation of chemicals through the seams are tested and the results are given in the below table.

The seam strength is evaluated based on the test report as shown below:

Article 4.2

Property of Material EN 14325:2018	9998 to 3 to	Rest Classific				Requirement of EN ISO 13982-1	Evaluation
	Chemical	I_P	Class	IR	Class		
4.11 Resistance	Sulfuric Acid (H ₂ SO ₄ %30 concentration)	0%	3	93.6%	3	0	
to penetration by liquids	Sudium Hydroxide (NaOH %10 concentration)	0%	3	86.3%	2	Class I or above	Success
	O-xylene	0%	3	96.2%	3 -		Pakin Ses
5.5 Seam Strength	Refer to the streng seams at different pa The lowest Class is g kinds of so	urts of co	overall.	Cla	ss 2	Class I or above	Success

Ref: Laboratory Test Report 1

EHSR Ref 1.1.1, 1.1.2.1, 1.2.1.2, 1.2.1.3, 1.3.1, 1.3.3, 3.10.2;

The requirements of the coverall with respect to health and safety, ageing and sizing are evaluated in EN ISO 13688 section of this report.

The coverall under evaluation is a one piece full body clothing, without a visor and foot protection. The necessary additional PPEs must be worn by the wearer for the intended use. The freedom of movements of the wearer is tested as a part of the Jet and spray tests (Seven Movements) and found to be appropriate.

According to the test results reported;

The test report claims the jet test that it is conducted according to EN ISO 17491-3 and the spray test that is conducted according to EN ISO 17491-4 Method B which is given in Clause 4.3.4.2 and 4.3.4.3 of this standard.

- The subjects were able to complete the excercises described comfortably. The inspection on the tested samples states that there was no damage, tears or rips in fabrics, seams and connection points to the additionally worn PPEs like gloves, boots etc.
- For spray test, the calibrated stain area is calculated for the undergarment is 4.56 cm². The laboratory reports that for the 3 samples tested the total stain are of undergarments are smaller then three times the calibrated stain area, values are (3.55 cm², 5.6 cm², 3.8 cm²). For more details please refer to the test report.
- For jet test, the calibrated stain area is calculated for the undergarment is 4.56 cm². The laboratory reports that for the 3 samples tested the total stain are of undergarments are smaller then three times the calibrated stain area, values are (0 cm², 0 cm², 3.2 cm²). For more details please refer to the test report.

The above results indicates that the tested coveralls complies with the resistance to penetration by liquids in the form of spray test and jet test requirement of this standard. Which is based on a test report conducted according to EN ISO 17491-4:2008+A1:2016 and EN ISO 17491-3:2008.

Ref: Laboratory Test Report 2, Laboratory Test Report 3

Article 4.3



ESSENTIAL HEALTH and SAFETY REQUIREMENTS GIVEN IN EUROPEAN UNION REGULATION EU 2016/425 CORRESPONDING to Annex ZA of EN ISO 13688:2013 STANDARD

1. GENERAL REQUIREMENTS APPLICABLE TO ALL PPE

1.2. Innocuousness of PPE

1.2.1. Absence of inherent risks and other nuisance factors

PPE must be designed and manufactured so as not to create risks or other nuisance factors under foreseeable conditions of use.

1.2.1.1. Suitable constituent materials

The materials of which the PPE is made, including any of their possible decomposition products, must not adversely affect the health or safety of users

1.2.1.2. Satisfactory surface condition of all PPE parts in contact with the user

Any part of the PPE that is in contact or is liable to come into contact with the user when the PPE is worn must be free of rough surfaces, sharp edges, sharp points and the like which could cause excessive irritation or injuries.

1.4. Manufacturer's instructions and information

In addition to the name and address of the manufacturer, the instructions that must be supplied with the PPE must contain all relevant information on:

- a) instructions for storage, use, cleaning, maintenance, servicing and disinfection. Cleaning, maintenance or disinfectant products recommended by manufacturers must have no adverse effect on the PPE or the user when applied in accordance with the relevant instructions;
- b) performance as recorded during relevant technical tests to check the levels or classes of protection provided by the PPE;
- c) where applicable, accessories that may be used with the PPE and the characteristics of appropriate spare parts;
- d) where applicable, the classes of protection appropriate to different levels of risk and the corresponding limits of use;
- e) where applicable, the month and year or period of obsolescence of the PPE or of certain of its components;
- f) where applicable, the type of packaging suitable for transport;
- g) the significance of any markings (see point 2.12);
- h) the risk against which the PPE is designed to protect;
- i) the reference to this Regulation and, where applicable, the references to other Union harmonisation legislation;
- j) the name, address and identification number of the notified body or bodies involved in the conformity assessment of the PPE;
- k) references to the relevant harmonised standard(s) used, including the date of the standard(s), or references to the other technical specifications used;
- 1) the internet address where the EU declaration of conformity can be accessed.

The information referred to in points (i), (j), (k) and (l) need not be contained in the instructions supplied by the manufacturer if the EU declaration of conformity accompanies the PPE.

2. ADDITIONAL REQUIREMENTS COMMON TO SEVERAL TYPES OF PPE

2.12. PPE bearing one or more identification markings or indicators directly or indirectly relating to health and safety

Where PPE bears one or more identification markings or indicators directly or indirectly relating to health and safety, those identification markings or indicators must, if possible, take the form of harmonised pictograms or ideograms. They must be perfectly visible and legible and remain so throughout the foreseeable useful life of the PPE. In addition, those markings must be complete, precise and comprehensible so as to prevent any misinterpretation. In particular, where such markings include words or sentences, the latter must be written in a language easily understood by consumers and other end-users, as determined by the Member State where the PPE is made available on the market.

Where PPE is too small to allow all or part of the necessary marking to be affixed, the relevant information must be mentioned on the packaging and in the manufacturer's instructions.



ESSENTIAL HEALTH and SAFETY REQUIREMENTS GIVEN IN EUROPEAN UNION REGULATION EU 2016/425 CORRESPONDING to Annex ZA of EN ISO 13982-1:2004 + A1:2010 STANDARD

1. GENERAL REQUIREMENTS APPLICABLE TO ALL PPE

1.1. Design principles

1.1.1. Ergonomics

PPE must be designed and manufactured so that, in the foreseeable conditions of use for which it is intended, the user can perform the risk-related activity normally whilst enjoying appropriate protection of the highest level possible.

1.1.2 Levels and classes of protection

1.1.2.1 Optimum level of protection

The optimum level of protection to be taken into account in the design is that beyond which the constraints imposed by the wearing of the PPE would prevent its effective use during the period of exposure to the risk or the normal performance of the activity.

1.2. Innocuousness of PPE

1.2.1. Absence of inherent risks and other nuisance factors

PPE must be designed and manufactured so as not to create risks or other nuisance factors under foreseeable conditions of use.

1.2.1.1. Suitable constituent materials

The materials of which the PPE is made, including any of their possible decomposition products, must not adversely affect the health or safety of users

1.2.1.2. Satisfactory surface condition of all PPE parts in contact with the user

Any part of the PPE that is in contact or is liable to come into contact with the user when the PPE is worn must be free of rough surfaces, sharp edges, sharp points and the like which could cause excessive irritation or injuries.

1.2.1.3. Maximum permissible user impediment

Any impediment caused by PPE to the actions to be carried out, the postures to be adopted and sensory perceptions shall be minimised. Furthermore, use of the PPE must not engender actions which might endanger the user.

1.3. Comfort and effectiveness

1.3.1. Adaptation of PPE to user morphology

PPE must be designed and manufactured in such a way as to facilitate its correct positioning on the user and to remain in place for the foreseeable period of use, bearing in mind ambient factors, the actions to be carried out and the postures to be adopted. For this purpose, it must be possible to adapt the PPE to fit the morphology of the user by all appropriate means, such as adequate adjustment and attachment systems or the provision of an adequate range of sizes.

1.3.2. Lightness and strength

PPE must be as light as possible without prejudicing its strength and effectiveness. PPE must satisfy the specific additional requirements in order to provide adequate protection against the risks for which it is intended and PPE must be capable of withstanding environmental factors in the foreseeable conditions of use.

1.3.3. Compatibility of different types of PPE intended for simultaneous use

If the same manufacturer places on the market several PPE models of different types in order to ensure the simultaneous protection of adjacent parts of the body, they must be compatible.

1.4. Manufacturer's instructions and information

In addition to the name and address of the manufacturer, the instructions that must be supplied with the PPE must contain all relevant information on:

m) instructions for storage, use, cleaning, maintenance, servicing and disinfection. Cleaning, maintenance or disinfectant products recommended by manufacturers must have no adverse effect on the PPE or the user when applied in accordance with the relevant instructions;

n) performance as recorded during relevant technical tests to check the levels or classes of protection provided by the PPE;



- o) where applicable, accessories that may be used with the PPE and the characteristics of appropriate spare parts;
- p) where applicable, the classes of protection appropriate to different levels of risk and the corresponding limits of use:
- q) where applicable, the month and year or period of obsolescence of the PPE or of certain of its components;
- r) where applicable, the type of packaging suitable for transport;
- s) the significance of any markings (see point 2.12);
- t) the risk against which the PPE is designed to protect;
- u) the reference to this Regulation and, where applicable, the references to other Union harmonisation legislation;
- v) the name, address and identification number of the notified body or bodies involved in the conformity assessment of the PPE;
- w) references to the relevant harmonised standard(s) used, including the date of the standard(s), or references to the other technical specifications used;
- x) the internet address where the EU declaration of conformity can be accessed.

The information referred to in points (i), (j), (k) and (l) need not be contained in the instructions supplied by the manufacturer if the EU declaration of conformity accompanies the PPE.

2. ADDITIONAL REQUIREMENTS COMMON TO SEVERAL TYPES OF PPE

2.12. PPE bearing one or more identification markings or indicators directly or indirectly relating to health and safety

Where PPE bears one or more identification markings or indicators directly or indirectly relating to health and safety, those identification markings or indicators must, if possible, take the form of harmonised pictograms or ideograms. They must be perfectly visible and legible and remain so throughout the foreseeable useful life of the PPE. In addition, those markings must be complete, precise and comprehensible so as to prevent any misinterpretation. In particular, where such markings include words or sentences, the latter must be written in a language easily understood by consumers and other end-users, as determined by the Member State where the PPE is made available on the market.

Where PPE is too small to allow all or part of the necessary marking to be affixed, the relevant information must be mentioned on the packaging and in the manufacturer's instructions.

3. ADDITIONAL REQUIREMENTS SPECIFIC TO PARTICULAR RISKS

3.10. Protection against substances and mixtures which are hazardous to health and against harmful biological agents

3.10.2. Protection against cutaneous and ocular contact

PPE intended to prevent the surface contact of all or part of the body with substances and mixtures which are hazardous to health or with harmful biological agents must be capable of preventing the penetration or permeation of such substances and mixtures and agents through the protective integument under the foreseeable conditions of use for which the PPE is intended.

To this end, the constituent materials and other components of those types of PPE must be chosen or designed and incorporated so as to ensure, as far as possible, complete leak-tightness, which will allow where necessary prolonged daily use or, failing this, limited leak-tightness necessitating a restriction of the period of wear.

Where, by virtue of their nature and the foreseeable conditions of their use, certain substances and mixtures which are hazardous to health or harmful biological agents possess high penetrative power which limits the duration of the protection provided by the PPE in question, the latter must be subjected to standard tests with a view to their classification on the basis of their performance. PPE which is considered to be in conformity with the test specifications must bear a marking indicating, in particular, the names or, in the absence of the names, the codes of the substances used in the tests and the corresponding standard period of protection. The manufacturer's instructions must also contain, in particular, an explanation of the codes (if necessary), a detailed description of the standard tests and all appropriate information for the determination of the maximum permissible period of wear under the different foreseeable conditions of use.







Technical Assessment of EN ISO 13982-1:2004 + A1:2010 Standard and other Standards it refers to, Clauses Corresponding to the Essential Health and Safety Requirements given above

EN ISO 13982-1:2004 + A1:2010 Standard Requirements Evaluation

EHSR Ref 1.2.1, 1.3.2;

The coverall material performance are tested according to EN 14325:2018 standard for the following properties, since the coverall is claimed to be for single use no cleaning cycle is applied;

Property of Material EN 14325:2018	Result Classification		Requirement of EN ISO 13982-1	Evaluation
4.4 Abrasion Resistance	No Abrasion @2000 revs	Class 6	Class 1 or above	Success
4.5 Flex cracking resistance	>40,000 Cycles	Class 5	Class 1 or above	Success
4.7 Trapezoidal tear resistance	Width 21.3 N Length 42.7 N	Class 2	Class 1 or above	Success
4.10 Puncture Resistance	6.4 N	Class 1	Class 1 or above	Success

Article 4.1

The above results are derived from the test report, in the reference below. In the evaluation of the test report it was stated that all the tests are conducted with the completion of conditioning requirements as (20 ± 2) C° and (65 ± 5) % relative humidity for 24 hours.

The manufacturer do not claim a performance for the resistance to ignition or flammability of the product, in the user information sheet it is explained that the coveralls must be kept away of fire. Other requirements referred for skin compatibility, no irritation or adverse effects are evaluated in EN ISO 13688 section of this report.

Ref: Laboratory Test Report 1, Technical File

EHSR Ref 1.3.2, 3.10.2;

The affects of seams to the performance of the coverall in penetration of solid particles through stitch holes are evaluated in the whole suit test and evaluated in Article 4.3 of this section.

The seam strength is evaluated based on the test report as shown below;

Arti	clo	12
ALL	cie	7.4

Property of Material EN 14325:2018	Result Classification		Requirement of EN ISO 13982-1	Evaluation
5.5 Seam Strength	Refer to the strength values for seams at different parts of coverall. The lowest Class is given among all kinds of seams	Class 2	Class 1 or above	Success

Ref: Laboratory Test Report 1

EHSR Ref 1.1.1, 1.1.2.1, 1.2.1.2, 1.2.1.3, 1.3.1, 1.3.3, 3.10.2;

Article 4.3

The requirements of the coverall with respect to health and safety, ageing and sizing are evaluated in EN ISO 13688 section of this report.

The coverall under evaluation is a one piece full body clothing, without a visor and foot protection. The necessary additional PPEs must be worn by the wearer for the intended use. The freedom of



EN ISO 13982-1:2004 + A1:2010 Standard Requirements Evaluation

movements of the wearer is tested as a part of the Total Inward Lekage test and found to be appropriate.

According to the test results reported;

- The subjects were able to complete the excercises described comfortably. The inspection on the tested samples states that there was no damage, tears or rips in fabrics, seams and connection points to the additionally worn PPEs like gloves, boots etc.
- The results of percentages of inward lekage values reported claims that All 90 measurements are smaller and equal to 30. Which means all 90 of the total lekage measurements among all excercises for all positions and all samples are smaller than 30%.
- All 10 of the average total inward lekage per tested suit of 10 is smaller or equal to 15%.

The above results indicates that the tested coveralls complies with the total inward leakage of aeroslols of solid particles requirement of this standard. Which is based on a test report conducted according to EN ISO 13982-2:2005

Ref: Laboratory Test Report 4

EHSR Ref 2.12:

Each piece of coverall have marking with the following information on the single PPE package / PPE itself;

- Name / trademark of the manufacturer, type and model of PPE
- Size of the coverall
- Applied product standards (EN ISO 13982-1+A1:2010)
- Pictograms for protection against chemicals, invitation to read manufacturer's instructions, single use
- Shelf life and date of manufacturing

The above mentioned marking requirements are stated in the technical file of the manufacturer. The evaluated samples did not have all these marking and information on the PPE. The manufacturer shall follow the instructions in the technical file in case of serial manufacturing of the PPE and verify before putting the PPE on the market. The PPE coverall is for single use, the markings for re-use cleaning or disinfection is discarded.

Ref: Technical File PPE Marking section.

EHSR Ref 1.4;

The information supplied by the manufacturer is defined in the relevant section of the technical file. This information includes explanation required by all applied product standard requirements. The defined user information text in the technical file includes the following data;

- Name / trademark of the manufacturer, its address, or the authorised representative for EU community
- Type and model of PPE
- Applied product standards (EN ISO 13982-1+A1:2010)
- Size designation table
- Type of protection against chemicals (Type-5). The information also includes a reminder for wearing necessary additional PPE in order to achieve a full body protection (i.e boots, gloves, mask and visor / face shield).
- The statement that the coverall provides a total inward lekage Ljmn, $82/90 \le 30$ % and LS, $8/10 \le 15$ %
- Material test performance classifications (Based on EN 14325:2018 classification)
- · Pictogram and information that the PPE is non-reusable also the shelf life is mentioned
- Instructions for use, controls before use, how to wear / unwear, limitations, instructuions for

Article 5

Article 6



EN ISO 13982-1:2004 + A1:2010 Standard Requirements Evaluation

storage conditions, complementary, instructions for disposal The above user information text is available in English Ref Technical File, User Information Sheet







ESSENTIAL HEALTH and SAFETY REQUIREMENTS GIVEN IN EUROPEAN UNION REGULATION EU 2016/425 CORRESPONDING to Annex ZA of EN ISO 13034:2005 + A1:2009 STANDARD

1. GENERAL REQUIREMENTS APPLICABLE TO ALL PPE

1.1. Design principles

1.1.1. Ergonomics

PPE must be designed and manufactured so that, in the foreseeable conditions of use for which it is intended, the user can perform the risk-related activity normally whilst enjoying appropriate protection of the highest level possible.

1.2. Innocuousness of PPE

1.2.1. Absence of inherent risks and other nuisance factors

PPE must be designed and manufactured so as not to create risks or other nuisance factors under foreseeable conditions of

1.2.1.1. Suitable constituent materials

The materials of which the PPE is made, including any of their possible decomposition products, must not adversely affect the health or safety of users

1.2.1.3. Maximum permissible user impediment

Any impediment caused by PPE to the actions to be carried out, the postures to be adopted and sensory perceptions shall be minimised. Furthermore, use of the PPE must not engender actions which might endanger the user.

1.3. Comfort and effectiveness

1.3.2. Lightness and strength

PPE must be as light as possible without prejudicing its strength and effectiveness. PPE must satisfy the specific additional requirements in order to provide adequate protection against the risks for which it is intended and PPE must be capable of withstanding environmental factors in the foreseeable conditions of use.

1.3.3. Compatibility of different types of PPE intended for simultaneous use

If the same manufacturer places on the market several PPE models of different types in order to ensure the simultaneous protection of adjacent parts of the body, they must be compatible.

1.4. Manufacturer's instructions and information

In addition to the name and address of the manufacturer, the instructions that must be supplied with the PPE must contain all relevant information on:

- a) instructions for storage, use, cleaning, maintenance, servicing and disinfection. Cleaning, maintenance or disinfectant products recommended by manufacturers must have no adverse effect on the PPE or the user when applied in accordance with the relevant instructions;
- b) performance as recorded during relevant technical tests to check the levels or classes of protection provided by
- c) where applicable, accessories that may be used with the PPE and the characteristics of appropriate spare parts;
- d) where applicable, the classes of protection appropriate to different levels of risk and the corresponding limits of
- e) where applicable, the month and year or period of obsolescence of the PPE or of certain of its components;
- f) where applicable, the type of packaging suitable for transport;
- g) the significance of any markings (see point 2.12);
- h) the risk against which the PPE is designed to protect;
- the reference to this Regulation and, where applicable, the references to other Union harmonisation legislation;
- the name, address and identification number of the notified body or bodies involved in the conformity assessment of the PPE;
- k) references to the relevant harmonised standard(s) used, including the date of the standard(s), or references to the other technical specifications used;
- the internet address where the EU declaration of conformity can be accessed.



The information referred to in points (i), (j), (k) and (l) need not be contained in the instructions supplied by the manufacturer if the EU declaration of conformity accompanies the PPE.

2. ADDITIONAL REQUIREMENTS COMMON TO SEVERAL TYPES OF PPE

2.4. PPE subject to ageing

If it is known that the design performance of new PPE may be significantly affected by ageing, the month and year of manufacture and/or, if possible, the month and year of obsolescence must be indelibly and unambiguously marked on each item of PPE placed on the market and on its packaging.

If the manufacturer is unable to give an undertaking with regard to the useful life of the PPE, his instructions must provide all the information necessary to enable the purchaser or user to establish a reasonable obsolescence month and year, taking into account the quality level of the model and the effective conditions of storage, use, cleaning, servicing and maintenance.

Where appreciable and rapid deterioration in PPE performance is likely to be caused by ageing resulting from the periodic use of a cleaning process recommended by the manufacturer, the latter must, if possible, affix a marking to each item of PPE placed on the market indicating the maximum number of cleaning operations that may be carried out before the equipment needs to be inspected or discarded. Where such a marking is not affixed, the manufacturer must give that information in his instructions.

2.12. PPE bearing one or more identification markings or indicators directly or indirectly relating to health and safety

Where PPE bears one or more identification markings or indicators directly or indirectly relating to health and safety, those identification markings or indicators must, if possible, take the form of harmonised pictograms or ideograms. They must be perfectly visible and legible and remain so throughout the foreseeable useful life of the PPE. In addition, those markings must be complete, precise and comprehensible so as to prevent any misinterpretation. In particular, where such markings include words or sentences, the latter must be written in a language easily understood by consumers and other end-users, as determined by the Member State where the PPE is made available on the market.

Where PPE is too small to allow all or part of the necessary marking to be affixed, the relevant information must be mentioned on the packaging and in the manufacturer's instructions.

3. ADDITIONAL REQUIREMENTS SPECIFIC TO PARTICULAR RISKS

3.10. Protection against substances and mixtures which are hazardous to health and against harmful biological agents

3.10.2. Protection against cutaneous and ocular contact

PPE intended to prevent the surface contact of all or part of the body with substances and mixtures which are hazardous to health or with harmful biological agents must be capable of preventing the penetration or permeation of such substances and mixtures and agents through the protective integument under the foreseeable conditions of use for which

the PPE is intended.

To this end, the constituent materials and other components of those types of PPE must be chosen or designed and incorporated so as to ensure, as far as possible, complete leak-tightness, which will allow where necessary prolonged daily use or, failing this, limited leak-tightness necessitating a restriction of the period of wear.

Where, by virtue of their nature and the foreseeable conditions of their use, certain substances and mixtures which are hazardous to health or harmful biological agents possess high penetrative power which limits the duration of the protection provided by the PPE in question, the latter must be subjected to standard tests with a view to their classification on the basis of their performance. PPE which is considered to be in conformity with the test specifications must bear a marking indicating, in particular, the names or, in the absence of the names, the codes of the substances used in the tests and the corresponding standard period of protection. The manufacturer's instructions must also contain, in particular, an explanation of the codes (if necessary), a detailed description of the standard tests and all appropriate information for the determination of the maximum permissible period of wear under the different foreseeable conditions of use.







Technical Assessment of EN ISO 13034:2005 + A1:2009 Standard and other Standards it refers to, Clauses Corresponding to the Essential Health and Safety Requirements given above

EN ISO 13034:2005 + A1:2009 Standard Requirements Evaluation

EHSR Ref 1.2.1, 1.2.1.1, 1.3.2, 3.10.2;

The coverall material performance are tested according to EN 14325:2018 standard for the following properties, since the coverall is claimed to be for single use no cleaning cycle is applied;

Property of Material EN 14325:2018	Result Classification	*******	Requirement of EN ISO 13034	Evaluation
4.4 Abrasion Resistance	No Abrasion @2000 revs	Class 6	Class 1 or above	Success
4.7 Trapezoidal tear resistance	Width 21.3 N Length 42.7 N	Class 2	Class 1 or above	Success
4.9 Tensile Strength	W 49.6 N L 125.6 N	Class 1	Class 1 or above	Success
4.10 Puncture Resistance	6,4 N	Class 1	Class I or above	Success
	Sulfuric Acid (H ₂ SO ₄) I _R is 93.6 %	Class 3		Success
4.12 Liquid repellency	Sudium Hydroxide (NaOH) I _R is 86.3 %	Class 2	Class 3 at least for 1 chemical	
	o-Xylene I _R is 96.2 %	Class 3	THE RESERVE THE PROPERTY OF TH	
*	Sulfuric Acid (H2SO4) I _P is 0 %	Class 3	600g	
4.10 Resistance to penetration by liquids	Sodium Hydroxide (NaOH) IP is 0 %	Class 3	Class 2 at least for 1 chemical	Success
The control of the co	o-Xylene (Undiluted) IP is 0 %	Class 3		

Article 4.1

The above results are derived from the test report in the reference below. In the evaluation of the test report it was stated that all the tests are conducted with the completion of conditioning requirements as (20 ± 2) C° and (65 ± 5) % relative humidity for 24 hours.

The manufacturer do not claim a performance for the resistance to ignition or flammability of the product, in the user information sheet it is explained that the coveralls must be kept away of fire. Other requirements referred for skin compatibility, no irritation or adverse effects are evaluated in EN ISO 13688 section of this report.

Ref: Laboratory Test Report 1, Technical File

EHSR Ref 1.3.2, 3.10.2;

The affects of seams to the performance of the coverall in penetration of liquid through stitch holes or through other components of a seam are evaluated in the whole suit mist test and evaluated in Article 5.2 of this section.

Article 4.2

Property of Material EN 14325:2018	aluated based on the test report as Result Classification		Requirement of EN ISO 13982-1	Evaluation
5.5 Seam Strength	Refer to the strength values for seams at different parts of coverall. The lowest Class is	Class 2	Class 1 or above	Success

Yland Can a land

~



10.00	EN ISO 13034:2005 + A1:2009 Standard Requirements Evaluation
	Ref: Laboratory Test Report 1
	EHSR Ref 1.2.1.3, 2.4, 3.10.2;
	The requirements of the coverall with respect to health and safety, ageing and sizing are evaluated in EN ISO 13688 section of this report.
	The coverall under evaluation is a one piece full body clothing, without a visor and foot protection. The necessary additional PPEs must be worn by the wearer for the intended use. The freedom a movements of the wearer is tested as a part of the light spray (mist) test (Seven Movements) are found to be appropriate.
	The test report claims the light spray test that it is conducted according to Method A of EN IS 17491-4 which corresponds the test setup defined in Clause 5.2 of this standard.
	According to the test results reported;
Article 5.1,5.2	The subjects were able to complete the excercises (seven movements) described comfortable. The inspection on the tested samples states that there was no damage, tears or rips in fabric seams and connection points to the additionally worn PPEs like gloves, boots etc.
	• The calibrated stain area is calculated for the undergarment is 4.56 cm ² . The laborator reports that for the 3 samples tested the total stain are of undergarments are smaller then three times the calibrated stain area, values are (0 cm ² , 0 cm ² , 0 cm ²). For more details please reto the test report. The values are very close to the limits.
	The above results indicates that the tested coveralls complies with the resistance to penetration liquids in the form of a light spray (mist) test requirement of this standard. Which is based on a t report conducted according to EN ISO 17491-4:2008+A1:2016 Method A.
	Ref: Laboratory Test Report 5
	EHSR Ref 2.12;
	Each piece of coverall have marking with the following information on the single PPE package / P itself;
	 Name / trademark of the manufacturer, type and model of PPE
	Size of the coverall
	Applied product standards (EN ISO 13034:2005+A1:2009)
Irticle 6	Pictograms for protection against chemicals, invitation to read manufacturer's instructions
	Shelf life and date of manufacturing
	The above mentioned marking requirements are stated in the technical file of the manufacturer. evaluated samples did not have all these marking and information on the PPE. The manufacturer s follow the instructions in the technical file in case of serial manufacturing of the PPE and verbefore putting the PPE on the market. The PPE coverall is for single use, the markings for recleaning or disinfection is discarded.
	Ref: Technical File PPE Marking section.
gegennete geget gehann i met til kommen frå sektion	EHSR Ref 1.3.3, 2.4, 2.12;
	The information supplied by the manufacturer is defined in the relevant section of the technical This information includes explanation required by all applied product standard requirements.
	This information includes explanation required by an applied product standard requirement defined user information text in the technical file includes the following data;
Article 7	Name / trademark of the manufacturer, its address, or the authorised representative for
	community
	• Type of protection against chemicals (Type-6). The information also includes a reminder wearing necessary additional PPE in order to achieve a full body protection (i.e boots, glomask and visor / face shield).



EN ISO 13034:2005 + A1:2009 Standard Requirements Evaluation

- Size of the coverall and model name
- The standard code / name with the published year
- The statement that the coverall is tested against the chemical names (tested for) and performance levels for mechanical strengths including repellency and resistance to penetration of liquids (Based on EN 14325:2018 classification)
- Pictogram and information that the PPE is non-reusable also the shelf life is mentioned
- Instructions for use, controls before use, how to wear / unwear, limitations, instructuions for storage conditions, complementary, instructions for disposal
- The statement on the light spray test results
- · Statement for warning the user on flammability, to keep away of fire

The above user information text is available in English

Ref User Information Sheet







ESSENTIAL HEALTH and SAFETY REQUIREMENTS GIVEN IN EUROPEAN UNION REGULATION EU 2016/425 CORRESPONDING to Annex ZA of EN ISO 14126:2003 + AC:2004 STANDARD

1. GENERAL REQUIREMENTS APPLICABLE TO ALL PPE

1.1. Design principles

1.1.2.2. Classes of protection appropriate to different levels of risk

Where differing foreseeable conditions of use are such that several levels of the same risk can be distinguished, appropriate classes of protection must be taken into account in the design of the PPE.

1.3. Comfort and effectiveness

1.3.1. Adaptation of PPE to user morphology

PPE must be designed and manufactured in such a way as to facilitate its correct positioning on the user and to remain in place for the foreseeable period of use, bearing in mind ambient factors, the actions to be carried out and the postures to be adopted. For this purpose, it must be possible to adapt the PPE to fit the morphology of the user by all appropriate means, such as adequate adjustment and attachment systems or the provision of an adequate range of sizes.

1.3.2. Lightness and strength

PPE must be as light as possible without prejudicing its strength and effectiveness.

PPE must satisfy the specific additional requirements in order to provide adequate protection against the risks for which it is intended and PPE must be capable of withstanding environmental factors in the foreseeable conditions of use.

1.4. Manufacturer's instructions and information

In addition to the name and address of the manufacturer, the instructions that must be supplied with the PPE must contain all relevant information on:

- instructions for storage, use, cleaning, maintenance, servicing and disinfection. Cleaning, maintenance or disinfectant products recommended by manufacturers must have no adverse effect on the PPE or the user when applied in accordance with the relevant instructions;
- b) performance as recorded during relevant technical tests to check the levels or classes of protection provided by the PPE;
- c) where applicable, accessories that may be used with the PPE and the characteristics of appropriate spare parts;
- d) where applicable, the classes of protection appropriate to different levels of risk and the corresponding limits of use:
- e) where applicable, the month and year or period of obsolescence of the PPE or of certain of its components;
- f) where applicable, the type of packaging suitable for transport;
- g) the significance of any markings (see point 2.12);
- h) the risk against which the PPE is designed to protect;
- i) the reference to this Regulation and, where applicable, the references to other Union harmonisation legislation;
- j) the name, address and identification number of the notified body or bodies involved in the conformity assessment of the PPE;
- k) references to the relevant harmonised standard(s) used, including the date of the standard(s), or references to the other technical specifications used;
- 1) the internet address where the EU declaration of conformity can be accessed.

The information referred to in points (i), (j), (k) and (l) need not be contained in the instructions supplied by the manufacturer if the EU declaration of conformity accompanies the PPE.

2. ADDITIONAL REQUIREMENTS COMMON TO SEVERAL TYPES OF PPE

2.4. PPE subject to ageing

If it is known that the design performance of new PPE may be significantly affected by ageing, the month and year of manufacture and/or, if possible, the month and year of obsolescence must be indelibly and unambiguously marked on each item of PPE placed on the market and on its packaging.

If the manufacturer is unable to give an undertaking with regard to the useful life of the PPE, his instructions must provide all the information necessary to enable the purchaser or user to establish a reasonable obsolescence month and year, taking into account the quality level of the model and the effective conditions of storage, use, clearing, servicing and maintenance.



Where appreciable and rapid deterioration in PPE performance is likely to be caused by ageing resulting from the periodic use of a cleaning process recommended by the manufacturer, the latter must, if possible, affix a marking to each item of PPE placed on the market indicating the maximum number of cleaning operations that may be carried out before the equipment needs to be inspected or discarded. Where such a marking is not affixed, the manufacturer must give that information in his instructions.

2.12. PPE bearing one or more identification markings or indicators directly or indirectly relating to health and safety

Where PPE bears one or more identification markings or indicators directly or indirectly relating to health and safety, those identification markings or indicators must, if possible, take the form of harmonised pictograms or ideograms. They must be perfectly visible and legible and remain so throughout the foreseeable useful life of the PPE. In addition, those markings must be complete, precise and comprehensible so as to prevent any misinterpretation. In particular, where such markings include words or sentences, the latter must be written in a language easily understood by consumers and other end-users, as determined by the Member State where the PPE is made available on the market.

Where PPE is too small to allow all or part of the necessary marking to be affixed, the relevant information must be mentioned on the packaging and in the manufacturer's instructions.

3. ADDITIONAL REQUIREMENTS SPECIFIC TO PARTICULAR RISKS

3.10. Protection against substances and mixtures which are hazardous to health and against harmful biological agents

3.10.2. Protection against cutaneous and ocular contact

PPE intended to prevent the surface contact of all or part of the body with substances and mixtures which are hazardous to health or with harmful biological agents must be capable of preventing the penetration or permeation of such substances and mixtures and agents through the protective integument under the foreseeable conditions of use for which the PPE is intended.

To this end, the constituent materials and other components of those types of PPE must be chosen or designed and incorporated so as to ensure, as far as possible, complete leak-tightness, which will allow where necessary prolonged daily use or, failing this, limited leak-tightness necessitating a restriction of the period of wear.

Where, by virtue of their nature and the foreseeable conditions of their use, certain substances and mixtures which are hazardous to health or harmful biological agents possess high penetrative power which limits the duration of the protection provided by the PPE in question, the latter must be subjected to standard tests with a view to their classification on the basis of their performance. PPE which is considered to be in conformity with the test specifications must bear a marking indicating, in particular, the names or, in the absence of the names, the codes of the substances used in the tests and the corresponding standard period of protection. The manufacturer's instructions must also contain, in particular, an explanation of the codes (if necessary), a detailed description of the standard tests and all appropriate information for the determination of the maximum permissible period of wear under the different foreseeable conditions of use.







Technical Assessment of EN 14126:2003 + AC:2004 Standard and other Standards it refers to, Clauses Corresponding to

	EN 14126:2003 + AC:2004 Standard Requi	irements Evaluatio	n	
Article 4.1.2	EHSR Ref 1.3.2; The coverall material performance are tested accord properties required by the Type defining standard evaluation claims compliance with Type 3, Type 4, flammability performance levels are evaluated in the ISO 13982-1 and EN ISO 13034 standards within the this standard.	ds for protective c Type 5 and Type 6. he corresponding cla	lothing. The requirenuses of El	ne coverall und ed mechanical ar N ISO 14605, E
	EHSR Ref 1.1.2.2, 3.10.2; Evaluation of the performance requirements against processistance to penetration by contaminated liquids obtained results of the corresponding test report; • The coverall material withstands and do not hydrostatic pressure and is classified as Classified	o ISO 16603 and a under hydrostatic of allow any penetral as 6 according to Table evaluation of the land is classified as on by infective ager cording to ISO 226 setup parameters where tested specimens	pressure. Ition of bacable 1 gives class 6 ac action to 10:2018 tes were inline withstands	standards for According to the According to the According to the According to the According to According to Table and the According to Table with the standard. The According to Table the According to Table according to the Table according to the According to Table according to Ta
Article 4.1.4	14126 standard Classification of resistance to per contact with substances containing contaminated liquid The coverall is tested for its resistance to penetration 22612:2005 testing standard. The laboratory environments were inline with the standard requirements. The	netration by infectivations in by contaminated someontal conditions laboratory results	olid particle and the ter indicates	due to mechani es according to I st setup paramet that the tested
Article 4.1.4	14126 standard Classification of resistance to per contact with substances containing contaminated liquid The coverall is tested for its resistance to penetration 22612:2005 testing standard. The laboratory environment were inline with the standard requirements. The specimens the arithmetic mean of penetration result classified as Class 3 according to Table 4 of Clause resistance to penetration by contaminated solid partition The results of evaluation for clause 4.1.4 is summar.	netration by infectivated so in by contaminated so in the conditions alaboratory results are smaller than 1 se 4.1.4.4 of EN 14 cles. ised below; Result	olid particle and the te- indicates log cfu. T 126 standa	due to mechani es according to Itst setup paramet that the tested the tested sample rd Classification Requirement
Article 4.1.4	14126 standard Classification of resistance to per contact with substances containing contaminated liquid The coverall is tested for its resistance to penetration 22612:2005 testing standard. The laboratory environce were inline with the standard requirements. The specimens the arithmetic mean of penetration result classified as Class 3 according to Table 4 of Clauser resistance to penetration by contaminated solid partial	netration by infectivated. In by contaminated someonic laboratory results are smaller than 1 see 4.1.4.4 of EN 14 cles. In the contaminated someonic laboratory results are smaller than 1 see 4.1.4.4 of EN 14 cles.	olid particle and the te- indicates log cfu. T 126 standa	due to mechanics according to I st setup paramet that the tested the tested sampled Classification Requirement of EN 14126
Article 4,1.4	14126 standard Classification of resistance to per contact with substances containing contaminated lique. The coverall is tested for its resistance to penetration 22612:2005 testing standard. The laboratory environce were inline with the standard requirements. The specimens the arithmetic mean of penetration result classified as Class 3 according to Table 4 of Clause resistance to penetration by contaminated solid parti. The results of evaluation for clause 4.1.4 is summar. Resistance to Penetration Propery ISO 16604 - Resistance to penetration by	netration by infectivated so in the property of the property o	olid particle and the terindicates log cfu. T	due to mechani es according to I st setup paramet that the tested the tested sample rd Classification Requirement

Ref: Laboratory Test Report 1 and Test Report 6








	The seam strength is evaluated and classified based on the test report a			t report as	s shown below; Requirement of EN	
Article 4.2	Property of Material EN 14325:2018		Result Classification		EN 14126	
		14323,2018	Refer to the strength			
		5.5 Seam Strength	values for seams at different parts of coverall. The lowest Class is given among all kinds of seams	Class 2	To be Classified	
	Ref: Laboratory Test Report 1					
Article 4.3	EHSR Ref 1.3.1, 3.10.2; The PPE under evaluation conforms the relevant requirements of EN ISO 13688 standard. The requirements of the coverall with respect to health and safety, ageing and sizing are evaluated in EN ISO 13688 section of this report.					
Article 5	EHSR Ref 2.12;					
	The marking requiremnts for protective clothing against chemicals are evaluated in the relevant section of this report. Aditionally; Each piece of coverall have marking with the following information on the single PPE package / PP itself;					
	Applied product standards (EN 14126:2003+AC:2004) Applied product standards (EN 14126:2003+AC:2004) Applied product standards (EN 14126:2003+AC:2004)					
	 Type marking of the PPE as Type 3-B / Type 4-B / Type 5-B / Type 6-B the pictogram "protection against biological hazard" 					
	the pictogram "protection against biological hazard" The above mentioned marking requirements are stated in the technical file of the manufacturer. The above mentioned marking requirements are stated in the technical file of the manufacturer shall be a second of the manufacturer.					
	evaluated samples did not have all these marking and information on the PPE. The maintracturer same follow the instructions in the technical file in case of serial manufacturing of the PPE and veri before putting the PPE on the market.					
	Ref: Teo	chnical File PPE Marking se	ection Annex 9.1	-44-04-05-05-05-05-05-05-05-05-05-05-05-05-05-		
EHSR Ref 1.4; The information supplied by the manufacturer is defined in the relevant section of the to This information includes explanation required by all applied product standard required defined user information text in the technical file includes the following data;						Helles, 11
Article 6	 Name / trademark of the manufacturer, its address, or the authorised representative for F community Type of protection against chemicals (Type-6). The information also includes a reminder to the community 					
	wearing necessary additional PPE in order to achieve a full body protection (i.e boots, glove mask and visor / face shield).					
	• The standard number (EN 14126)					
	• The performance levels identified with the tests against infactive agents					
	 Pictogram and information that the PPE is non-reusable also the shelf life is mentioned Instructions for use, controls before use, how to wear / unwear, limitations, instructuions 					
		Instructions for use, contrastorage conditions, compl	emantary, instructions for	or disposal		
		ove user information text is er Information Sheet	available in English			

n - - - 24125



Sample Photos



Base Model ZK3B-53L



ZK3B-53L VAR1




ZK3B-53L VAR2



ZK3B-53L VAR3



ZK3B-53L VAR4



Arzu ŞEREMETLİ

Osman CAMCI



Approval Suat KAÇMAZ UNIVERSAL CERTIFICATION - Director