

**PQ Corporation**

Performance Materials Division

INTERMINGLASS Sp. z o.o.

Part of PQ Corporation

58-309 Wałbrzych, POLAND

ul. Wrocławska 18A

e-mail : office.poland@pottersbeads.com

tel. +48 74 846 66 58

fax : +48 74 846 66 57

www.pottersbeads.com

DECLARATION OF PERFORMANCE**No. 5**

1. Unique identification code of the product-type:
Code 129 ; 125-850
2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):125-850 (item H23-00-30Q-A-1)
Pallets no. 254-258,261,262 to order no. 323 of 28.02.2020
to Invoice 20250033
3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:
Materials dropped onto paints, thermoplastics and cold plastics, immediately after application to the road surface
4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):
INTERMINGLASS SP Z.O.O.
Wrocławska 18A
58-309 Wałbrzych
Polska
5. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:
System 1
6. The notified body COPRO (N°1137) performed under system 1 the following tasks:
- the determination of the product-type on the base of type testing (including sampling),
- the initial inspection of the manufacturing plant and of factory production control, and
- continuous surveillance, assessment and evaluation of factory production control,
and issued the certificate of constancy of performance 1137- CPR-0474/81
7. Declared performance

Essential characteristics	Performance		Harmonised technical specification
Granulometries :	Sieve μ	Cumulative retained %	EN 1423 : 2012 + EN 1423:2012/AC2013
	1000	0-2	
	850	0-10	
	500	15-45	
	355	55-95	
	212	95-100	
	<212	100	
Maximum weighted % of defective glass beads	PASS		
Refractive index of the glass beads	CLASSE A		
Dangerous substances	Classe I : As / Pb / Sb \leq à 200 ppm		
Resistance to water , hydrochloric acid, calcium chloride and sodium sulfide	PASS		

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 7.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4:

Signed for and on behalf of the manufacturer by:

Wałbrzych / Poland ,

06-03-2020

DYREKTOR ZAKŁADU

Sebastian Draus Sebastian Draus
Plant Manager INTERMINGLASS" Spółka z o.o.
w Wałbrzychu