

# SEMISYNTHETIC 4T 10W-40

## SEMISYNTHETIC ALL-SEASON MOTOR OIL FOR FOUR-STROKE ENGINES.

### SPECIFICATIONS:

SAE 10W-40

API SL

JASO MA2

JASO T903:2016

### DESCRIPTION:

Intended for lubricating systems of modern four-stroke engines of motorcycles, ATVs, scooters and other motor vehicles with any clutch type, and for the power equipment.

Using in water-cooled outboard engines is acceptable.

Produced of high-quality foreign mineral base oils with premium additives package.

### BENEFITS:

- Has high thermal stability and excellent detergency;
- Provides high anti-wear protection within a wide load range;
- Provides effective overheat protection for the engine;
- Minimizes exhaust smoking and emissions toxicity;
- Contains modern premium additives package;
- Excellent stability of viscosity rating within the viscosity grade throughout the service life;

### TYPICAL CHARACTERISTICS:

Kinematic viscosity at 100°C, mm <sup>2</sup> /s	14,0
Density at 20°C, kg/m <sup>3</sup>	873
Viscosity index	143
Alkalinity, mg KOH/g	6,1
Flash point in open crucible, °C	215
Pour point, °C	-32

Packing	Vendor code	Barcode
Canister plastic 1l	004878	482007024193