

Technical Specifications

uMEC10 Monitor size: Weight:	315mm x 155 mm x 220mm ≤3.5kg, Standard parameters configuration, including a lithium battery and a recorder
uMEC12 Monitor size: Weight:	345mm x160mm x 255mm ≤4kg, Standard parameters configuration, including a lithium batter and a recorder
Display Type:	uMEC10: 10.4" color LED, or touchscreen uMEC12: 12.1" color LED, or touchscreen
Resolution: Waveforms:	800 x 600 pixels uMEC10: up to 7 uMEC12: up to 11
External display:	1 display through VGA
ECG Lead set:	3-lead: I, II, III 5-lead: I, II, III, aVR, aVL, aVF, V Automatic 3/5 – lead recognition x0.125, x0.25, x0.5, x1, x2, x4, Auto 6.25 mm/s, 12.5 mm/s, 25 mm/s, 50 mm/s Diagnostic Mode: 0.05-150Hz Monitor Mode: 0.5-40Hz Surgical Mode: 1-20Hz ST Mode: 0.05-40Hz Withstand 5000V (360J)defibrillation <10 s
Defib.protection: Recovery time: CMRR:	Diagnostic Mode: >90dB Monitor, Surgical, ST Mode: >105dB Range:-2.0 to 2.0 mV Accuracy: ±0.02 mV or ±10 %, whichever is greater (-0.8 to +0.8 mV) Resolution: 0.01mV
ST analysis:	Yes, multi-lead, 24 classifications, including AF
Arr analysis: QT analysis:	Yes
Heart Rate Range:	Adu: 15 to 300 bpm Ped/Neo: 15 to 350 bpm
Resolution: Accuracy: HR analysis:	1 bpm ±1 bpm or ±1%, whichever is greater Yes
Respiration Range:	Adu: 0 to 120 rpm Ped/Neo: 0 to 150 rpm
Resolution: Accuracy:	1 rpm 7 to 150 rpm: ±2 rpm or ±2%, whichever is greater 0 to 6 rpm: Not specified
Lead: Sweep speed:	I or II 3mm/s, 6.25 mm/s, 12.5 mm/s, 25 mm/s or 50mm/s
SpO₂ Range: Resolution: Accuracy:	0 to 100% 1% ±2% (70-100%, Adu/Ped) ±3% (70-100%, Neo) Unspecified (0-69%)
Refreshing rate:	≤2 s
Pulse Rate Range:	20 to 300 bpm (from SpO ₂) 30 to 300 bpm (from NIBP) 25 to 350 bpm (from IBP)
Accuracy:	±3 bpm (from SpO ₂) ±3bpm or ±3%, whichever is greater (from NIBP) ±1bpm or ±1%, whichever is greater (from IBP)
Resolution: Refreshing rate:	1 bpm ≤2 s
NIBP Method: Operation mode: Parameters: Systolic range:	Automatic Oscillometric Manual, Auto, STAT, Sequence Systolic, Diastolic, Mean Adu: 25 to 300 mmHg Ped: 25 to 240 mmHg Neo: 25 to 140 mmHg
Diastolic range:	Adu: 10 to 250 mmHg Ped: 10 to 200 mmHg Neo: 10 to 115 mmHg
Mean range:	Adu: 15 to 260 mmHg Ped: 15 to 215 mmHg Neo: 15 to 125 mmHg
Accuracy: Max standard deviation: Resolution: NIBP analysis:	Max mean error:±5 mmHg 8 mmHg 1 mmHg Yes
Temperature Channel:	1-ch (uMEC10), 2-ch (uMEC12)

Parameters: Range: Resolution: Accuracy:	T1, T2 and TD 0 to 50°C (32 to 122 °F) 0.1°C ±0.1°C or ±0.2 °F (without probe)
IBP (for uMEC 12 only) Channel: Range: Resolution: Accuracy: Sensitivity: Impedance range:	up to 2 channels -50 to 300 mmHg 1 mmHg ±2% or ±1 mmHg, whichever is greater (without sensor) 5 μV/V/mmHg 300 to 3000Ω
C.O. (for uMEC 12 only) Method: Range:	Thermodilution C.O.: 0.1 to 20 L/min TB: 23 to 43°C Ti:0 to 27°C
Accuracy:	C.O.: ±5% or ±0.1 L /min, whichever is greater TB, Ti: ±0.1°C (without sensor) C.O.: 0.1 L/min TB, Ti: 0.1°C
CO₂ (for uMEC 12 only) Mode: Range: Accuracy:	Sidestream 0 to 20% (0-152mmHg under standard atmospheric pressure) ±0.1% (<1%) ±0.2% (1 to 4.9%) ±0.3% (5 to 6.9%) ±0.4% (7 to 11.9%) ±0.5% (12 to 12.9%) ±(0.43%+8%rel) (13 to 20%) Unspecified (over 20%)
Sample flowrate: Sample flowrate Accuracy: Start-up time: Response time:	90, 120 ml/min (Sidestream) ±15% or ±15 ml/min, whichever is greater. <90s When using adult water trap and 2.5 m adult sampling line <5.5 s @120 ml/min When using neonatal water trap and 2.5 m neonatal sampling line <4.5 s @ 90 ml/min
AWRR range: AWRR precision:	0 to 150 rpm <60rpm: ±1 60-150 rpm: ±2
Apnea time:	10 s, 15 s, 20 s, 25 s, 30 s, 35 s, 40 s
Data Storage Trend data: Alarm events: Arr. events: NIBP: Waveforms:	1200hrs (Interval 10min), 120 hrs (interval 1 min), 4 hrs (interval 5 sec) 1800 events and associated waveforms 128 Arr. events and associated waveforms 1600 measurements Max. 48 hrs full disclosure waveforms
Battery Type: Voltage: Capacity: Run time: Recharge time:	1 Build-in chargeable Lithium-ion battery 11.1 VDC 2500 mAh (5000 mAh optional) 4 hrs(2500 mAh), 8 hrs (5000 mAh) 2500 mAh: 4 hrsmaximum (power off) 5000 mAh: 8 hrsmaximum (power off)
Interfacing Connectors:	1 AC power connector 1 RJ45 network connector 2 USB 2.0 connector 1 VGA output connector 1 multifunctional output connector (output ECG,nurse call and Defib. Synch. Signals)
WiFi support: Barcode Scanner: Network printer:	Yes, 5G/2.4G dual band Support Support
Recorder Type: Speed: Trace:	Thermal array 12.5mm/s, 25 mm/s, 50 mm/s 3
Power Requirements AC Voltage: Current:	100 to 240 VAC, 50/60Hz 1.5 A
Environmental Requirements Temperature: Storage: Humidity: Operating: Storage: Barometric:	Operating: 0 to 40°C(32 to 104 °F) -20 to 60°C (-4 to 140 °F) 15 to 95 % (non condensing) 10 to 95 % (non condensing) Operating: 427.5 to 805.5 mmHg (57.0 to 107.4 kPa) Storage: 120 to 805.5 mmHg (16.0 to 107.4 kPa)
*Not all of the functions are available in all geographies, please contact with local Mindray sales representative for more information.	



uMEC
Patient Monitor

Taking high cost out of
quality healthcare



www.mindray.com

P/N:ENG-uMEC-210285X4P-20181128
©2018 Shenzhen Mindray Bio-Medical Electronics Co.,Ltd. All rights reserved.


mindray
healthcare within reach




Advanced Performance

With Mindray's 25-year experience in patient monitoring, uMEC series patient monitors cater to clinical needs by offering precise and stable measurement of essential parameters. When monitoring is reliable, you can naturally be more confident with your clinical decisions.


- Mindray's patented Multi-lead ECG Algorithm greatly improves the accuracy of measurement and reduces false alarms
- NIBP quick-measurement technique reduces the discomfort caused by cuff inflation, especially for patients suffering from hypertension or hypotension
- Anti-interference SpO₂ algorithm provides accurate measurement even when the patient is mobile
- Large capacity for data storage enables comprehensive review of patient's history data, and external USB storage devices are also supported
- 8-hour continuous runtime with one Lithium-ion battery



Essentially advanced measurements



Huge data capacity



Long battery working time



Easy to Use

As an user-friendly patient monitor, uMEC helps to simplify workflow and improve efficiency. The monitor provides very intuitive user interface to help faster and easier applications even for new users. Caregivers need less time for training, and get more time for patient care.

- 10.4 inch/12.1 inch high resolution LED screen with optional touch screen
- Supports various monitoring screen layouts for different clinical needs, including large font, full/half screen 7-lead monitoring, view other bed, etc.
- Default settings satisfy general clinical requirements, no need to adjust the settings before using and helps you get started quickly
- Statistics for heart rate changes and ambulatory blood pressure monitoring, making ups and downs visible
- Less than 3.5kg weight with battery makes it very portable
- Unique accessory cabinet makes accessories management effective
- One piece design makes cleaning easier



HR/BP Analysis



User-friendly Interfaces



Unique accessory cabinet



High Durability

To be effective in different environment, uMEC has passed strict electrical safety tests and reliability tests. It is extremely durable and has a long life span.

- Working temperature is 0~40°C, unaffected by extremes
- 0.75 m drop-protection and IPX1 water resistance
- Strong plastic housing resists aging and yellowing, with high corrosion resistance
- Low power consumption and fanless design makes it environmentally friendly and reduces the risk of cross contamination
- Mindray accessories are highly reliable with quality material and production technique



High-quality Accessories



Drop protection



Compatible with multiple cleaning agents