GLITHERM

TECHNICAL SPECIFICATION

Jastrzębie-Zdrój, 1.03.2021

Glicar liquid G12+

Glicar liquid G12+ Long Life - high-quality, glycerine-free car radiator liquid based on ethylene glycol (MEG) characterized by high-performance parameters. Effectively protects the metals of the cooling system against corrosion and ensures long-term durability of the rubber elements thanks to a wide set of anti-corrosion additives, antioxidants, stabilizers, and anti-foaming agents. It is intended for use in the engine cooling systems of passenger cars, delivery vans, trucks and buses, construction machines, military equipment, agricultural tractors and stationary engines fitted with both brass (copper) brazed and aluminium coolers. Ensures protection of the engine cooling system for a period of 5 years or 250 000 km of continuous use.

The product is compliant with the following standards: PN93/C-40008-10;PN-C-40007;ASTM D 5931-13;ASTM D 1287-11;PN 93/C-40008-05;PN-C-4008-06:1993/AZ 1:2000. The product meets the requirements of the AUDI/SEAT/SKODA/VW TL 774 D/F(G12, G12+), ASTM D3306, BS 6580:2010, ASTM D 4985, ASTM 6210, CATERPILAR MAK A4.05.09.01, CUMMINS CES 14439, CUMMINS CES 14603, DAF 74002, FORD WSS-M97-844 D, JOHN DEERE JDM H5, KOMATSU AF-NAC and Man 324 SNF, MB 325.3, RENAULT 41-01-001/- S-TYPE D, VOLVO COOLANT VCS.

Properties

Type of glycol	monoethylene glycol
Concentration	48÷50%
Colour	according to dye
Formulation	homogeneous liquid without sediment
Smell	weak odour
Crystallisation temperature	- 37°C
Expiry date	60 months (5 years without replacement)

The given physical and chemical parameter values are the typical values.

GLI-THERM Sp. z o.o. MANUFACTURER'S DECLARATION.

The manufacturer of the product in question guarantees that the composition of the product shall remain unchanged.

GLI-THERM Sp. z o.o. ul. Rozwojowa 11, 44-338 jastrzębie zdroj, wwige-weiniotocopia tel: 32 797 15 27, biuro@gli-therm.pl, www.ge-weiniotocopia Corespunde cu originalul



SLITHERM

Version:	1
Date of issue:	15.09.2021
Number of updates:	0
Data of updates:	_
Page number:	1 z 6

SECTION 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product Identifier Trade name:

COOLING LIQUID GLICAR G12+

- 1.2. Relevant identified uses of the substance/mixture and uses advised against Recommended use: Filling the cooling system of internal combustion engines
- 1.3.
 Details of the supplier of the safety data sheet

 Company:
 Gli-therm Sp. z o.o.

ul. Rozwojowa 11, 44-338 Jastrzębie-Zdrój Tel.: +48 533 798 833 <u>biuro@gli-therm.pl</u> www.gli-therm.pl

1.4. Emergency telephone number: +48 533 798 833

SECTION 2. HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

Product classification:

Acute Tox. 4, H302, STOT RE 2, H373

Please consult chapter 16 of this SDS for full text of mentioned H phrases.

Physical and chemical hazards:

- none.

- Human health hazards:
- harmful if swallowed
- may cause damage to organs through prolonged or repeated exposure.

Environmental hazards:

none.

2.2. Label elements

Hazard pictograms:



Signal Word: WARNING

H Phrases:

H302 Harmful if swallowed

H373 May cause damage to organs through prolonged or repeated exposure

P Phrases:

P102 Keep out of reach of children

P260 Do not breathe vapours/ spray

P264 Wash hands thoroughly after handling

P270 Do not eat, drink or smoke when using this product

P301+P312 IF SWALLOWED: Call a POISON CENTRE/ doctor if you feel unwell

P314 Get medical advice/attention if you feel unwell

P501 Dispose of contents/container to hazardous or special waste collection point

Contents: Ethane-1,2-diol

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB at concentration equal to or greater than 0,1% by weight.

Declar pe propria răspundere că fotocopia corespunde cu originalul



GLITHERM

Version: 15.09.2021 Date of issue: Number of updates: 0 Data of updates: Page number: 2z6

	A. h. t			<u>.</u>
3.1.	Substances	15		
N.A.				
3.2.	Mixtures			. N.S.
49.0%	- 51.0% Ethane-1,2-diol			N
	Index No: 603-027-00-1	CAS No: 107-21-1	EC No: 203-473-3	
	REACH No: 01-2119456816-28	-0004		
-	Acute Tox. 4, H302, STOT RE 2	2, H373		
0.2% -	0.6% 2-Ethylhexanoic acid			
	Index No: 607-230-00-6	CAS No: 149-57-5	EC No: 205-743-6	
· ·	Repr. 2, H361d			
Please	consult chapter 16 of this SDS for full	ext of mentioned H phrases.		
	California California California	SECTION 4. FIRST AIL	MEASURES	
4.1.	Description of first aid measu	res		
In case	e of Inhalation:			
-	remove to open air	a		

- if breathing is irregular or stopped, administer artificial respiration
- in case of accident or unwellness, consult a doctor immediately and show him packing or label.

In case of skin contact:

- immediately take off all contaminated clothing
 - immediately wash with plenty of water
- if irritation persists, obtain immediate medical attention

wash contaminated clothing separately before using them again.

In case of eyes contact:

- remove contact lenses, if present
- irrigate copiously with clean, fresh water form at least 15 minutes
- if irritation persists, obtain immediate medical attention.

In case of Ingestion:

- rinse mouth thoroughly with water
- induce vomiting only if indicated by the doctor
- give nothing by mouth to an unconscious person
- get medical attention if any discomfort continues
- show this safety data sheet to the medical personnel.

Most important symptoms and effects, both acute and delayed 4.2.

Consumption and inhalation of product mist may cause breathing difficulties. Prolonged skin contact may cause redness and irritation. See section 11.

4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

SECTION 5. FIRE-FIGHTING MEASURES

- 5.1. Extinguishing media suitable extinguishing media:
 - chemical powders (type ABC or BC), CO2, foam, nebulized water extinguishing media which must not be used for safety reasons: water jet, snow extinguishers

5.2. Special hazards arising from the substance or mixture

- do not inhale explosion and combustion gases
- burning produces heavy smoke (CO, CO₂)

cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk cool containers exposed to flames with water until well after the fire is out.

5.3. Advice for firefighters

- use suitable breathing apparatus
- collect contaminated fire extinguishing water separately. This must not be discharged into drains

collect contaminated fire extinguishing water separately. This must not be discharged move undamaged containers from immediate hazard area if it can be done safely and the second secon

03800100803

GLITHERM

1
15.09.2021
0
-
3z6

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures 6.1.

- wear personal protection equipment
- remove all sources of ignition
- evacuate area
- wear breathing apparatus if exposed to vapours/spray
- provide adequate ventilation
- use appropriate respiratory protection.

Environmental precautions 6.2.

- do not allow to enter into soil/subsoil; do not allow to enter into surface water or drains
- retain contaminated washing water and dispose it
- in case entry into waterways, soil or drains, inform the responsible authorities.

Methods and material for containment and cleaning up 6.3.

- immediately remove the product using appropriate personal protective equipment
- eliminate all ignition sources if safe to do so. No smoking, sparks, flames or other sources of ignition near spillage retain contaminated washing water and dispose it
- contain and collect spillage with non-combustible, absorbent material e.g. sand or earth
- flush contaminated area with plenty of water.

6.4. Reference to other sections

See also section 8 and 13.

SECTION 7. HANDLING AND STORAGE

7.1. Precautions for safe handling

- keep away from unguarded flame, sparks, and heat sources. Avoid direct exposure to sunlight. wear personal protection equipment
- use localized ventilation system
- avoid the accumulation of electrostatic charges
- do not eat or drink while working
- avoid breathing vapor, avoid contact with eyes and skin
- do not smoke, do not use matches or lighters.

Conditions for safe storage, including any incompatibilities 7.2.

- always keep the containers tightly closed, in a dry, cool and well-ventilated place (under 40 °C) keep only in the original container
- keep containers upright
- keep away from food, drink and feed
- keep away from unguarded flame, sparks, and heat sources. Avoid direct exposure to sunlight.
- cool and adequately ventilated
- do not store with incompatible substances (see section 10).

Exposure routes

Skin contact

Skin contact

Inhalation

Inhalation

7.3. Specific end use(s)

See section 1.2.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. **Control parameters**

Exposure limit values:

Ethane-1,2-diol:

LTEL/8h: 20 ppm - 52 mg/m³ (Skin) STEL: 40 ppm – 104 mg/m³ (Skin)

DNEL - Ethane-1,2-diol:

Application Area Workers Workers Consumers Consumers.

PNEC - Ethane-1,2-diol: Compartment Fresh water Marine water Aquatic intermittent release **Health effect**

lea. Long-term local 6. Long-term systemic ette Long-term systemic ette Long-term local effects corespunde cu originalul



Value 10 mg/l 1 mg/l 10 mg/l



	Version:	1
	Date of issue:	15.09.2021
	Number of updates:	0
ſ	Data of updates:	-
	Page number:	4 z 6

Fresh water sediment

Soil

Sewage treatment plant

20.9 mg/kg 1.53 mg/kg 199.5 mg/l

8.2. Exposure controls Eye protection:

use close fitting safety goggles, masks suitable for the product.

Protection for skin and hands:

- wear protective gloves, protective clothing. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. Considering the data specified by the glove manufacturer, check during use that the gloves are retaining their protective properties and change them as soon as any deterioration is detected. Frequent changes are recommended.
- Respiratory protection:
- use adequate protective respiratory equipment
 - good ventilation is essential when handling this material do not breathe vapour
- in case of mist or spray exposure wear suitable personal respiratory protection (breathing mask) and protective suit. Thermal Hazards:

None.

Environmental exposure controls:

do not allow to enter into soil/subsoil; do not allow to enter into surface water or drains.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES


9.1. Information on basic physical and chemical properties

(a) Physical state:	homogeneous liquid, without sediments
	various
(b) Colour:	
(c) <mark>Odour:</mark>	little or odorless
(d) Melting point/freezing point:	-37°C (+/- 3°C)
e) Boiling point or initial boiling point and boiling	
range:	> 109 °C
(f) Flammability:	N.A.
(g) Lower and upper explosion limit:	3.2% vol./15.3% vol. (Ethane-1,2-diol)
(h) Flash point:	> 60 °C
(i) Auto-ignition temperature:	398 °C (Ethane-1,2-diol)
(j) Decomposition temperature:	N.A.
(k) pH:	8.0 - 9.5
(I) Kinematic viscosity:	N.A.
(m) Solubility:	N.A.
(n) Partition coefficient n-octanol/water (log value):	-1.36 (Ethane-1,2-diol)
(o) Vapour pressure:	N.A.
(p) Density and/or relative density:	1.055-1.065 a/cm ³
q) Relative vapour density:	2.14 (Air = 1) (Ethane-1,2-diol)
(r) Particle characteristics:	Not applicable
9.2. Other information	

Other solvents: alcohol, acetone, ether. Dynamic viscosity: 16.1 mPas (20 °C) (Ethane-1,2-diol) Critical temperature: 446 °C (Ethane-1,2-diol)

SECTION 10. STABILITY AND REACTIVITY

10.1. Reactive Stable under not	
Stable under nor	mai conditions.
10.2. Chemic Stable under not	cal stability mal conditions.
10.3. Possib N.A.	ility of hazardous reactions
- keep avoid a	ions to avoid way from unguarded flame, sparks, and heat sources. Avoid direct exposure to surfight, ccumulating electrostatic charge ontact with moisture.
- strong	bases and acids. Declar De Dropria Corespundere că fotocopia originalui
	CU Originatia
	alul



Version:	1
Date of issue:	15.09.2021
Number of updates:	0
Data of updates:	-
Page number:	5 z 6

Hazardous decomposition products 10.6.

None.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on hazard classes as defined in Regulation (EC) No 1272/2008 11.1. There is no toxicological data available on the mixture. Consider the individual concentration of each component to assess toxicological effects resulting from exposure to the mixture.

a) Acute toxicity:

Harmful if swallowed. Mixture: 300 < ATEmix ≤ 2000 (mg/kg bodyweight) Oral: Ethane-1,2-diol: Rat LD50 7112 mg/kg Oral: Skin:

Rat LD50 > 3500 mg/kg Rat LC50 > 2.5 mg/l Inhalation:

b) Skin corrosion/irritation: N A

c) Serious eye damage/irritation:

N.A.

d) Respiratory or skin sensitization:

N.A.

e) Germ cell mutagenicity:

NA f) Carcinogenicity:

N.A.

g) Reproductive toxicity:

NA.

h) STOT-single exposure:

N.A.

i) STOT-repeated exposure:

May cause damage to organs through prolonged or repeated exposure.

j) Aspiration hazard:

N.A.

11.2. Information on other hazards: None.

SECTION 12. ECOLOGICAL INFORMATION

Adopt good working practices, so that the product is not released into the environment. Prevent product entering water courses, sewers and prevent penetration of the product into the earth.

12.1. Toxicity: N.A.

Ethane-1,2-diol: EC50: 13 900-57 600 mg/l - toxicity to Daphnia magna, 48h EC50: 6 500-13 000 mg/l - toxicity to Pseudokirchneriella subcapitata, 96h LC50: 72 860 mg/l - toxicity to fish Pimephales promelas, 96h NOEC: 15 380 mg/l - toxicity to fish Pimephales promelas, 7d


12.2. Persistence and degradability:

N.A.

12.3. **Bioaccumulative potential:**

12.3. L...
N.A.
12.4. Mobility in soil: N.A.
12.5. Results of PBT and vPvB assessment: vPvB Substances: None - PBT Substances: None 12.6. Endocrine disrupting properties: Son not available.
The effects:





1: .
15.09.2021
0
 .
6 z 6

SECTION 13. DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods:

Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force.

	SECTION 14	4. TRANSPORT INFORMATION	
14.1.	UN number or ID number:	N.A	
14.2.	UN proper shipping name:	N.A.	
14.3.	Transport hazard class(es):	N.A.	
14.4.	Packing group:	N.A.	
14.5.	Environmental hazards:	N.A.	
14.6.	Special precautions for user:	N.A.	

Maritime transport in bulk according to IMO instruments: N.A. 14.7.

SECTION 15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture 15.1.

- REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on 1. classification, labelling and packaging of substances and mixtures, amending and repealing
- REGULATION (EC) No 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 18 December 2006 concerning 2. the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.

Chemical safety assessment 15.2.

No.

SECTION 16. OTHER INFORMATION

This document was prepared by a competent person who has received appropriate training. This safety data sheet has been prepared on the basis of data provided by the manufacturer.

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This document must not be regarded as a guarantee on any specific product property

ADR: European Agreement concerning the International Carriage of

Dangerous Goods by Road.

CAS: Chemical Abstracts Service (division of the American Chemical Society).

CLP: Classification, Labeling, Packaging.

DNEL: Derived No Effect Level.

EINECS: European Inventory of Existing Commercial Chemical Substances. IMDG: International Maritime Code for Dangerous Goods.

EC50: Half maximal effective concentration

LC50: Lethal concentration, for 50 percent of test population.

LD50: Lethal dose, for 50 percent of test population. STOT: Specific Target Organ Toxicity.

TLV TWA: Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard)

Acute Tox. 4 Acute toxicity 4 Reproductive toxicity 2 Repr. 2

STOT RE 2 Specific target organ toxicity - repeated exposure 2

Full text of phrases referred to in Section 3:

Harmful if swallowed H302

- H361d Suspected of damaging the unborn child
- H373 May cause damage to organs through prolonged or repeated exposure

This document was prepared by:

CHEMIKOS; www.chemikos.pl; e-mail: biuro@chemikos.pl COrespunder De propria COrespunder Caroporia CU Originaluj

0803