

Bookeye® 5

Bookeye® 5 V2 Archive



Scanning Speed

The scanning speed depends on the resolution alone. The Bookeye® 5 scanner always scans in full color, even if bitonal image output is selected. This produces the best possible images. The following matrix shows the scan speed depending on the resolution.

BE5-V2 Archive Scan Time A2+ (620*460 mm)

DIN A2+	@ 150 dpi	0.9 s
DIN A2+	@ 200 dpi	1.1 s
DIN A2+	@ 300 dpi	1.6 s
DIN A2+	@ 400 dpi	2.0 s
DIN A2+	@ 600 dpi	3.0 s

Optical System

Maximum Scan Area	460 x 620 mm (18 x 24 inch), 14% more than DIN/ISOA2
Scanner Resolution	600 x 600 dpi
Pixel Dimension	9.3 x 9.3 µm
Minimum Document Size	100 x 100 mm (4 x 4 inch)
Camera	CCD line sensor, 22,500 pixels (11,000 scan lines equals to a 245 MPixel matrix camera)
Live Preview Camera	CMOS matrix, area sensor
Color Depth	48 bit color 16 bit grayscale
Scan Modes	24 bit color, 8 bit grayscale, bitonal, enhanced halftone
File Formats	Multipage PDF (PDF/A) and TIFF, JPEG, JPEG 2000, PNM, PNG, BMP, TIFF (Raw, G3, G4, LZW, JPEG), AutoCAD DWF, JBIG, DjVu, DICOM, PCX, Postscript, EPS, Raw data and more

Illumination System

Light Source	White LEDs, tested according to IEC 62471
Warm-up Time	None
Temperature Dependency	None
UV / IR Emission	None
Lamp Lifetime	50,000 hours typ. Lamps are covered by the Extended Warranty Option

Electrical Specifications

External Power Supply

Voltage	100 – 240 V AC
Frequency	47 – 63 Hz
Operating Temperature	5 to 40 °C (40 to 105 °F)
Relative Humidity	20 to 80% (non-condensing)
ECO Standard	CEC level VI

Scanner

Voltage	24 V DC
Current	Max. 7.5 A

Power Consumption

Sleep	< 0.5 W
Standby	1.5 W
Ready to Scan, Monitor on	40 W
Scanning	110 W

Dimensions and Weight

Scanner Outer Dimensions (H x W x D)	870 x 730 x 670 mm (35 x 29 x 26 inch)
Weight of Scanner	53 kg (117 lbs.)
Dimension Transport Box (H x W x D)	1010 x 820 x 840 mm (40 x 32 x 33 inch)
Scanner Weight, Ready to Ship	102 kg (225 lbs.)

Ambient Conditions

Operating Temperature	5 to 40 °C (40 to 105 °F)
Storage Temperature	0 to 60 °C (32 to 140 °F)
Relative Humidity	20 to 80% (non-condensing)
Ambient Luminance	< 800 Lux
Noise	< 42 dB(A) (Operating) < 33 dB(A) (Standby)

© 2022 by Image Access GmbH, Wuppertal, Germany.

Printed in Germany. All rights reserved. Reproduction in whole or in part in any form or medium without express written permission of Image Access is prohibited. Scan2Net®, Scan2Pad®, WideTEK® and Bookeye® are registered trademarks of Image Access. All other trademarks are the property of their respective owners.

Image Access reserves the right to change the described products, the specifications or documents at any time without prior notice. For the most recent version, always check our web site www.imageaccess.de or www.imageaccess.us or the customer service portal at portal.imageaccess.de