



FIRE FLASHLIGHT

ISKRA LED



ISKRA LED firefighter flashlight is designed for use in fire protection as well as gas, vapour and mist (G) or dust (D) explosion hazard zones. Durable, non-flammable and light housing. Made of flame-retardant and anti-static thermoplastic. Power source: 4 AA alkaline batteries.

ISKRA LED non-flammable firefighter flashlight with ATEX

- ✓ The flashlight complies with Directive 2014/34/EU and the following harmonised standards:
 - ▶ EN IEC 60079-0:2018
 - ▶ EN 60079-7:2015
 - ▶ EN 60079-11:2012
 - ▶ EN 60079-31:2014
- ✓ Designation: II 2G Ex e ib IIB T4 Gb
II 2D Ex tb IIIC TMax 95°C Db, IP 67
- ✓ Certificate: IEP 14 ATEX 0192
- ✓ Complies with EN 443:2008 point 4.11 in terms of flame resistance.

**Technical parameters:**

- ▶ Power source: — 4 AA (LR6) alkaline batteries
- ▶ Light source: — CREE LED Q5 diode light module
- ▶ Light intensity: — 120 lm
- ▶ Operating time (one set of batteries): — min. 72 h
- ▶ IP protection level: — IP 67
- ▶ Range: — approx. 100 m
- ▶ Weight: — 128g (excl. batteries)

foc lanternă

iskra condus



Lanternă LED ISKRA pentru pompieri este concepută pentru a fi utilizată în protecția împotriva incendiilor, precum și în zonele cu pericol de explozie cu gaz, vapori și ceață (G) sau praf (D). Carcasă durabilă, neinflamabilă și ușoară. Fabricat din termoplast ic ignifug și antistatic. Sursa de alimentare: 4 baterii alcaline AA.

Lanternă ISKRA LED neinflamabilă pentru pompieri cu ATEX

Lanternă respectă Directiva 2014/34/UE și următoarele standarde armonizate:

EN IEC 60079-0:2018
EN 60079-7:2015
EN 60079-11:2012
EN 60079-31:2014

Denumire: II 2G Ex e ib IIB T4 Gb
II 2D Ex tb IIIC TMax 95°C Db, IP 67

Certificat: IEP 14 ATEX 0192

Conform EN 443:2008 punctul 4.11 în ceea ce privește rezistența la flacără.



Parametri tehnici:

Sursa de alimentare:	— 4 baterii alcaline AA (LR6).
Sursa de lumină:	— Modul de lumină cu diodă CREE LED Q5
Intensitatea luminii:	— 120 lm
de	— min. 72 h
protecție IP:	- IP 67
Interval:	— aprox. 100 m
Greutate:	— 128 g (fără baterii)