

Visual/Audible signalling devices

Sounders, bells, flashers and fire signs for analogue addressable control panels

Visual/Audible signalling devices play a key role in every fire detection system. In the event of a fire, these are the devices that warn persons in the area of imminent danger. Sounders, bells and strobe lights are just some of the devices INIM offers in its extensive product line-up.

Conventional visual/audible signalling devices

IS0010RE – Sounder in Red

IS0010WE – Sounder in White

IS0010RES – Audible/Visual signalling device with low-profile base in red plastic

These audible signalling devices operate at 17 to 60 Vdc. Protection rating IP65 (IP 21 for the low-profile base). Complete with mounting base. They provide 32 tones configured by means of a DIP switch. The volume is easily adjusted using the internal trimmer.



Tones	32 tones selectable by means of a DIP Switch
Sound output @ 1 m	106 dB(A) adjustable to 86 dB(A) (depending on the selected tone)
Protection rating	IP65 (IP 21 for the low-profile base)
Operating voltage	17 – 60 Vdc

Current consumption	From 4 to 41 mA (depending on the selected tone)
Operating temperature	-25°C - +70°C
Wire Entry	2 x 20mm on base
Weight	250g
Dimensions	Ø 98 mm h 104 mm (h 80 mm for the low-profile base)

IS0020RE – Audible/Visual signalling device in red plastic enclosure with red lens

IS0020WE – Audible/Visual signalling device in white plastic enclosure with white lens and red LEDs

IS0020RES – Audible/Visual signalling device with low-profile base in red plastic with red lens

These audible signalling devices operate at 17 to 60 Vdc. Protection rating IP65 (IP 21 for the low-profile base). Complete with mounting base. They provide 32 tones configured by means of a DIP switch. The volume is easily adjusted using the internal trimmer.




Tones	32 tones selectable by means of a DIP Switch
Sound output @ 1 m	106 dB(A) adjustable to 86 dB(A) (depending on the selected tone)
Protection rating	IP65 (IP 21 for the low-profile base)
Operating voltage	17 – 60 Vdc
Current consumption Audible section	From 4 to 41 mA (depending on the selected tone)

Current consumption Visual section	5 mA
Operating temperature	-25°C - +70°C
Wire Entry	2 x 20mm on base
Weight	250g
Dimensions	Ø 98 mm h 104 mm (h 80 mm for the low-profile base)

IS0030RE – High powered sounder

These audible signalling devices operate at 10 to 60 Vdc. Protection rating IP66. Complete with mounting base. They provide 32 tones configured by means of a DIP switch. The volume is easily adjusted using the internal trimmer.



Tone	64 tones selectable by means of a DIP Switch
Sound output @ 1 m	120 dB(A) configurable
Protection rating	IP66
Operating voltage	10 – 60 Vdc

Current consumption-audible section	Up to a 550 mA (depending on the selected tone)
Operating temperature	-25°C - +70°C
Weight	1,8Kgg
Dimensions	166 x 150 mm