

Data depunerii ofertei: "20" septembrie 2021

Procedura de achiziție Nr.: 21044131

Anunț/Invitația de participare Nr.:

Către: **Agencia de Dezvoltare Regională Centru**

Specificare tehnica nr.1

Semnat: _____

[semnătura persoanei autorizate pentru semnarea ofertei]



Nume: Cires Ion

În calitate de: director

Ofertantul: SRL Policontract

Adresa: Chisainau, str. Lunca Bacului 33/3

Data: "20" septembrie 2021



| Item | Quantity | Part no. / Description |
|------|----------|---|
| A | 1 pc | 75035 Level switch 2-fold, PVDF/FPM/PVC with 5 m cable for product tank Mathcode: 650 NIVEAUSCHALTER Customs Tariff No.: 90261089 Net Weight: 0,2 kg |
| 30 | 1 pc | 39447 Tank 1000 l closed PE nature Ø1100x1300 with Screwing Cap PE/EPDM Mathcode: 0120G1000E01300112 Customs Tariff No.: 39251000 Net Weight: 37 kg Dosing tank Product: Dosing tank Type: closed, screwing cap with EPDM gasket Nominal capacity: 1000 l Material: PE nature Version: without mounting plate Height: 1300 mm (highest point of tank) Drain plug: threaded sleeve G3/4, not drilled out, plug PE/FPM Mounting set: Mounting angles with screws and washers Special design: FPM gaskets for screwing cap and drainage are attached |
| 31 | 1 pc | 12000135 Plastic Collecting Pan PE for 1000 Liter Round Container, Ø1150 mm h 1080 mm Mathcode: 0120A1000E1080 Customs Tariff No.: 39251000 Net Weight: 25,4 kg Collecting pan Product: Plastic collecting pan Suitable for tank size: 1000 l Material: PE nature Height: 1080 mm |



| Item | Quantity | Part no. / Description |
|------|----------|--|
| 40 | 1 pc | PSDOS-MAG-A2603 Hypochlorite Dosing Station Wall-mounted near the storage tank |

in detail consisting of:

| | |
|---------|--|
| 1,00 pc | wall mounted PE plate with trip pan |
| 3,00 pc | Wall Bracket for MEMDOS LB/LP 4 - 150 |
| 3,00 pc | <p>MEMDOS LP 60 PVC/FPM</p> <p>Product: MEMDOS Type: LP Delivery rate: 63 l/h at 50/60 Hz against max. 10 bar Material dosing head and valves: PVC Signal feedback: Analogue output 0/4 – 20 mA Electric drive: 230 V 1 ph 50/60 Hz 0.25 kW (EC motor) Electric connection: 1.8 m mains cable with plug, Europe (for 230 V AC) Suction valve: DN6 double-ball ceramic/FPM (ball/gasket) Discharge valve: DN6 double-ball ceramic/FPM (ball/gasket) Material suction connection: PVC Suction connection: Hose clamp connection 6/9 Material discharge connection: PVC Discharge connection: Hose clamp connection 6/9 Functions: Stroke frequency can be precisely adjusted via the keyboard Graphic display with multi-language menu Analogue input 0/4 – 20 mA Pulse input (increase and reduction) Level input with early warning and main alarm Release input for external start/stop Supply amount displayed in various units Maximum delivery rate can be limited Stroke feedback output Batch dosing with interval and timer functions Dosing control input Alarm relay output Analogue output 0/4 – 20 mA Dosing quantity adjustment possible in ppm</p> |
| 3,00 pc | Control Cable PVC Length 2 m with Coupling M12x1 4-pole A-coded |
| 3,00 pc | Control Cable PVC Length 2 m with Coupling M12x1 4-pole B-coded |
| 3,00 pc | <p>Suction Line SG-2 DN6 G5/8 M PVC/FPM</p> <p>Product: Suction line Version: Rigid, with adjustable length, foot valve, level control Nominal width: DN6 (50 l/h) Material: PVC Suction connection: Threaded spigot G5/8 M Suction line length: 1160 mm Gasket material: FPM Level control: PP float Number of switching points: 2 Material hose: without suction hose Hose length: - Tank connection: G1 external thread Special design: without Electrical connection: Circular plug-in connect M12x1 free cable length: approx. 1.7 m</p> |