



PX600

SOLID STATE DRIVE

- NVMe interface
- Capacities up to 2000 GB
- Perfect for gaming and everyday use
- Shock resistant and energy efficient
- 3-year warranty limited by TBW ³ with free technical support

PERFORMANCE

250 GB

500 GB

1000 GB

2000 GB

INCOMPRESSIBLE DATA READ SPEED (MAX) ¹	3 200 MB/s	4 700 MB/s	5 000 MB/s	5 000 MB/s
INCOMPRESSIBLE DATA WRITE SPEED (MAX) ¹	1 700 MB/s	1 700 MB/s	3 200 MB/s	4 200 MB/s
TBW ³	100 TB	160 TB	300 TB	600 TB

PARAMETERS

CAPACITIES	250 GB, 500 GB, 1000 GB, 2000 GB
DIMENSIONS	80 × 22 × 3,8 [mm]
INTERFACE	PCIe NVMe gen 4 x4
FORM FACTOR	M.2 2280 [M KEY]
NAND FLASH	3D NAND
MTBF	2 000 000 h
TEMPERATURE	- OPERATIONAL: -25°C ~ 85°C - STORAGE: -40°C ~ 85°C

LOGISTICS DATA

PRODUCT	CAPACITY	P/N	EAN
GOODRAM PX600 SSD	250 GB	SSDPR-PX600-250-80	5908267964071
	500 GB	SSDPR-PX600-500-80	5908267964088
	1 000 GB	SSDPR-PX600-1K0-80	5908267964095
	2 000 GB	SSDPR-PX600-2K0-80	5908267964101

¹ Based on tests performed in Crystal Disk Mark 6.0.0 on SSD in FOB (fresh-out-of-box) state . Actual results may vary depending on your system configuration or SSD wear.

² Storage capacity for GOODRAM SSD is provided in decimal values, i.e. 1GB = 1 000 000 000 bytes. Operating systems that use the binary conversion, i.e. 1GB = 1,073,741,824 bytes, may show lower storage capacity than provided in this specification.

³ For more information about capacities visit www.goodram.com
After exceeding the TBW or 3 years, the SSD is not covered 4 by warranty.