

Descrierea Tehnica "14 " decembrie 2021

la organizarea și instalarea sistemului de semnalizare și avertizare la incendiu

la obiectivul: IMSP Spitalul Clinic de Psihiatrie

amplasat pe adresa: MOLDOVA, mun.Chîșinău, or.Codru (mun. Chișinău), Costiujeni, 3

persoana de contact: 022 857-238 Aurica Ursu

email: achizitii21@bk.ru

Compartimentul 1. Utilaj				
Denumirea		Descrierea	un. de masura	Cantitatea
PREVIDIA216		Intrari Numar bucle: 2 Numar bucle pe sistem extins: 16 Numar adrese pe bucla: 240 Numar zone pe centrala: 1000 Iesiri Iesiri releu alarma: 5A/30V Iesire supervizata alarma: 1,5A 27V Iesire aux: 1,5A 27,6V	buc.	1
ED100		Detector de fum adresabil	buc.	52
EB0010		Soclu pentru detector	buc.	52
EC0020		Buton de alarma adresabil	buc.	2
ES2010RE		Sirena de interior, adresabila	buc.	3
ES0020RE		Sirena de exterior, adresabila	buc.	1
IFM4R		Modul cu 4 releu configurabile. Fiecare releu suporta incarcare pe contacte 5A 30V max. Pana la 16 IFM4R se pot conecta la o centrala.	buc.	1
IFM24160		Modul sursa alimentare curent furnizat 4A. Include circuit de incarcare acumulator de 1.5A, permite incarcarea acumulatorilor de 17 -24 Ah. Centrala poate gestiona 4 surse max in cutii separate.	buc.	1
EU311		Micromodule The EU311 MicroModule, due to its reduced-size, can be housed directly inside the enclosure of the device it controls (callpoint, sounderflasher, beam detector, etc.), it connects directly to the loop and is equipped with a supervised input (capable of controlling the status of a device), a loop-powered output (capable of driving of one audible/visual signalling devices).	buc.	1
Acumulator 12 V		Acumulator 12 V	buc.	2
Cablu de incendiu ignifug 2x0,8 mm		Cablu instalatii, semnalizare, alarmare incendiu, rezistent la foc, halogen-free, manta portocalie (rosu-portocalie). Intergitarea izolatiei construita sa reziste 180 min in flacara fara sa fie distrusa. Mentinerea integritatii in functionare 30 min la flacara directa.	m.	320
CYF 3x1,5 mm		Cablu de alimentare CU 3x1,5 mm	m.	20
20 x 10 x 2000		Pat dublu de 20 x 10 mm, Lungime: 2 m	m.	200
FURTUN METALIC D25		FURTUN METALIC CU IZOLATIE D=25-26MM	m.	10
Elemente de fixare			buc.	10