

KERN OBN 148

The fluorescence microscope for the professional user

KERN



Category

Brand	Optics
Product category	Microscope
Product group	Fluorescence microscope
Product family	OBN-14

Construction

Dimension (W×D×H)	530×220×490 mm
Optical system	Infinity
Tube type	Trinocular
Tube angle of inclination	30°
Tube 360° rotation	✓
Tube type	Siedentopf
Light distribution	0:100 80:20

Contrasting methods

Bright field
Darkfield (optional)
Fluorescent
Polarisation (optional)
Phase contrast (optional)

Standard objectives

4×
10×
20×
40×
100×

Lens quality	Infinity Plan
Nosepiece screw-in locations	5
Interpupillary distance [Min]	50 mm
Interpupillary distance [Max]	75 mm
Diopter adjustment	both-sided
Diopter adjustment [Min]	-5
Diopter adjustment [Max]	5

Ocular

Ocular type	Eyeiece HWF 10x / Ø 20mm with anti-fungus, high eye point
Ocular field width	HWF
Ocular magnifications	10x
Ocular visual field	20 mm
Ocular diameter	23,2 mm

Objective

Objectives - Details	Objective Infinity Plan 10x / 0,25 anti-fungus Objective Infinity Plan 100x / 1,25 oil, spring, anti-fungus Objective Infinity Plan 20x / 0,45 spring, anti-fungus Objective Infinity Plan 4x / 0,11 anti-fungus Objective Infinity Plan 40x / 0,65 spring, anti-fungus
Objectives magnifications	4x / 10x / 20x / 40x / 100x

Illumination

Illuminance	Reflected light Transmitted light
Illumination type incident light	HBO
Illumination type transmitted light	Halogen
Illumination intensity incident light	100 W
Illumination intensity transmitted light	20 W
Illumination dimmable	Transmitted light
Koehler illumination	✓
Filter possible	✓
Aperture diaphragm	✓
Field diaphragm	✓
Brand of light bulb	Philips

Focussing

Field of view [Min]	0,2 mm
Field of view [Max]	5 mm
Torque regulation	✓
Fine drive minimum	0,002 mm
Focusing mechanism	coaxial coarse and fine drive

KERN OBN 148



The fluorescence microscope for the professional user

Fluorescent

Fluorescent unit	Ultraviolet, Violet, Blue, Green (HB0)
------------------	--

Power Supply

Supplied power supply	Power supply unit
Power supply type	Built-in power supply

Plug-in power supply / adapter for countries - included with the delivery	EURO
---	------

Plug-in power supply / adapter for countries - optional	AUS UK US CH
---	-----------------------

Input voltage power supply / power [Max]	100 - 240 V
--	-------------

Power supply cable removable	removable
------------------------------	-----------

Input voltage device / power [Max]	100 - 240 V
------------------------------------	-------------

Power socket for mains adapter	Power supply cable
--------------------------------	--------------------

Environmental conditions

Storage temperature [Min]	-5 °C
---------------------------	-------

Storage temperature [Max]	40 °C
---------------------------	-------

Approval

CE mark	✓
---------	---

Packing & Shipping

Delivery time	1 d
---------------	-----

Dimensions packaging (W×D×H)	500×440×500 mm
------------------------------	----------------

Shipping method	Parcel service
-----------------	----------------

Net weight approx.	16 kg
--------------------	-------

Gross weight approx.	24 kg
----------------------	-------

Shipping weight	23 kg
-----------------	-------

Product information

GTIN/EAN number	4045761163157
REACH classification	no prohibited substances

Pictograms

STANDARD



OPTION

