Huaxia704 ,Huaxia804 Model



FEATURES

- —Excellent Chinese 4 cylinder direct injection diesel engines, fuel efficiency and high torque output;
- —Simple center console structure, high efficiency and easy maintenance, side console for driving and riding comfort;
- —Satisfy different needs and operation, special ceramic material for friction plates with high reliability as well as low use and maintenance cost;
- -12F+12R gears for multi-function operation;
- —New front axle used on the 4x4 model, reliable steering performance in harsh and paddy environments.





Specifications	UNITS	HX704	HX804
Engine		YTO/QC4108T70	YTO/QC4108T80
Rated engine power	hp/kw	70/51.47	80/58.83
Type		4 cyliner,vertical,water cooled,4-strokes	
Ratded engine speed	rpm	2400	2400
Fuel		diesel	
Туре		4 wheel drive,4x4	
Steering		Full hydraulic steering,2 hydraulic pumps	
Gear shifts		12Front + 12Rear,shuttle shift	
Clutch	Inch	Dual stage cluth (Ceramic disk),11 inch	
Speed range	km/h	Forward:2.61-33.59/Reverse:2.29-29.44	
Fuel tank capacity	L	90	
Hydraulic flow	L/min	38.4	
Lift capacity	kg	1500	
Rated traction force	kn	16	17.68
Rops		Available,roll bar and canopy	
Full view cabin		Available,air condition cabin	
Tire		Front/rear:8.3-24/14.9-30, Optional 9.5-20/14.9-30	
Dimensions LxWxH	mm	4150x1800/1900x2480(Rops)	4150x1800/1900x2480(Rops)
		4150x1800/1900x2780(Cab)	4150x1800/1900x2780(Cab)
Front wheel tread	mm	1400	1400
Rear wheel tread	mm	1300-1500 adjustable	1300-1500 adjustable
Wheel base	mm	2072	2072
Min land clearance	mm	410	410
Rops weight	kg	2610	2610
Cabin weight	kg	2820	2820
Front/rear balanced weight	kg	120/180	150/180
Air breaks		Optional,for trailer breaking	
Suspension type		Post positioned 3 point hitch	
PTO	r/min	Dual speeds 540/720r/min,positioned,6 teeth,8 teeth for option	
Start way		Electric starting	

Whatsapp/wechat:+8613625420878,Minna Email: minna@agriculturetractor.com.cn