

## Bratt Pans



Optional 10 mm thick duomat cooking surface with the combination of 2 different stainless steel for better thermal stability available on request

Rounded corners for ease of cleaning

Electronic ignition system visually controlled by indicator lamp on the front of gas models

Safety system to cut off gas and heating if the pan is raised

Safety thermostat to avoid overheating

Thermostatic temperature control between 50-300°C on gas models and 50-300°C on electric models

High quality thermal insulation for limited heat radiation and low energy consumption

Double skin lid with counter balanced mechanism for easy opening

Manual wheel-operated or optional electrically controlled tilt mechanism

Chromed swivel tap on top to refill with hot or cold water.

Even heat distribution with armored heating elements under the cooking surface on electric models



	CODE		L	W	H	CAPACITY	POWER	VOLTAGE
	7867.N1.80908.01		800	900	850	80 lt.	20 kW	230 V / NPE 50 / 60 Hz
	7867.N1.10908.02		1000	900	850	100 lt.	24 kW	230 V / NPE 50 / 60 Hz
	7867.N1.12908.03		1200	900	850	130 lt.	30 kW	230 V / NPE 50 / 60 Hz
	7867.N1.16908.14		1600	900	850	205 lt.	44 kW	400 V / 3 NPE 50 / 60 Hz
	7867.N1.80908.04		800	900	850	80 lt.	9 kW	400 V / 3 NPE 50 / 60 Hz
	7867.N1.10908.05		1000	900	850	100 lt.	12 kW	400 V / 3 NPE 50 / 60 Hz
	7867.N1.12908.06		1200	900	850	130 lt.	15 kW	400 V / 3 NPE 50 / 60 Hz
	7867.N1.16908.18		1600	900	850	205 lt.	21 kW	400 V / 3 NPE 50 / 60 Hz



**7867.N1.80908.04**

## External Boiling Pan



Stainless steel body

Height adjustable legs

Available in 200, 400 and 500 liters capacity

Counter-balanced double skin stainless steel pressure lid with safety valve

Silicone gasket with lid lock for a perfect seal

Safety valve with manometer to avoid overpressure of the steam in the jacket

Articulated spout on the worktop with for filling the boiling pan

2" chrome-plated draining valve with large athermic handle

High quality thermal insulation of the pan for energy saving



**7855.00500.00**

	CODE	CAPACITY	STEAM CONSUMPTION	DISCHARGE VALVE DIA.	MAXIMUM PRESSURE LEVEL	STEAM INLET CON.	STEAM OUTLET CON.	WATER INLET CON. (Ø)	DIMENSIONS
	7855.00500.00	500 l	90 kg./h	2"	40	1 1/2"	3/4"	3/4"	1208 x 1020
	7855.00400.00	400 l	80 kg./h	2"	40	1 1/2"	3/4"	3/4"	1005 x 1100
	7855.00200.00	200 l	60 kg./h	2"	40	1 1/2"	3/4"	3/4"	-