

REV	ECN	Revision History	Date	Editor
A02	D00059410	Update the manufacturer address	2019-06-24	Xu Lin
A01	D00056420	First Release	2018-12-17	Xu Lin
				</

VLS-50 Series Light Source Technical Specifications



SonoScape

SONOSCAPE MEDICAL CORP.

1 Overview

The VLS-50 series light source system is designed to realize multispectral illumination by a white light LED and a violet LED. The white light LED is featured with high color rendering index (≥ 90) and high luminous flux ($\geq 600\text{lm}$), and the violet LED (with main wavelength of 415nm, corresponding to the maximum absorption spectra of hemoglobin) enables to highlight the superficial mucosal micro-vessels, benefiting to identification and diagnosis of the lesion parts.

2 Advanced Technologies

- Multispectral illumination
- Aspheric optical technique
- Capacitor touch screen
- Quick luminous flux adjustment based on current regulation
- High color rendering index and high luminous flux in the white light mode
- High brightness and specific spectra in the special light modes
- Two special light modes
- Fast light mode switch in millisecond order

3 Functions

- Power switch: on/off
- Powering on/off the light source:
 - Powering on: press the **LIGHT** button to enlighten the lamp and the <LIGHT> indicator illuminates.
 - Powering off: press and hold the **LIGHT** button for about 2 seconds to power off the lamp and the <LIGHT> indicator lights off.
- Brightness adjustment:
 - Modes: automatic and manual
 - Adjusting levels: 1–19
- Air-feeding pressure adjustment :
low/medium/high
- Transillumination function:
 - Press the **TRANS** button to enable this function. The transillumination mode can maintain for 6–8 seconds if no button is pressed.
 - Press any button to disable the transillumination mode.
- Services time indication:
 - The elapsed time of the light source is counted every other minute and the left time is indicated when the light source is powered on.
 - The service time indicator flashes

<p>when the elapsed time reaches 10000 hours.</p> <ul style="list-style-type: none"> • Over-heat protection • Abnormal report and processing: Provide the LED flashing, buzzer alarming and so on according to the malfunction processing requirements. • Power-down protection: Provide power-down protection for the light control mode, light control level, air pump powering on/off, air pump flow level and service time <h4>4 Parameters</h4> <ul style="list-style-type: none"> • Light source: W-LED, 70W; violet LED, 50W; no auxiliary lamps • Air-feeding level: four levels off/low/medium/high • Light control level: level 1–19 • Total luminous flux output : $\geq 600\text{lm}$, allowance: -10% • Correlated color temperature (CCT): 5000K – 7000K • Color rendering index (CRI): ≥ 90 in the white light mode • Service time: 10000 hours (continuous use) • Air-feeding system: <ul style="list-style-type: none"> – Air-pump flow levels: high, medium, 	<p>low</p> <ul style="list-style-type: none"> – Pressure range: 0 – 65 Kpa – Maximum air flow volume: <ul style="list-style-type: none"> ➤ High: 3.7L/min – 5.5L/min ➤ Medium: 3.0L/min – 4.7L/min ➤ Low: 2.0L/min – 3.7L/min <h4>5 Ports</h4> <ul style="list-style-type: none"> • Endoscope port • Light source control port • Power supply input port • Equipotential terminal • Optical fiber cable port • Water bottle connector <h4>6 Compatible Equipment</h4> <ul style="list-style-type: none"> • Image processors: HD-550 • Video gastroscopes: 550 series video gastroscopes (EG-550/EG-550L) • Video colonoscopes: 550 series video colonoscopes (EC-550/EC-550T/EC-550/ EC-550L/T) • Trolley: HDT-330 <h4>7 Size and Weight</h4> <ul style="list-style-type: none"> • Size: $473\pm 5\text{mm(L)} \times 370\pm 5\text{mm(W)} \times 154\pm 5\text{mm(H)}$ • Weight: 13kg (approx.)
--	---

- Input power: 300VA

8 Standards

- IEC 60601–1:2005+A1:2012
- IEC60601–2–18:2009
- IEC 60601–1–2:2014

9 Environment Requirements

- Operation environment
 - Temperature: 0°C – + 40°C
 - Relative humidity: 30% – 80%
(non-condensing)
 - Atmosphere pressure: 700hPa –
1060hPa
- Storage environment
 - Temperature: -5°C – +40°C
 - Relative humidity: 30% – 80%
(non-condensing)
 - Atmosphere pressure: 700hPa –
1060hPa
- Transportation environment
 - Temperature: -20°C – +55°C
 - Relative humidity: 20% – 90%
(non-condensing)
 - Atmosphere pressure: 700hPa –
1060hPa
- Power supply requirements:
 - Input voltage: 100 – 240V AC
50/60Hz

NOTE:

- The specifications of this system may change without any prior notification.
- Some products or features may not be available in some countries.
- Please contact your local SonoScape sales representative for more information.

Manufacturer: SonoScape Medical Corp.

Address: Room 201 & 202, 12th Building, Shenzhen Software Park Phase II, 1 Keji Middle
2nd Road, Yuehai Subdistrict, Nanshan District, Shenzhen, 518057, Guangdong, China

Tel: +86-755-26722890

Fax: +86-755-26722850

E-mail: sonoscape@sonoscape.net

www.sonoscape.com