

BCS-B-SP1602G-1SFP

Index: 11286
GTIN13/EAN13: 5904890708457
URL: <https://bcs.pl/gb/poe-switches-/3402-bcs-b-sp1602g-1sfp-5904890708457.html>



Product Details

Product	BCS-B-SP1602G-1SFP
Brand	BCS BASIC
PoE ports	16×RJ45 100Mbps
Uplink ports	2×RJ45 1Gbps / 1×SFP 1Gbps
Standard IEEE	802.3af / 802.3at
Transfer	10/100/1000Mbps half-duplex, full-duplex, auto-negotiation, auto MDI/MDIX
Packet forwarding rate	5.36Mpps
Capacity	7.2Gbps
STANDARD mode	100m
VLAN mode	VLAN mode ports 1-16 isolated
EXTEND mode	EXTEND mode ports 1-8 support transmission 250m 10Mbps (cat5e, cat6)
QoS mode	QOS Quality Of Service - priority video pockets
PoE mode	Monitoring ports supply PoE devices and automatic restart with power supply cut when not responding
PoE pin	1,2(+), 3,6(-)
LED status	PWR(red): power supply connected, LINK/ACT(green): device connected, PoE(yellow): device powered from PoE
PoE switch power	150W max 30W/port
Power supply	100~240V AC
Working environment	0°C~+40°C max 90% RH
Weight	1.5 kg

Casing	1U
Dimensions (W×D×H)	285×180×44mm