



Product Service

# CERTIFICATE

No. Z2 076729 0101 Rev. 20

**Holder of Certificate:** Seraphim Solar System Co.,Ltd.

No.1-2, Hengyao Rd, Henglin Zhen  
Wujin District  
213101 Changzhou  
PEOPLE'S REPUBLIC OF CHINA

**Certification Mark:**



**Product:**

**Crystalline Silicon Terrestrial Photovoltaic (PV) Modules  
Mono-crystalline Silicon Photovoltaic Module**

The product was tested on a voluntary basis and complies with the essential requirements. The certification mark shown above can be affixed on the product. It is not permitted to alter the certification mark in any way. In addition, the certification holder must not transfer the certificate to third parties. This certificate is valid until the listed date, unless it is cancelled earlier. All applicable requirements of the testing and certification regulations of TÜV SÜD Group have to be complied. For details see: [www.tuvsud.com/ps-cert](http://www.tuvsud.com/ps-cert)

**Test report no.:** 704061801207-21

**Valid until:** 2026-12-06

**Date,** 2021-12-08

( Zhulin Zhang )

# CERTIFICATE

No. Z2 076729 0101 Rev. 20

## Model(s):

1500 V DC Maximum System voltage,  
Fire Safety Class C Modules:  
SRP-xxx-6MA-HV (xxx=330-400, in step of 5);  
SRP-xxx-6MB-HV (xxx=275-330, in step of 5);  
SRP-xxx-E01A-HV (xxx=365-420, in step of 5);  
SRP-xxx-E01B-HV (xxx=305-350, in step of 5);  
SRP-xxx-BMA-HV (xxx=330-455 and xxx=525-550, in step of 5);  
SRP-xxx-BMB-HV  
(xxx=275-375 and xxx=440-455 and xxx=590-605, in step of 5);  
SRP-xxx-BMC-HV  
(xxx=305-380 and xxx=485-500 and xxx=650-670, in step of 5);  
SRP-xxx-BMD-HV (xxx=390-410 and xxx=535-545, in step of 5);  
SRP-xxx-BME-HV (xxx=475-485, in step of 5);  
SRP-xxx-BMF-HV (xxx=415-425, in step of 5);  
SRP-xxx-E6A-HV (xxx=410-435, in step of 5);  
SRP-xxx-E6B-HV (xxx=350-370, in step of 5);  
SRP-xxx-BMZ-HV (xxx=425-450, in step of 5);  
SRP-xxx-6MA-TB (xxx=330-400, in step of 5);  
SRP-xxx-6MB-TB (xxx=275-330, in step of 5);  
SRP-xxx-E01A-TB (xxx=365-420, in step of 5);  
SRP-xxx-E01B-TB (xxx=305-350, in step of 5);  
SRP-xxx-BMA-TB (xxx=330-455 and xxx=525-550, in step of 5);  
SRP-xxx-BMB-TB  
(xxx=275-375 and xxx=440-455 and xxx=590-605, in step of 5);  
SRP-xxx-BMC-TB  
(xxx=305-380 and xxx=485-500 and xxx=650-670, in step of 5);  
SRP-xxx-BMD-TB (xxx=390-410 and xxx=535-545, in step of 5);  
SRP-xxx-BME-TB (xxx=475-485, in step of 5);  
SRP-xxx-BMF-TB (xxx=415-425, in step of 5);  
SRP-xxx-E6A-TB (xxx=410-435, in step of 5);  
SRP-xxx-E6B-TB (xxx=350-370, in step of 5);  
SRP-xxx-BMZ-TB (xxx=425-450, in step of 5);

1000 V DC Maximum System voltage,  
Fire Safety Class C Modules:  
SRP-xxx-6MA (xxx=330-400, in step of 5);  
SRP-xxx-6MB (xxx=275-330, in step of 5);  
SRP-xxx-E01A (xxx=365-420, in step of 5);  
SRP-xxx-E01B (xxx=305-350, in step of 5);  
SRP-xxx-BMA (xxx=330-455 and xxx=525-550, in step of 5);  
SRP-xxx-BMB  
(xxx=275-375 and xxx=440-455 and xxx=590-605, in step of 5);  
SRP-xxx-BMC  
(xxx=305-380 and xxx=485-500 and xxx=650-670, in step of 5);  
SRP-xxx-BMD (xxx=390-410 and xxx=535-545, in step of 5);  
SRP-xxx-BME (xxx=475-485, in step of 5);  
SRP-xxx-BMF (xxx=415-425, in step of 5);  
SRP-xxx-E6A (xxx=410-435, in step of 5);  
SRP-xxx-E6B (xxx=350-370, in step of 5);  
SRP-xxx-BMZ (xxx=425-450, in step of 5);

1500 V DC Maximum System voltage,  
Fire Safety Class A Modules:  
SRP-xxx-6MA-BG (xxx=350-395, in step of 5);  
SRP-xxx-6MB-BG (xxx=295-325, in step of 5);  
SRP-xxx-6MA-DG (xxx=350-395, in step of 5);  
SRP-xxx-6MB-DG (xxx=295-325, in step of 5);  
SRP-xxx-BMA-BG (xxx=330-455 and xxx=525-550, in step of 5);  
SRP-xxx-BMB-BG  
(xxx=290-375 and xxx=440-455 and xxx=590-605, in step of 5);  
SRP-xxx-BMC-BG



# CERTIFICATE

No. Z2 076729 0101 Rev. 20

(xxx=320-375 and xxx=485-500 and xxx=650-670, in step of 5);  
 SRP-xxx-BMD-BG (xxx=395-410 and xxx=535-545, in step of 5);  
 SRP-xxx-BME-BG (xxx=475-485, in step of 5);  
 SRP-xxx-BMF-BG (xxx=415-425, in step of 5);  
 SRP-xxx-BMA-DG (xxx=350-425, in step of 5);  
 SRP-xxx-BMB-DG (xxx=290-350, in step of 5);  
 SRP-xxx-BMC-DG (xxx=320-350, in step of 5);  
 SRP-xxx-BMZ-BG (xxx=425-450, in step of 5);  
 xxx is standing for rated output power at STC.

## Parameters:

Safety Class:	Class II
Max. System Voltage:	1000V DC or 1500V DC
Test Laboratory:	Changzhou HuaYang Inspection and Testing Technology Co., Ltd No.8 Lanxiang Road Wujin Economic Development Zone Changzhou, Jiangsu, China.
Construction:	Framed or Frameless, with Junction box, cable and connector.
Fire Safety Class:	Class C or Class A according to UL790

## Tested according to:

IEC 61215-1(ed.1)  
 IEC 61215-1-1(ed.1)  
 IEC 61215-2(ed.1)  
 IEC 61730-1(ed.2)  
 IEC 61730-2(ed.2)