


| Category | | DLP--0.6ST SHORT THROW PROJECTOR |
|---------------------------|-------------------|--|
| Model Description | | Native XGA with 240w Lamp |
| OWAY PROJECTOR MODEL NAME | | P290 |
| Photo | |  |
| Main components | Technology | DLP |
| | Projection system | 0.55'DMD |
| | Lens | 0.6:1 (80"@1m) |
| | Lamp Life | 4000(standard), 6000hrs (power saving) |
| Resolution | Standard | XGA |
| | Compatible | VGA\SVGA\XGA\SXGA\SXGA+\WXGA\UXGA |
| Brightness | | 4200lumen (ISO21118) |
| Lamp | | 240w |
| Contrast | | 8000:1 |
| Uniformity | | 80% |
| Colorwheel | | 6segment |
| Colors | | 1.07 billion |
| Weight | | 2.6kg |
| Dimension | | 284.0mm x 234.3 mmx 81.5 mm |
| Projection Method | | front projection/rear projection, table/ceiling mounted |
| Projection Size | | 30"-300" |
| Aspect Ratio | | 4:3/ 16:9 |
| Keystone Correction | | vertical v-correction±40° |
| Scanning Frequency | | horizontal: 31 ~ 100 KHz; vertical: 50 ~ 120 Hz |
| Video Format | | NTSC, NTSC 4.43 |
| | | PAL, PAL-N, PAL M |
| | | SECAM、HDTV (480i/p, 576p, 720p, 1080i/p)、 |
| Interfaces | Input | 2 x VGA (15-pin D-Sub) ,1x Composite Video (RCA jack), 1x S-Video (Mini-DIN 4 pin), 2x Audio(3.5 mm), HDMI x 1 |
| | Output | 1x VGA ,1x Audio(3.5 mm) |
| | Controlling | 1xUSB Type B; 1x RS-232 |
| Speaker | | embedded 2W*1 speaker |
| Noise | | standard mode 32dB,economic mode 30dB |
| Power Supply | | AC 100-240 V, 50 - 60 Hz |
| Power Consumption | | 315W(maximum) stand by<0.5W |
| Ambient Temperature | | operation: temprature0°C-40°C humidity10%-80% |
| | | storage: temprature-20°C-60°C humidity 30%-85% |
| Gross Weight | | 3KG |
| carton size (WxDxH) | | 330mm x 140mm x 330mm |