

Dispozitiv de agățare tomberon



Parametrii tehnici:

Dispozitiv de gățare tomberon

LUNGIME:	3000 mm
LATIME:	600 mm
INALTIME:	3200 mm
GREUTATE:	400 kg
Sistem de functionare:	Hidraulic
PUTERE hidraulica:	160 bar
Latimea de agatare tomberon:	360-560 mm
Înălțimea de ridicare tomberon:	3300 mm
Capacitatea de încărcare:	500 kg

Lama nivelare pe incarcator frontal MTC Metals



Parametrii tehnici:

Lama nivelare pe incarcator frontal EURO

Latime:	2000 mm
Inaltime:	600 mm
Greutate:	205 kg
Viteza de lucru:	5 km/ora
Agatare:	EURO
Putere tractor:	70/120 cp

Mătură stradală MTC 2000



Parametrii tehnici:

Mătură stradală

Latime de lucru:	2000 mm
Înălțime:	800 mm
Greutate:	470 kg
Viteza de lucru:	6 km/ora
Agatare:	EURO
Putere tractor:	70/120 cp
Volum collector:	250 litri
Viteză de rotație a periei:	130 rot/min



Main Dispositions:

Dual-function clutch
 Twin turning speeds of P.T.O.
 Power steering
 Saft start switch Metal sheet hood
 Combined meters Quality seat system
 Seat belt

Options:

Creeper gear
 Hydraulic outlet Air brake system

Tractor Parameters	Model		DF-904/954
	Drive Type		4WD
	Overall Dimensions L×W×H(mm)		4240×2050×2810
	Wheel Track(mm)	Front	1610
		Rear	1620-2020(1620)
	Wheel Base(mm)		2362
	Ground Clearancr(mm)	Under Front Axle	379
	Rated Traction Force(N)		18600/19200
	Construction Mass(Kg)		4500
	Min. Turning Radius(m)		4.1
	Theoretical Speed(km/h)	Forward	2.30,3.60,5.80,8.00,10.0,15.6,25.0,34.9
		Reverse	3.10,4.80,7.70,10.80
Engine Specifications	Model		LRC4108T/4MC-T
	Type		4-cylinder,Upright inline cylinder radiator cooling,4-storke cycle,direct-injection
	Rated Power(Kw/hp)		59.0/80.0,62.5/85.0
	Rated Fuel Consumption(g/kw/h)		≤242
	Rated Speed(rpm)		2300
	Bore×Stroke(mm)		108×135/110×135
	Total Displacement(L)		4.94/5.13
Drive System	Clutch		Dry Independent type dual Function clutch
	Gear Box		4*3/4
	Main Drive		One Pair of Spiral Bevel Gear
	Differential		Obturation,four bevel gears
	Differential Lock		Mesh gear
	Final Transmissions		Planetary reduction gear
Travelling Mechanism	Tyre	front	13.6-24
		rear	16.9-34
	Steering Gear		Hydraulic steering
	Brake		Oil immersed muliplate disc
Working Device	Hydraulic System	Lifting Capacity at 610 mm Behind Lift Point(Kg)	3300
		3-point Suspension	Category:II
	P.T.O.Shaft	Rotating Speed(rpm)	540/1000
		Spline size	6- φ 35 Rectangular spline

5 Tons



PRODUCT FEATURES AND OPTIONS



Capacity
7,6m³



Dimensions: 210x400x50
(Width x Length x Side Door)



Loading Capacity:
5 Tons



Extention:
: 30+30 cm or 40+40 cm



Tyre:
11.5 / 80-15.3

OPTIONS & DIFFERENCES ON THE COMPONENTS



Extra Extention Difference



Openable Side Doors Difference



Brand (Hammock) Differences



Air Brake Differences

Tocator crengi TN-130TKcu transport.2m*



Tara producatoare	Ucraina / Shkiv
Modul de agregatare	Purtat
Grosimea de taiere in verde	13 cm
Grosimea de taiere in uscat	10 cm
Grosimea de taiere lemn tare	9 cm
Productivitatea	2-6 m3/h
Greutatea kg	290
Lungimea de taiere	12-14 cm
Puterea necesara CP	Min.65
Garantie	12 luni

Tomberon/Pubela 120 L



Parametrii tehnici:

Tomberon din plastic cu capac si roti din cauciuc, 120 L

VOLUM:	120 L
DIMENSIUNI mm:	480 x 530 x 990 mm
DIAMETRU ROȚI:	200 mm
MATERIALUL PRODUS:	HDPE
CULOARE:	VERDE
DOTĂRI:	MÂNERE / ROȚI / AX ZINCAT