

Shaping new

Delivering Safe Hematology Care

Affordable Hematology Solutions for Small-Mid Laboratories









Compact Hematology Solution

- Open Tube & Closed Tube versions
- CBC/DIFF Analysis
- 2 reagents use
- 37 parameters menu



Full Walk Away Solution

- Auto loader version
- Integrated auto sampler
- Positive identification
- 40 tubes in continuous loading
- Urgent mode







Dimensions for Hematology

New Dimensions for Hematology Diagnosis

Enhanced Performance, New Features, Increased Benefits

#1 Workflow Management



Optimize your daily routine

#2 Clinical Performances



Ensure effective diagnosis

#3 Infectious Screening



Cost effective flagging: Malaria & Dengue

#4 Remote Connection



Connect the lab with Yumicare

Extensive Applications

Variety of clinical lab environments and clinical settings



Critical care

- Capillary Blood Compatibility
- Fast Testing
- Prediluted Mode



Backup System

- Satellite Labs
- Night Shift Analysis
- Back up to HELO Solution



Oncology Care

- WBC Diff Separation
- WBC Immature Cells: IMG, IML, IMM
- Blasts Flagging



Health Centers

- Simplicity of use
- HL7
- Infectious Screening Flags



Infectious Care

- Malaria & Dengue Screening Flags
- Scoring Flags
- Neutrophils-To-Lymphocyte Ratio




Blood Banks

- QC testing: RBC & PLT concentrates
- Residual Cells Detection of WBC concentrates in cellular therapy



#1 Workflow Management



Expend your analysis possibilities

Different analysis modes

- Standard Patient mode
- Prediluted mode with customized dilution ratio for micro sample volumes
- QC mode for dedicated Difftrol ® QC kits

Safe blood testing against pathogens exposure with:

- Closed tube with the H500
- Sample rack auto loading with the H550

Capillary blood compatibility

Yumizen H500 and H550 have been validated on capillary blood samples with correlation to venous blood.







Fully walkaway system with new usability

High automation level

- Continuous loading (40 tubes)
- Automatic and scheduled start up and shutdown
- Secured reagent management with unique identification code
- Positive tube identification in rack mode
- Automated user maintenance

Improved usability

- New graphical interface with color-coded menus
- Only 2 reagents for hematology analysis and 1 reagent for cleaning maintenance

Data Management

Data Management options

- Yumizen P8000 Connection
- Data printout with optional printer
- Paperless patient reports results in PDF formats
- 10,000 patient data storage with easy USB export
- Bidirectional host communication: ASTM and HL7 standards
- Save & Restore database and settings







Quality Control Management

Embedded quality control indicators

- iQC indicators: Levey-Jennings flags, Radar Graphs view, XB means
- Overlapping QC when switching QC batches
- eQC testing in different modes
- Repeatability testing mode

Full quality tools package

HORIBA Medical provides a full Quality Assurance Program:

- QCP: inter-laboratory comparison program
- QSP: cytology skills staff monitoring
- Accreditation Help Support
- Cytological Atlas



Report Results Faster

Increase throughput

60 tests per hour: 3 models able to process whole blood samples on 20µL.

Urgent mode


Yumizen H550 able to manage urgent samples in **real STAT mode** to run closed, open tubes or micro-tubes during routine workflow.







#2 Clinical Performances



WBC: Full Leukocytes Menu for Oncology Care Monitoring

Large Immature Cells (LIC) differentiation:

- IML: Immature cells of lymphoid lineage with large and granulocytic lymphocytes.
- IMM: Immature cells of monocytic lineage which could include promocytes or monoblasts.
- **IMG**: Immature cells of granulocytic lineage with precursors cells of myelocytes, promyelocytes and metamyelocytes.

Exclusive Lymphocytes differentiation:

• **ALY**: Atypical Lymphocytes as sub population of Lymphocytes for detecting activated lymphocytes, granulocytic lymphocytes, Sezary cells, tricholeucocytes,...

RBC: Full Digital Technology Measurement for Accurate Results

Patented RBC Filtering Technology

New digital filtering technology: RBCs pulses optimization by rejecting the rotated cells and other flow induced particles.

- Accurate measurement of RBCs volume and distribution widths.
- Very good correlation of MCV and RDW parameters between hydro-focused system and classical impedance with digital filters.

Diagnostics Tools for Anemias and Thalassemia Pathologies

Complete parameters menu for flagging RBCs disorders:

HGB (cyanide free lysis), MCV, MCHC, MIC (Microcytes), MAC (Macrocytes), RDW-CV, RDW-SD

PLT: Reliable Counting and Markers for Platelets Disorders

Low Limit Of Quantification: below 10.10⁹/L fitting to support clinicians taking **blood transfusion** decision.

Specific Indices for Platelets Activation at no extra cost

P-LCC and **P-LCR** (Platelet Large Cells Count & Ratio), into **large platelets size flagging**: immature platelets in cases of thrombocytopenia, reactive thrombocytosis or Giant platelets either from inherited disorders or in myeloproliferative syndrome.





#3 Infectious Screening



Infectious Screening Flags Combined with Full Blood Count



The Automated Suspicion Flags are optionally available in routine use with Diff hematology test and without any specific reagent or dedicated mode for:

- Malaria Plasmodium falciparum
- Malaria Plasmodium vivax
- Dengue fever

Flag's methodology and efficiency

- Innovative machine-learning techniques
- 3 different labs assessment: India and Africa
- Clinical accuracy: 70 to 85%
- S-Flags: triggering levels & displaying relevancy
- NLR: marker of inflammation & infectious monitoring

80 55 40
Malaria P. Falciparum? P. Vivax? Dengue?

Infectious Screening Flags are optionally available on Yumizen H500 and H550 upon request towards vour HORIBA Medical representative

#4 Remote Connection



Connect the lab with Yumicare

Increasing Analyzer Availability

- Remote Software Update
- Predictive Maintenance

Easing Quality Control

- Remote QC target values
- Automated QC results transfer to QCP

Monitoring Hematology Activity

- Daily Routine Overview
- Consumption Monitoring











Dimensions & Weight: Height Width Depth Weight

Yumizen H500 OT 39.7 x 47.7 x 48.3 cm 22 kg 15.63 x 18.78 x 19.02 in. 49 lbs

Yumizen H500 CT 39.7 x 47.7 x 48.3 cm 23.5 kg 15.63 x 18.78 x 19.02 in. 51 lbs

Yumizen H550 53 x 66.8 x 62.1 cm 35 kg 20.87 x 26.3 x 24.45 in. 78 lbs

Printer (optional): Compatible models with Linux drivers

Throughput: 60 samples/hour

Sample Management (Yumizen H550): Autonomy of 40 tubes in 1 hour Continuous Loading STAT Mode Rack Automatic Mixing Tubes Positive Identification

Analysis Mode: Patient, Prediluted, iQC (Difftrol), eQC (External)

Sound Level: 60 dBa

Operating Temperature & Humidity: +15°C (+59°F) to + 30°C (+86°F) Relative humidity up to 80% maximum, without condensation

Specimen Type & Volume: Human venous and capillary blood EDTA K2, EDTA K3 anticoagulant CBC mode: 20µL DIF mode: 20µL

Power Requirements:

Power Supply: AC/DC adapter (external) 24 Vdc Power consumption: 180 VA Heat output: 378 KJ/h

Reagents:

2 reagents for analysis: ABX Diluent (10L or 20L) Whitediff 1L (cyanide free)

1 reagent for daily shutdown: ABX Cleaner 1L

ECO FRIENDLY SOLUTION

LED light source Cyanide free lysis reagent Low reagents consumption: < 20 µL/test WEEE Standard compliance

PHYSICAL SPECIFICATIONS MEASUREMENT PRINCIPLES

WBC & Differential

Methods:

- - Double Hydrodynamic Sequential System 'DHSS'
- Optical Reading : Absorbance
- Impedance Variation

HGB Measurement

Method:

Spectrophotometry

RBC & PLT Detection

Methods:

- Impedance Variation
- Analogic Digital Conversion

HCT Measurement Method:

Analogical integration

SOFTWARE SPECIFICATIONS

 Data Processing Color LCD touch screen: 12,1 in. Operating System: Linux™ Connection: RS232, Ethernet, USB Communication: ASTM & HL7 protocols Capacity: 10 000 results + graphs Options: keyboard, mouse and bar code reader

 Quality Control 3 controls levels (low, normal, high) Target values download QC results compatible with HORIBA Medical Quality Control Program (QCP) Levey-Jennings graphs Radar graphs XB on 3 or 9 parameters Overlapping QC (6 active QC files)

• Yumicare® Connected service option: LAN, Wifi, 4G Automatic QC management (target values download and QC results upload to QCP) Analyzer activity monitoring Consumption management Remote software update

Predictive maintenance

PARAMETERS & PERFORMANCE DATA

37 Parameters: **WBC** NEU# & NEU% LYM# & LYM% MON# & MON% EOS# & EOS% BAS# & BAS% IMG# & IMG% IML# & IML% IMM# & IMM%* ALY# & ALY% LIC# & LIC%*

RBC HGB **HCT** MCV MCH **MCHC** RDW-CV RDW-SD* MIC* MAC*

РΙΤ MP\/ PCT³ PDW/ P-LCC P-LCR*

NLR (Neutrophil-To-Lymphocyte Ratio)

Infectious Screening Flags (Option) Plasmodium falciparum, Plasmodium vivax, Dengue fever Scoring flags

Analytical Measurements Range:

Linearity Limits	Visible Range	Unit
WBC 0 - 300 RBC 0 - 8 HGB 0 - 240 HCT 0 - 0.67 PLT 0 - 2500 PLT (concentrate)	300 - 999 8 - 18 240 - 300 0.67 - 0.80 2500 - 4000	10 ⁹ /L 10 ¹² /L g/L L/L 10 ⁹ /L
0 – 4000	4000 - 5000	10 ⁹ /L
Limit Of Quantification	Unit 10º/l	

10¹²/L

g/L

109/L

cision (Repeatability)

RBC 0,2

HGB 1,5

PLT 8

riecision (nepeatability).		
Parameters CV (%)	Range	Unit
WBC <3.0	4 – 100	10 ⁹ /L
RBC <2.0	3.6 - 6.2	10 ¹² /L
HGB <1.5	120 - 180	g/L
HCT <2.0	0.36 - 0.54	L/L
PLT <5.0	180 - 500	10 ⁹ /L

* RUO parameters (Research Use Only)-





FRANCE +33 (0)4 67 14 15 15 - ITALY +39 / 06 51 59 22 1 - SPAIN +34 / 91- 353 30 10 - PORTUGAL +351 / 2 14 72 17 70 - UK +44 (0) 1604 542650 POLAND +48 / 22 6732022 - USA +1 / 949 453 0500 - BRAZIL +55 / 11 2923-5439 - THAILAND +66 / 2 861 59 95 - IINDONESIA +62 / 21 3044 8525 CHINA +86/21 3222 1818 - INDIA +91/11 4646 5000 - GERMANY AXON LAB AG +49/7153 92260 - DISTRIBUTORS NETWORK +33 (0)4 67 14 15 16 HORIBA Medical online: https://www.horiba.com/medical

















(

