

SPECIFICAȚII TEHNICE (F4.1)

Nr.	ocds-b3wdp1-MD-1592826164460	14.07.2020	Alternativa nr.-
	Denumirea licitației: Serviciul de Informații și Securitate al RM	Lot 1-17	Pagina 1 din 1

LOT	Denumirea bunurilor și/sau a serviciilor	Modelul articolului	Țara de origine	Producătorul	Specificarea tehnică deplină solicitată	Specificarea tehnică deplină propusă de către ofertant	Standarde de referință
1	2	3	4	5	6	7	8
Lot 1	Calculator ALL-IN-ONE	V530-24ICB AIO	China	Lenovo	CPU: minim 3 MB Cache, minim of Cores 2, frecvența nu mai mică de 2,7 GHz; RAM: min 4 GB DDR4; Stocare: SSD minim 256 GB Ecran: minim 23", Full HD IPS WLED 1920x1080; Porturi: GLAN RJ 45, Audio jack 3.5mm, Jack microfon, HDMI, USB tip 2.0 și 3.0; Boxe încorporate; În completare: tastieră cu fir USB (ro-ru) + mouse cu fir USB de la uzina producătorului (aceeași marcă); Sistem de operare: Microsoft Windows 10 pro x64, En.	Calculator All-in-One Lenovo V530-24ICB AIO CPU: Intel Pentium Gold G5420T (2C / 4T, 3.2GHz, 4MB) RAM: 4 GB DDR4; Stocare: 2.5" SSD 256 GB Ecran:23.8" FHD (1920x1080) IPS Anti-glare, WLED Porturi: GLAN RJ 45, Audio jack 3.5mm, Jack microfon, HDMI-in,HDMI-out,4xUSB tip 2.0 și 3x3.1; Boxe încorporate 3Wx2; În completare: tastieră cu fir USB (en/ro-ru) + mouse cu fir USB de la uzina producătorului (Lenovo); Sistem de operare: Microsoft Windows 10 pro x64, En.	
Lot 2	Monitor	Pro 1000	China	Sven	Monitor BLACK minim 23.8", IPS-ADS LED, 250 cd/m2, 1000:1, 10M:1, 178/178 grade vizibilitate, 5 ms, audio inclus 2x2 W, VGA, DVI, HDMI, bloc de alimentare încorporat, boxe încorporate, cabluri (video, audio, power) incluse.	SVEN Pro 1000 (USB), Line-interactive UPS with AVR, 1000VA /720W, 3x Schuko outlets, 2x7AH, AVR: 175-280V, USB, RJ-45, Cold start function, Black	
Lot 3	Imprimanta color	-	-	-	Color/tehnologie laser, A4, min 60000 foi/luna, 4 culori, 1200x1200 dpi, min 20 foi/min, posibilitate de	-	
Lot 4	UPS	-	-	-	Line Interactive/600w/1000va/220-240V/AVR/CPU controlat, battery 12v/7A sau (7,2A), minim 2 puteri	-	
Lot 5	Scanner	-	-	-	Scanner, USB 3.0 compatibil cu 2.0, compatibilitate Windows 7/10 x32/x64, A4, 4800x4800,	-	
Lot 6	Memorie de stocare	-	-	-	USB Flash Drive 32 GB, USB 3.0 (Read-min 80 MB/s, Write-min 20 MB/s), material extern plastic dur	-	
Lot 7	Memorie de stocare	-	-	-	USB Flash Drive 128 GB, USB 3.0 (Read-min 80 MB/s, Write-min 15 MB/s), material extern plastic dur	-	
Lot 8	Memorie de stocare	-	-	-	2.5" SSD 256 GB, SATA III, citire și scriere minim 550/490 MB/s.	-	
Lot 9	Husă	-	-	-	Geantă de mână + curea pentru umăr adițional, rezistență la uzură, pentru Notebook, Compatibilitate:	-	
Lot 10	Cartus imprimantă original	-	-	-	Cartus original compatibil cu HP M602N, resursa de imprimare minim 20000 pagini.	-	
Lot 11	Căști	-	-	-	Headset over the hear with Microphone noise canceling, 3.5 mm plug x2 pcs, minim 2 m cable length,	-	
Lot 12	Adaptor	-	-	-	Adaptor IDE/SATA to USB.	-	
Lot 13	Cabluri USB	-	-	-	Cabluri USB 3.0 Extension, minim 1.8 m.	-	
Lot 14	Baterie BIOS	-	-	-	Battery 3V, CR2032.	-	
Lot 15	Marker	-	-	-	Marker permanent pentru CD/DVD, Plastic etc.	-	
Lot 16	Lavetă	-	-	-	Lavetă microfibră dimensiuni minim 25x25 cm, maxim 35x40 cm.	-	
Lot 17	Server	SR250	China	Lenovo	Chassis Rack 1U, included Sliding Rail Kit. CPU sockets 1, 6 x 3.4 GHz, Cores 6, 12M cache, 6C/12T, turbo (80W) Operating System Supported Microsoft® Windows Server®, Novell® SUSE® Linux Enterprise Server, Red Hat® Enterprise Linux VMware® ESX®. RAM 2x16 GB 2666MT/s DDR4 ECC UDIMM (4 UDIMM slots). HDD 4 HDD x 1,2 TB 10K RPM SAS 12Gbps 512n 2.5in Hot-plug Hard Drive. RAID Controllers plug-in card Interfețe SATA 6Gb/s SAS 12Gb/s. Suportă RAID level – 0,1,5,6,10,50,60. Network Controller Dual Port 1 GbE, Lan NIC 1GbE out-of-band-management. Power 2 hotplug PSU with support (1+1) redundancy, maximum 600W Management Out-of-band-management, separate 1GbE port, allows use of IPMI out-of-band interfaces such as IPMI over LAN (Power management, Remote console, Virtual media, Access via web interface), license Enterprise. Ports Front: one USB 2.0, Rear: Two USB 3.0; VGA; Serial connector. Others Parts Only Warranty 3 Years.	Chassis Rack 1U, included Sliding Rail Kit. CPU - Intel Xeon E-2236G 6C 80W 3.4GHz (6C/12T) Operating System Supported Microsoft® Windows Server®, Novell® SUSE® Linux Enterprise Server, Red Hat® Enterprise Linux VMware® ESX®. RAM 2x 16GB TruDDR4 2666MHz (2Rx8, 1.2V) UDIMM HDD 4 x ThinkSystem 2.5" 1.2TB 10K SAS 12Gb Hot Swap 512n HDD RAID ThinkSystem RAID 930-8i 2GB Flash PCIe 12Gb Adapter Interfețe SATA 6Gb/s SAS 12Gb/s. Suportă RAID level – 0,1,5,6,10,50,60. Network Controller Dual Port 1 GbE, Lan NIC 1GbE out-of-band-management. Power 2xThinkSystem 450W(230V/115V) Platinum Hot-Swap Power Supply Management Out-of-band-management, separate 1GbE port, allows use of IPMI out-of-band interfaces such as IPMI over LAN (Power management, Remote console, Virtual media, Access via web interface), license Enterprise. Front: 1x VGA port (optional), 1x USB 3.1 Gen 1 port, and 1x USB 2.0 port with XClarity Controller access. Rear: 1x VGA port, 2x USB 3.1 Gen 2 ports, 1x DB-9 serial port, and 1x RJ-45 10/100/1000 Mb Ethernet systems management port. Others Parts Only Warranty 3 Years.	

Semnat: _____

Nume: Eugeniu Cobilas

În calitate de: Director general

Ofertantul: „Accent Electronic” SA

Adresa: or. Chișinău, str. Bulgară 33/1

Data: 14.07.2020