

Mini Converter Audio to SDI 4K



Mini Converter Audio to SDI 4K includes everything you need to embed 4 channels of analog audio or 8 channels of AES/EBU digital audio into any SDI video connection. Now you can embed professional audio from devices such as audio mixers and analog decks into SDI video connections for use with SDI routers and decks or to add extra audio channels to video converters!

Connections

SDI Video Inputs

1 x SD, HD or 6G-SDI. 1 x ALT SDI Input for automatic switch over if main input fails.

SDI Video Outputs

1 x Embedded SDI Output.

Analog Audio Inputs

4 channels of professional balanced analog audio with standard 1/4 inch jack connections.

Digital Audio Inputs

8 channels of professional balanced digital with standard 1/4 inch jack connections.

SDI Redundant Input

Automatically switches over if main SDI input is lost.

Multi Rate Support


Auto detection SD, HD or 6G-SDI.

Updates and Configuration

Via USB 2.0 high speed. (480 Mb/s)

Reclocking

Yes



Standards

SD Video Standards

525i59.94 NTSC, 625i50 PAL

HD Video Standards

720p50, 720p59.94, 720p60,
1080p23.98, 1080p24, 1080p25,
1080p29.97, 1080p30, 1080p47.95,
1080p48, 1080p50, 1080p59.94,
1080p60, 1080PsF23.98, 1080PsF24,
1080PsF25, 1080PsF29.97,
1080PsF30, 1080i50, 1080i59.94,
1080i60

2K Video Standards

2Kp23.98 DCI, 2Kp24 DCI, 2Kp25 DCI,
2Kp29.97 DCI, 2Kp30 DCI,
2Kp47.95 DCI, 2Kp48 DCI, 2Kp50 DCI,
2Kp59.94 DCI, 2Kp60 DCI,
2KPsF23.98 DCI, 2KPsF24 DCI,
2KPsF25 DCI, 2KPsF29.97 DCI,
2KPsF30 DCI

Ultra HD Video Standards

2160p23.98, 2160p24, 2160p25,
2160p29.97, 2160p30

4K Video Standards

4Kp23.98 DCI, 4Kp24 DCI, 4Kp25 DCI,
4Kp29.97 DCI, 4Kp30 DCI

SDI Compliance

SMPTE 259M, SMPTE 292M,
SMPTE 296M, SMPTE 372M,
SMPTE ST-2081, ITU-R BT.656
and ITU-R BT.601

SDI Video Rates

SDI video inputs are automatically
detected between standard definition
and high definition.

SDI Video Sampling

4:2:2, 4:4:4

SDI Audio Sampling

Television standard sample rate of
48kHz and 24-bit.

SDI Color Precision

4:2:2, 4:4:4

SDI Color Space

YUV, RGB

SDI Auto Switching

Automatically selects between SD,
HD, 3G and 6G-SDI.

Software

Software Control

Mac™ and Windows™ software
upgrade via USB.

Internal Software Upgrade

Via included updater application.

Operating Systems



Mac 10.15 Catalina,
Mac 11.1 Big Sur or later.



Windows 10, 64-bit.

Settings Control

Mini Switches or USB software.

Power Requirements

Power Supply

+12V universal power supply included with international socket adapters for all countries. Cable tie point.

Power Consumption

8.40 Watts

Operational Voltage Range

12 - 31V DC

Physical Specifications



Environmental Specifications

Operating temperature

0° to 40° C (32° to 104° F)

Storage temperature

-20° to 45° C (-4° to 113° F)

Relative Humidity

0% to 90% non-condensing

What's Included

Mini Converter Audio to SDI 4K
12V universal power supply with international socket adapters

Warranty

3 Year Limited Manufacturer's Warranty.

All items on this website are copyright Blackmagic Design Pty. Ltd. 2023, all rights reserved. All trademarks are property of their respective owners. MSRP includes duties, but excludes sales tax and shipping costs. This website uses remarketing services to advertise on third party websites to previous visitors to our site. You can opt out at any time by changing cookie settings. [Privacy Policy](#)

Blackmagic Design Authorized Reseller