



ENDOASCULAR

Wide range of minimally invasive diagnostics devices dedicated to endovascular procedures
enabling treatment of peripheral artery disease.



COBALT-CHROMIUM PERIPHERAL STENT NEPTUN C

with OTW delivery system options



The Neptun C stent for peripheral vessels is made of L605 cobalt-chromium alloy manufactured using the state-of-the-art laser technology.

- Next generation stent design
- Stent delivery system provides good deliverability and placement accuracy
- Cobalt-chromium alloy (L605) structure provides excellent radial force and visibility
- Low profile
- High flexibility

NEPTUN C / (OTW) DELIVERY SYSTEM OPTION

Technical data overview

Stent material	cobalt-chromium alloy (L605)	Crossing profile	low
Radiopacity	very good	Nominal pressure	6 atm
MRI	MR Conditional	Delivery system length	110 cm
Radial force	excellent	Delivery system type	Over The Wire (OTW)
Pushability and trackability	very good		

Availability and specifications are subject to change. For more information, please contact your Balton sales representative.



PERIPHERAL STENTS
NEPTUN C – COBALT-CHROMIUM PERIPHERAL STENT

OVER THE WIRE (OTW) OPTION

Reference:	Nominal stent diameter [mm]	Nominal stent length [mm]	Use with guidewire [inch]	Use with introducer [F]	Catheter length [cm]
		C	E		
ZSTPCOTW 4x CE 110	4	16, 20, 25, 30, 35, 40, 45, 50, 55, 60, 65, 70, 75, 80, 85, 90, 100	0.018"	5	110
			0.025"	5	
			0.035"	6	
ZSTPCOTW 5x CE 110	5	16, 20, 25, 30, 35, 40, 45, 50, 55, 60, 65, 70, 75, 80, 85, 90, 100	0.025"	5	
			0.035"	6	
ZSTPCOTW 6x CE 110	6	16, 20, 25, 30, 35, 40, 45, 50, 55, 60, 65, 70, 75, 80, 85, 90, 100	0.025"	5	
			0.035"	6	
ZSTPCOTW 7x CE 110	7	16, 20, 25, 30, 35, 40, 45, 50, 55, 60, 65, 70, 75, 80, 85, 90, 100	0.035"	6	
ZSTPCOTW 8x CE 110	8	16, 20, 25, 30, 35, 40, 45, 50, 55, 60, 65, 70, 75, 80, 85, 90, 100	0.035"	6	
ZSTPCOTW 9x CE 110	9	16, 20, 25, 30, 35, 40, 45, 50, 55, 60, 65, 70, 75, 80, 85, 90, 100	0.035"	6	
ZSTPCOTW 10x CE 110	10	20, 25, 30, 35, 40, 45, 50, 55, 60, 65, 70, 75, 80, 85, 90, 100	0.035"	7	
ZSTPCOTW 12x CE 110	12	30, 40, 50, 60, 70, 80, 90, 100	0.035"	8	

When ordering use Ref. Number: ZSTPCOTW 8x2035110

NOTE: Catheters 80, 100, 110, 120 and 135 cm in length are also available for order. When ordering the catheter of other length, please substitute the length of 110 in the Ref. Number with the desired length e.g. ZSTPCOTW8x303580.

