

Pump
 Vacuum Pump



- Features:**
- * Oil free, clean exhausted air by built-in filter.
 - * Automatic cooling exhaust system ensures 24h operation continuously.
 - * The pressure adjustable design can satisfy a certain range of vacuum and gas velocity.
 - * TEFLON surface treatment, anti-gas corrosion.
 - * Orange look for anticorrosive vacuum pump.(eg: GM-0.33IIP, GM-0.5P, GM-0.5IIP, GM-1.0P)

Technical Parameters:

Model	GM-0.20	GM-0.5II	GM-0.5	GM-0.33II	GM-1.0
Pump Head	1	2	1	1	2
Speed of Evacuation	12L/Min	30L/Min	30L/Min	20L/Min	60L/Min
Ultimate Pressure	≥0.075Mpa	≥0.095Mpa	≥0.08Mpa	≥0.08Mpa	≥0.08Mpa
Vacuum	250mbar	50mbar	200mbar	200mbar	200mbar
Pressure	≥30 Psi	Negative pressure	≥30 Positive,	Negative pressure	≥30 Positive,
	Positive		Positive or		Positive or
	or negative		negative		negative
	pressure		pressure		pressure
Inlet	φ6mm	φ6mm	φ6mm	φ6mm	φ6mm
Outlet	φ6mm	Silencer	φ6mm	Silencer	φ6mm
Working Temp.	7-40℃				
Body Temp.	<55℃				
Noise	<60dB			<50dB	
Motor Power Consumption	75W	160W			
Power Supply	AC110/220V±10%, 50/60Hz				
Diaphragm	NBR				
Valves	/	NBR			
Net Weight(kg)	4	10	6.6	6.2	10
Gross Weight(kg)	4.5	11	7.6	7.5	11
External Size(L*W*H) mm	195*98*156	300*120*235	210*160*235	215*120*235	300*160*235
Package Size(L*W*H) mm	330*210*240	314*205*316	300*210*310	315*200*310	380*340*270